


guided drive DFM-80-125-P-A-KF

Part number: 170964

FESTO

With integrated guide.

The proximity switch, type SMTSO-8E, can be used with this product with stroke lengths equal to or greater than 50 mm. The corresponding mounting kit, type SMB-8E, is mounted inwardly or outwardly.



Data sheet

| Feature | Value |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------|
| Centre of gravity distance from working load to yoke plate | 125 mm |
| Stroke | 125 mm |
| Piston diameter | 80 mm |
| Operating mode of drive unit | Yoke |
| Cushioning | P: Flexible cushioning rings/plates at both ends |
| Assembly position | Any |
| Guide | Recirculating ball bearing guide |
| Design structure | Guide |
| Position detection | For proximity sensor |
| Operating pressure MPa | 0.05 ... 1 MPa |
| Operating pressure | 0.5 ... 10 bar |
| Max. speed | 0.4 m/s |
| Mode of operation | double-acting |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 0 - No corrosion stress |
| PWIS conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -5 ... 60 °C |
| Impact energy in end positions | 0.75 Nm |
| Max. force Fy | 2,048 N |
| Max. force Fy static | 3,120 N |
| Max. force Fz | 2,048 N |
| Max. force Fz static | 3,120 N |
| Max. torque Mx | 158.67 Nm |
| Max. torque Mx static | 241.8 Nm |
| Max. torque My | 100.35 Nm |
| Max. torque My static | 152.9 Nm |
| Max. torque Mz | 100.35 Nm |
| Max. torque Mz static | 152.9 Nm |
| Max. permissible torque load Mx as a function of the stroke | 29.83 Nm |
| Max. useful load as a function of the stroke at defined distance xs | 306 N |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), retracting | 2,827 N |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance | 3,016 N |
| Moving mass | 5,093 g |
| Product weight | 10,485 g |
| Centre of gravity of the moving mass as a function of the stroke | 84.1 mm |
| alternative connections | See product drawing |
| Pneumatic connection | G3/8 |
| Materials note | Conforms to RoHS |
| Material cover | Wrought Aluminium alloy |
| Material seals | NBR |
| Material housing | Wrought Aluminium alloy |
| Material piston rod | High alloy steel, non-corrosive |