position sensor SMH-S1-HGD16 Part number: 175713

Product to be discontinued

With Hall effect, for contactless detection with mini-grippers. Only functional in combination with evaluation unit SMH-AE1 or signal converter SVE4.



Data sheet

Feature	Value	
Design	for gripper	
CE mark (see declaration of conformity)	to EU directive for EMC	
	in accordance with EU RoHS directive	
UKCA marking (see declaration of conformity)	To UK instructions for EMC	
	To UK RoHS instructions	
Materials note	Conforms to RoHS	
Measured variable	Position	
Measuring principle	Hall magnetic	-
Ambient temperature	5 60 °C	
Short circuit strength	No	
Overload withstand capability	Not available	
Output signal	Analogue	
Polarity protected	No	
Electrical connection 1, connection type	Cable with plug	
Electrical connection 1, connection technology	M8x1, A-coded to EN 61076-2-104	
Electrical connection 1, number of pins/wires	4	
Material electrical contact	Brass, gold-plated	
Cable length	0.5 m	
Cable sheath colour	Grey	
Material cable sheath	TPE-U(PUR)	
Mounting type	Screwed on gripper	
Assembly position	Any	
Product weight	30 g	
Material housing	Wrought Aluminium alloy	
	Epoxy resin	
	Nickel-plated brass	
	POM	
	PUR	
Protection class	IP65	
Corrosion resistance classification CRC	2 - Moderate corrosion stress	
PWIS conformity	VDMA24364-B2-L	



FESTO