


short-stroke cylinder AEVC-10-10-A-P-A Part number: 188073 Product to be discontinued

For proximity sensing, piston-rod end with male thread.





FESTO



Data sheet

| Feature | Value |
|---|--|
| Stroke | 10 mm |
| Piston diameter | 10 mm |
| Spring return force, retracted | 3 N |
| Cushioning | P: Flexible cushioning rings/plates at both ends |
| Assembly position | Any |
| Mode of operation | single-acting |
| | pushing action |
| Design structure | Piston |
| | Piston rod |
| Position detection | For proximity sensor |
| Operating pressure MPa | 0.15 0.8 MPa |
| Operating pressure | 1.5 8 bar |
| | 21.75 116 psi |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further |
| | operation) |
| Corrosion resistance classification CRC | 1 - Low corrosion stress |
| PWIS conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -20 80 °C |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance | 41 N |
| Moving mass | 3.5 g |
| Product weight | 26 g |
| Mounting type | with through hole |
| | with accessories |
| | Optional |
| Pneumatic connection | M5 |
| Materials note | Conforms to RoHS |
| Material cover | Wrought Aluminium alloy |
| | Anodised |
| Material seals | NBR |
| | TPE-U(PU) |
| Material housing | Wrought Aluminium alloy |
| | Anodised |
| Material piston rod | High alloy steel |