

## short-stroke cylinder AEVC-12-5-I-P-A Part number: 188080 Product to be discontinued

For proximity sensing, piston-rod end with female thread. Type to be discontinued. Available until 2026. See Support Portal for alternative products.





**FESTO** 

## **Data sheet**

Feature	Value
Stroke	5 mm
Piston diameter	12 mm
Spring return force, retracted	4 N
Cushioning	P: Flexible cushioning rings/plates at both ends
Assembly position	Any
Mode of operation	single-acting
	pushing action
Design structure	Piston
	Piston rod
Position detection	For proximity sensor
Operating pressure MPa	0.15 1 MPa
Operating pressure	1.5 10 bar
	21.75 145 psi
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	1 - Low corrosion stress
PWIS conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 80 °C
Theoretical force at 0.6 MPa (6 bar, 87 psi), advance	59 N
Moving mass	8.4 g
Product weight	51 g
Mounting type	with through hole
	with accessories
	Optional
Pneumatic connection	M5
Materials note	Conforms to RoHS
Material cover	Wrought Aluminium alloy
	Anodised
Material seals	TPE-U(PU)
Material housing	Wrought Aluminium alloy
	Anodised
Material piston rod	High alloy steel