

CPE10SC-M1BH-5J-QS-4

Solenoid valve

Data sheet

Part no.: 192513

Page:1

Feature	Data/description
Switching function	5/2-way valve
Switching function short code	5/2
Direction of flow reversible	No
Operating principle	Slide
Shape of function component	Piston
With exhaust flow control	Yes
Type of regulation	Indirect
Control type	Bistable
Type of mounting	Screw
Installation position	Any
Nominal size	3 mm
Operating pressure min.	3 bar
Operating pressure max.	8 bar
Minimum ambient temperature	-5 °C
Maximum ambient temperature	50 °C
Minimum medium temperature	-5 °C
Maximum medium temperature	50 °C
Type of connection, air supply	Push-in
Nominal size of tubing connection, suppl	4
Air connection type power port	Push-in
Nominal size of tubing connection, worki	4
Type of connection, exhaust	Push-in
Nominal size of tubing connection,	4
Air connection type aux. pilot air suppl	Internal
Air connection type aux. pilot air exhau	Thread
Connecting thread for aux. pilot air exh	M 3
Type pilot control air Supply and exhaus	Internal pilot air, ducted pilot exhaust
Actuation/reset	Double solenoid
Manual override	Non-detenting (detenting with attachment)
Operating status display	No
Material of cap	PA-reinforced

CPE10SC-M1BH-5J-QS-4

Solenoid valve

Data sheet

Part no.: 192513

Page:2

Feature	Data/description
Material of housing	AL, die-cast metal
Material of seals	NBR-Elastomer
CT criterion	Free of copper and PTFE
Product weight	0,085 kg
Standard nominal flow rate 1 - 2	185 l/min
Standard nominal flow rate 2 - 3	185 l/min
Standard nominal flow rate 1 - 4	185 l/min
Standard nominal flow rate 4 - 3/5	185 l/min
Response time OFF/OVER (dom.)	8 ms
Voltage type	DC
Nominal voltage	24 V
Medium	Filtered compr. air (40 µm) (may be lubricated)
Degree of protection	IP65