

connecting cable

KMP6-15P-12-5



Part number: 527544

Classic - do not use for new projects

For valve terminal CPV-SC, with 15-pin Sub-D plug, 5 m long.

Modern alternatives can be found by entering the first four characters of the type code in the search field.

FESTO



Data sheet

| Feature | Value |
|--|--------------------------------------|
| Conforms to standard | DIN 41652 |
| Cable identification | Without inscription label holder |
| Connection frequency | 50 |
| Product weight | 585 g |
| Electrical connection 1, function | Field device side |
| Electrical connection 1, design | Angular |
| Electrical connection 1, connection type | Plug socket |
| Electrical connection 1, cable outlet | Straight |
| Electrical connection 1, connection technology | Sub-D |
| Electrical connection 1, number of pins/wires | 15 |
| Electrical connection 1, occupied pins/wires | 15 |
| Electrical connection 1, type of mounting | 2 screws 4-40 UNC |
| Electrical connection 2, function | Controller side |
| Electrical connection 2, connection type | Cable |
| Electrical connection 2, connection technology | Open end |
| Electrical connection 2, number of pins/wires | 15 |
| Electrical connection 2, occupied pins/wires | 15 |
| Operating voltage range DC | 0 ... 30 V |
| Nominal operating voltage DC | 24 V |
| Acceptable current load at 40°C | 2.8 A |
| Surge strength | 1 kV |
| Cable length | 5 m |
| Cable attribute | Standard |
| Test conditions of cable | Test conditions on request |
| Bending radius, fixed cable installation | ≥ 86 mm |
| Bending radius, flexible cable installation | ≥ 129 mm |
| Cable diameter | 8.6 mm |
| Cable diameter tolerance | ± 0,25 mm |
| Cable structure | 15x0,34 |
| Nominal conductor cross-section | 0.34 mm ² |
| Wire ends | Cut off bluntly |
| Protection class | IP40 |
| Note on degree of protection | in assembled condition |
| Ambient temperature | -25 ... 70 °C |
| Ambient temperature with flexible cable installation | -5 ... 70 °C |
| Storage temperature | -20 ... 75 °C |
| CE mark (see declaration of conformity) | in accordance with EU RoHS directive |
| UKCA marking (see declaration of conformity) | To UK RoHS instructions |
| PWIS conformity | VDMA24364-B2-L |
| Materials note | Conforms to RoHS |
| Degree of contamination | 2 |
| Material cable sheath | PVC |

| Feature | Value |
|-----------------------------|--------------------------|
| Cable sheath colour | Grey |
| Material housing | PBT-reinforced |
| Housing colour | Grey |
| Material screw-type lock | Nickel-plated brass |
| Material electrical contact | Gold-plated copper alloy |