
regulator plate VABF-S3-1-R2C2-C-10 Part number: 543535

For valve terminal VDMA-01/02, standard port pattern to 15407-1, up to 10 bar.



Data sheet

Feature	Value
Width	26 mm
Based on the standard	ISO 15407-1
Assembly position	Any
Pneumatic vertical stacking	Pressure regulator for 2
Controller function	Output pressure constant
	with secondary exhaust
Pressure gauge selection	possible
Pressure regulation range MPa	0.2 0.85 MPa
Pressure regulation range	2 8.5 bar
Pressure regulation range psi	29 123.25 psi
Inlet pressure 1	0.5 10 bar
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	0 - No corrosion stress
PWIS conformity	VDMA24364-B1/B2-L
Protection class	IP65
	NEMA 4
Ambient temperature	-5 50 °C
Product weight	305 g
Vertical stacking type of mounting	on manifold block
	on individual sub-base
Pressure gauge connection	with retaining clamp
Materials note	Conforms to RoHS
Material control panel	PA
Material regulator housing	Aluminium die cast



FESTO