
semi-rotary drive DRQD-B-20-180-YSRJ-A-AL-FW Part number: 563338 Product to be discontinued

for position sensing, with adjustable shock absorbers and play compensating gearing. supply port left.

Type to be discontinued. Available until 2018. See Support Portal for alternative products.







Data sheet

Feature	Value
Size	20
Setting range of swivel angle on both sides	-20 /+ 6 deg
Swivel angle	180 deg
Cushioning	YSRJ: Shock absorber, hard characteristic curve, adjustable
Assembly position	Any
Design structure	Rack and pinion
Max. number of intermediate positions	1
Position detection	For proximity sensor
Operating pressure	2 10 bar
Max. swivel frequency at 6 bar	1.8 Hz
Mode of operation	double-acting
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further
	operation)
Corrosion resistance classification CRC	1
Ambient temperature	-10 60 °C
Theoretical torque at 6 bar	3.1 Nm
Permissible mass moment of inertia	0.1 kgm2
Mounting type	Optional
	with through hole
	with internal (female) thread
Pneumatic connection	M5
Materials note	Free of copper and PTFE
Materials information for drive shaft	Heat-treatment steel
Materials information for cover	Aluminium
Materials information for seals	NBR
	TPE-U(PU)
Materials information, housing	Aluminium