

## solenoid valve **VUVG-B10-T32U-MZT-F-1P3**Part number: 574365

**FESTO** 

This type is suitable for vacuum.





## **Data sheet**

Feature	Value
Valve function	2x3/2 open, monostable
Type of actuation	electrical
Valve size	10 mm
Standard nominal flow rate	130 l/min
Operating pressure MPa	-0.09 1 MPa
Operating pressure	-0.9 10 bar
Design structure	Piston slide
Type of reset	mechanical spring
Authorisation	RCM Mark
	c UL us - Recognized (OL)
Protection class	IP40
	IP65
	with plug socket
Nominal size	1.7 mm
Exhaust-air function	throttleable
Sealing principle	soft
Assembly position	Any
Manual override	detenting
	Pushing
	Covered
Type of piloting	Piloted
Pilot air supply	external
Overlap	Positive overlap
Pilot pressure MPa	0.2 0.8 MPa
Pilot pressure	2 8 bar
Suitability for vacuum	Yes
Switching time off	11 ms
Switching time on	8 ms
Duty cycle	100 %
Max. positive test pulse with logic 0	700 μs
Max. negative test pulse with logic 1	900 µs
Characteristic coil data	24 V DC: 1 W
	24 V DC: low-current phase 0.3 W, high-current phase 1.0 W
Permissible voltage fluctuation	+/-10%
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Vibration resistance	Transport application test at severity level 2 in accordance with FN 942017-4 and EN 60068-2-6
Restriction ambient and medium temperature	Without holding current reduction -5 - 50 °C
Shock resistance	Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27
Corrosion resistance classification CRC	2 - Moderate corrosion stress



Feature	Value
PWIS conformity	VDMA24364-B1/B2-L
Medium temperature	-5 60 °C
Pilot medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Ambient temperature	-5 60 °C
Product weight	54 g
Electrical connection	Via electrical connection plate
Mounting type	on manifold rail
Materials note	Conforms to RoHS
Material seals	HNBR
	NBR
Material housing	Wrought Aluminium alloy