
## spindle axis ELGA-BS-KF-70-400-0H-10P-ML Part number: 8041819

With recirculating ball bearing guide



## **Data sheet**

| Feature                                                                    | Value                                   |
|----------------------------------------------------------------------------|-----------------------------------------|
| Working stroke                                                             | 400 mm                                  |
| Size                                                                       | 70                                      |
| Stroke reserve                                                             | 0 mm                                    |
| Spindle diameter                                                           | 12 mm                                   |
| Spindle pitch                                                              | 10 mm/U                                 |
| Assembly position                                                          | Any                                     |
| Guide                                                                      | Recirculating ball bearing guide        |
| Design structure                                                           | Electromechanical linear axis           |
|                                                                            | with recirculating ball bearing spindle |
| Motor type                                                                 | Stepper motor                           |
|                                                                            | Servomotor                              |
| Spindle type                                                               | Ball screw spindle                      |
| Measuring method: displacement encoder                                     | Incremental                             |
| Max. acceleration                                                          | 15 m/s2                                 |
| Max. speed                                                                 | 3,000 1/min                             |
|                                                                            | 0.5 m/s                                 |
| Repetition accuracy                                                        | ±0,02 mm                                |
| PWIS conformity                                                            | VDMA24364 zone III                      |
| Protection class                                                           | IP40                                    |
| Ambient temperature                                                        | -10 60 °C                               |
| Area moment of inertia 2nd degree ly                                       | 165E+03 mm4                             |
| Area moment of inertia 2nd degree Iz                                       | 472E+03 mm4                             |
| No-load torque at maximum travel speed                                     | 0.24 Nm                                 |
| No-load torque at minimum travel speed                                     | 0.17 Nm                                 |
| Max. force Fy                                                              | 1,500 N                                 |
| Max. force Fz                                                              | 1,850 N                                 |
| Fy with theoretical service life of 100 km (from a guide perspective only) | 5,520 N                                 |
| Fz with theoretical service life of 100 km (from a guide perspective only) | 6,808 N                                 |
| Max. torque Mx                                                             | 16 Nm                                   |
| Max. torque My                                                             | 132 Nm                                  |
| Max. torque Mz                                                             | 132 Nm                                  |
| Mx with theoretical service life of 100 km (from a guide perspective only  | 59 Nm                                   |
| My with theoretical service life of 100 km (from a guide perspective only) | 486 Nm                                  |
| Mz with theoretical service life of 100 km (from a guide perspective only) | 486 Nm                                  |
| Max. radial force at drive shaft                                           | 220 N                                   |
| Max. feed force Fx                                                         | 650 N                                   |
| Torsional mass moment of inertia It                                        | 28.3E+03 mm4                            |
| Mass moment of inertia JH per metre of stroke                              | 0.142 kgcm2                             |
| Mass moment of inertia JL per kg of working load                           | 0.0253 kgcm2                            |
| Mass moment of inertia, JO                                                 | 0.038 kgcm2                             |
| Feed constant                                                              | 10 mm/U                                 |
| Moving mass                                                                | 804 g                                   |
| Additional slide weight                                                    | 620 g                                   |
| Additional weight per 10 mm stroke                                         | 33 g                                    |

## **FESTO**



## FESTO

| Feature                                | Value                                 |  |
|----------------------------------------|---------------------------------------|--|
| Dynamic deflection (load moved)        | 0.05% of the axis length, max. 0.5 mm |  |
| Static deflection (load at standstill) | 0.1% of the axis length               |  |
| Material of end caps                   | Wrought Aluminium alloy               |  |
|                                        | Anodised                              |  |
| Material of profile                    | Wrought Aluminium alloy               |  |
|                                        | Anodised                              |  |
| Materials note                         | Conforms to RoHS                      |  |
| Material drive cover                   | Wrought Aluminium alloy               |  |
|                                        | Anodised                              |  |
| Material guide slide                   | Steel                                 |  |
| Material guide rail                    | Steel                                 |  |
| Material slide                         | Wrought Aluminium alloy               |  |
|                                        | Anodised                              |  |
| Material spindle nut                   | Steel                                 |  |
| Material spindle                       | Steel                                 |  |