



position transmitter SDAS-MHS-M40-1L-PNLK-PN-E-2.5-LE

Part number: 8063975

FESTO



Data sheet

Feature	Value
Design	for T-slot
Authorisation	RCM Mark c UL us - Listed (OL)
CE mark (see declaration of conformity)	to EU directive for EMC in accordance with EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
KC mark	KC-EMV
Certificate issuing department	UL E232949
Materials note	Conforms to RoHS Halogen-free
Instructions for use	Link: Drive-Sensor-Overview
Measured variable	Position
Measuring principle	Hall magnetic
Sensing range	$\leq 52,000 \mu\text{m}$
Ambient temperature	$-40 \dots 80 \text{ }^\circ\text{C}$
Typical scanning interval	2 ms
Max. travel speed	3 m/s
Travel resolution	$\leq 0.02 \text{ mm}$
Repetition accuracy	0.2 mm
Switch output	2x PNP or 2x NPN, adjustable
Switching element function	N/C or N/O contact, switchable
Switch-on time	$< 4 \text{ ms}$
Switch-off time	$< 4 \text{ ms}$
Max. switching frequency	125 Hz
Max. switching output voltage DC	30 V
Max. output current	50 mA
Max. contact rating DC	1.5 W
Voltage drop	$< 0.5 \text{ V}$
Typical linearity error in $\pm \text{mm}$	$\pm 1 \text{ mm}$
Short circuit strength	Yes
Overload withstand capability	Available
Protocol	I-Port IO-Link
IO-Link, protocol	Device V 1.1
IO-Link, profile	Smart sensor profile
IO-Link, function classes	Process Data Variable (PDV) Identification diagnosis Teach channel Switching signal channel (SSC)
IO-Link, communication mode	COM2 (38,4 kBaud)
IO-Link, SIO mode support	Yes
IO-Link, port type	A
IO-Link, process data width IN	2 Byte
IO-Link, process data content IN	12 bit PDV (position measured value)

Feature	Value
	4 bit SSC (switching signal)
IO-Link, minimum cycle time	2,5 ms
Operating voltage range DC	10 ... 30 V
Residual ripple	10 %
Idle current	< 12 mA
Polarity protected	for all electrical connections
Electrical connection 1, connection type	Cable
Electrical connection 1, connection technology	Open end
Electrical connection 1, number of pins/wires	4
Connector exit direction	axial
Test conditions of cable	Bending strength according to Festo standard Torsion resistance: > 300,000 cycles, ±270°/0.1 m Energy chain: > 5 million cycles, bending radius 28 mm
Cable length	2.5 m
Cable attribute	Suitable for energy chains/robot applications
Cable sheath colour	Grey
Material cable sheath	TPE-U(PUR)
Mounting type	Tightened Insertable in slot from above
Assembly position	Any
Product weight	27 g
Material housing	PA-reinforced High alloy steel, non-corrosive
Operating status display	Yellow LED
Status display	Red LED
Setting options	IO-Link Capacitive pushbutton
Ambient temperature with flexible cable installation	-20 ... 70 °C
Protection class	IP65 IP68
PWIS conformity	VDMA24364-B2-L
RSBP classification to CD-0033	F1a
Cleanroom class	ISO class 4