

angle seat valve

VZXA-B-TS6-20-M2-B1T-30-K-75-20-PM

Part number: 8111591

FESTO



Data sheet

| Feature | Value |
|--|---|
| Design structure | Poppet valve with piston actuator |
| Type of actuation | pneumatic |
| Assembly position | Any |
| Mounting type | Line installation |
| Line connection | G $\frac{3}{4}$ threaded collar to DIN ISO 228 |
| Valve function | 2/2 |
| Flow direction | non reversible |
| Pressure of medium | 0 ... 3 MPa |
| Medium pressure | 0 ... 30 bar |
| Type of reset | mechanical spring |
| Type of piloting | With external control |
| Pneumatic connection | Female thread G1/8 |
| Operating pressure MPa | 0.5 ... 0.7 MPa |
| Operating pressure | 5 ... 7 bar 72.5 ... 101.5 psi |
| Medium | Vapour Mineral oil-based hydraulic oil Inert gases Mineral oil Water Filtered compressed air, degree of filtration 200 μ m Neutral fluids |
| Flow direction | Below valve seat, for gaseous and liquid media |
| Control of the medium | On/off operation |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Max. viscosity | 600 mm ² /s |
| Medium temperature | -10 ... 180 °C |
| Ambient temperature | 0 ... 60 °C |
| Flow rate Kv | 11.8 m ³ /h |
| Outdoor use | C1 - weather protected locations of use |
| Materials note | Conforms to RoHS |
| PWIS conformity | VDMA24364 zone III |
| Material process valve housing | Brass |
| Material number, process valve housing | CW724R |
| Material seals | FPM |
| Material spindle seal | PTFE |
| Material seat seal | PTFE |
| Product weight | 2,448 g |
| Actuator size | 75 mm |
| Stroke | 20 mm |
| Control function | Closed via spring force, NC |
| Position detection | With mechanical indicator |
| Material drive housing | PA-reinforced |
| Storage temperature | -10 ... 60 °C |
| Protection class | IP65 IP67 |
| Material piston rod | High alloy steel, non-corrosive |
| Material cover | PA-reinforced |