

Standards-based cylinder DSBG-80-400-PPSA-N3 Part number: 1646795







Data sheet

f-adjusting pneumatic end-position cushioning 52 ead barrel imity sensor nded piston rod2 MPa bar bar citing seed air in accordance with ISO8573-1:2010 [7:4:4]
f-adjusting pneumatic end-position cushioning 52 ead od barrel imity sensor nded piston rod .2 MPa bar bar cating
f-adjusting pneumatic end-position cushioning 52 ead od barrel imity sensor nded piston rod .2 MPa bar bar cating
f-adjusting pneumatic end-position cushioning 52 ead od barrel imity sensor nded piston rod .2 MPa bar bar
barrel simity sensor ended piston rod and a barrel sections of the control of the
ead od barrel imity sensor inded piston rod2 MPa bar bar inded piston
ead od barrel imity sensor inded piston rod .2 MPa bar bar cating
barrel imity sensor inded piston rod2 MPa bar bar bar
barrel imity sensor nded piston rod2 MPa bar bar acting
barrel imity sensor nded piston rod2 MPa bar bar acting
mity sensor nded piston rod 2 MPa bar acting
mity sensor nded piston rod 2 MPa bar acting
nded piston rod 2 MPa bar acting
.2 MPa bar acting
bar acting
acting
ed operation possible (subsequently required for further
n)
erate corrosion stress
364-B1/B2-L
°C
rnal (female) thread
essories
s to RoHS
lie-cast aluminium
J)
Aluminum alloy
y steel
Ј)
J)
anodised wrought aluminium alloy
lvanized
ed steel
by steel