

Guide cylinder DFM-16-10-P-A-KF



Part number: 170907

★ Core product range

With integral guide.

The proximity switch, type SMTSO-8E, is not suitable for this product.

FESTO



Data sheet

Feature	Value
Centre of gravity distance from working load to yoke plate	50 mm
Stroke	10 mm
Piston diameter	16 mm
Operating mode of drive unit	Yoke
Cushioning	P: Flexible cushioning rings/plates at both ends
Assembly position	Any
Guide	Recirculating ball bearing guide
Design structure	Guide
Position detection	For proximity sensor
Operating pressure MPa	0.2 ... 1 MPa
Working pressure	2 ... 10 bar
Max. speed	0.8 m/s
Mode of operation	double-acting
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	0 - No corrosion stress
PWIS conformity	VDMA24364-B1/B2-L
Ambient temperature	-5 ... 60 °C
Impact energy in end positions	0.15 Nm
Max. force F _y	389 N
Max. force F _y static	415 N
Max. force F _z	389 N
Max. force F _z static	415 N
Max. torque M _x	8.95 Nm
Max. torque M _x static	9.55 Nm
Max. torque M _y	3.89 Nm
Max. torque M _y static	4.15 Nm
Max. torque M _z	3.89 Nm
Max. torque M _z static	4.15 Nm
Max. permissible torque load M _x as a function of the stroke	2.19 Nm
Max. useful load as a function of the stroke at defined distance x _s	45 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), retracting	90 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), advance	121 N
Moving mass	212 g
Product weight	426 g
Centre of gravity of the moving mass as a function of the stroke	13.4 mm
alternative connections	See product drawing
Pneumatic connection	M5
Materials note	Conforms to RoHS
Material cover	Wrought Aluminum alloy
Material seals	NBR
Material housing	Wrought Aluminum alloy
Material piston rod	High alloy steel, non-corrosive