
## Electrical pressure regulator MS6N-LRE

Part number: 535192

With NPT thread Type to be discontinued. Available until 2023. See Support Portal for alternative products.



## **Data sheet**

Overall data sheet – Individual values depend upon your configuration.

| Feature  | Value  |
|--|--|
| Size   | 6  |
| Series   | MS   |
| Assembly position                                | Any  |
|  | Preferably vertical  |
| Design structure                                 | Electrically adjustable pressure regulator                       |
| Short circuit strength                           | for all electrical connections                                   |
| Controller function                              | Output pressure constant   |
|  | with initial pressure compensation                               |
|  | with secondary exhaust   |
| Pressure gauge                                   | Optional   |
|  | With display and control unit                                    |
|  | with pressure gauge  |
| Operating pressure MPa                           | 0.08 2 MPa   |
| Working pressure                                 | 0.8 20 bar   |
| Pressure regulation range                        | 0.3 16 bar   |
| Max. pressure hysteresis                         | 0.25 bar   |
| Standard nominal flow rate                       | 2,200 7,500 l/min  |
| Analog output                                    | 0 - 10 V   |
|  | 4 - 20 mA  |
| Duration of control at 25°C                      | Max. 90 s  |
| Type of inputs                                   | Per IEC 61131-2  |
|  | No electrical isolation  |
| Nominal operating voltage DC                     | 24 V   |
| Current consumption at nominal operating voltage | Max. 1 A   |
| Current consumption                              | max 3.5 A at 24 V DC   |
| Control duration/ interval ratio                 | 1:3  |
| Permissible voltage fluctuation                  | +/- 10 %   |
| Authorization                                    | c UL us - Recognized (OL)  |
| CE symbol (see declaration of conformity)        | according to EU-EMV guideline                                    |
| Operating medium                                 | Compressed air in accordance with ISO8573-1:2010 [7:4:4]         |
|  | Inert gases  |
| Note on operating and pilot medium               | Lubricated operation possible (subsequently required for further |
|  | operation)   |
| Corrosion resistance classification CRC          | 2 - Moderate corrosion stress                                    |
| PWIS conformity                                  | VDMA24364-B2-L   |
| Storage temperature                              | -10 50 °C  |
| Food-safe  | See Supplementary material information                           |
| Medium temperature                               | 0 50 °C  |
| Protection class                                 | IP65   |
| Ambient temperature                              | 0 50 °C  |

**FESTO** 

## FESTO

| Feature                                    | Value                    |  |
|--|--------------------------|--|
| Product weight                             | 1,820 g                  |  |
| Analog outputs, absolute accuracy at 25° C | ± 3%                     |  |
| Cable interface                            | Input: M12x1 plug, 5-pin |  |
|  | Output: M8x1 plug, 3-pin |  |
| Mounting type                              | Line installation        |  |
|  | On subbase               |  |
|  | with wall/surface fixing |  |
|  | with accessories         |  |
|  | Optional                 |  |
| Material operator unit                     | PA                       |  |
| Material seals                             | NBR                      |  |
| Material housing                           | Aluminum die cast        |  |
| Material membrane                          | NBR                      |  |