
Retro-reflective sensor SOEG-RSP-M18W-PS-S-2L

Part number: 537700 Product to be discontinued

With polarized light, round design, with 90° angled beam Type to be discontinued. Available until 2024. See Support Portal for alternative products.



Data sheet

Feature	Value
Design	Round
Conforms to standard	EN 60947-5-2
Authorization	RCM Mark
	c UL us - Listed (OL)
CE symbol (see declaration of conformity)	according to EU-EMV guideline
Measured variable	Position
Measuring principle	Optoelectronic
Measurement method	Retro-reflective sensor
Type of light	Red, polarized
Working range	2,000 mm
Ambient temperature	-25 55 °C
Switch output	PNP
Switching element function	Dark switching
Max. switching frequency	1,000 Hz
Max. output current	200 mA
Voltage drop	<= 2 V
Short circuit strength	Pulsing
Operating voltage range DC	10 36 V
Residual ripple	20 %
Idle current	15 mA
Polarity protected	for all electrical connections
Electrical connection	3-pin
	M12x1
	Plug
Size	M18x1
Mounting type	with lock nut
Tightening torque	20 Nm
Product weight	56 g
Material housing	Brass
	Chromed-plated
Material of union nut	Brass
	Chromed-plated
Operating status display	Yellow LED
Operating reserve display	Green LED
Ambient temperature with flexible cable installation	-5 55 °C
Idle current Polarity protected Electrical connection Size Mounting type Tightening torque Product weight Material housing Material of union nut Operating status display Operating reserve display Ambient temperature with flexible cable installation Protection class	IP65
	IP67
Corrosion resistance classification CRC	1 - Low corrosion stress
PWIS conformity	VDMA24364-B2-L

FESTO

