
Pressure regulator LR-1/4-DB-7-MINI Part number: 539682 Product to be discontinued

Directly controlled regulator, working pressure up to 7 bar, with

Type to be discontinued. Available until 2024. See Support Portal for alternative products.



FESTO



Data sheet

| Feature | Value |
|---|--|
| Size | Mini |
| Width | 44 mm |
| Series | DB |
| Actuator lock | Rotary knob with lock |
| Assembly position | Any |
| Design structure | Pressure regulator with gauge |
| Controller function | with secondary exhaust |
| | with return flow |
| Pressure gauge | with pressure gauge |
| Operating pressure MPa | 0.1 1 MPa |
| Working pressure | 1.5 10 bar |
| Pressure regulation range | 0.5 7 bar |
| Max. pressure hysteresis | 0.5 bar |
| Standard nominal flow rate | >= 1,300 l/min |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further |
| | operation) |
| Corrosion resistance classification CRC | 1 - Low corrosion stress |
| PWIS conformity | VDMA24364-B1/B2-L |
| Air purity class at output | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Medium temperature | -5 50 °C |
| Ambient temperature | -5 50 °C |
| Product weight | 150 g |
| Mounting type | Front panel installation |
| | Line installation |
| | with through hole |
| | With mounting bracket |
| | Optional |
| Pressure gauge connection | G1/8 |
| Pneumatic connection, port 1 | G1/4 |
| Pneumatic connection, port 2 | G1/4 |
| Materials note | Conforms to RoHS |
| Material seals | NBR |
| Material rotary knob | POM |
| Material housing | PA-reinforced |