

One-way flow control valve VFOF-LE-BAH-G18-Q6 Part number: 8001459







Data sheet

| Feature | Value |
|---|---|
| Valve function | One-way flow control function for exhaust air |
| Pneumatic connection, port 1 | QS-6 |
| Pneumatic connection, port 2 | G1/8 |
| Type of actuation | manual |
| Pilot air port 21 | QS-6 |
| Adjusting element | Internal hex |
| Mounting type | Threaded |
| Standard nominal flow rate in flow control direction | 240 l/min |
| Standard nominal flow rate in non-return direction | 120 220 l/min |
| Working pressure | 0.2 10 bar |
| Pilot pressure | 2 10 bar |
| Ambient temperature | -10 60 °C |
| Material housing | PBT |
| Assembly position | Any |
| Type of actuation, controlled non-return function | pneumatic |
| Manual exhaust function | Pushing |
| Ability to swivel | 360° / no continuous swivelling permissible |
| Operating pressure complete temperature range | 0.2 10 bar |
| Standard flow rate in flow control direction 0.6->0 MPa (6->0 bar, 87->0 psi) | 420 l/min |
| Standard flow rate in non-return direction at 0.6->0 MPa (6->0 bar, 87->9 | 400 460 l/min |
| psi) actuated | |
| Standard flow rate in non-return direction at 0.6->0 MPa (6->0 bar, 87->0 | 400 460 l/min |
| psi) not actuated | |
| Standard nominal flow rate in non-return direction, actuated | 150 230 l/min |
| Standard nominal flow rate in non-return direction, unactuated | 120 220 l/min |
| Switching time off | 9 ms |
| Switching time on | 6 ms |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| PWIS conformity | VDMA24364-B1/B2-L |
| Medium temperature | -10 60 °C |
| Pilot medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Nominal tightening torque | 6 Nm |
| Tolerance for nominal tightening torque | ± 20 % |
| Permissible actuation moment, regulating screw | 1 Nm |
| Product weight | 28.6 g |
| Material of cover | ES-BE |
| Materials note | Conforms to RoHS |
| Material cover | PBT |
| Material seals | NBR |
| Material hollow bolt | Wrought Aluminum alloy |
| Material sleeve | Wrought Aluminum alloy |
| Material release ring | POM |
| Material adjusting screw | Brass |