


## 嚮導管路

# NEBC-S2G36-K-0.5-N-C2W36-S7

料號: 5105646

FESTO



## 技術參數

特性	值
Cable identification	Without inscription label holder
Electrical connection 1, function	Field device side
Electrical connection 1, design	有角的
Electrical connection 1, connection type	插頭
Electrical connection 1, cable outlet	直的
Electrical connection 1, connection technology	SCSI
Electrical connection 1, number of pins/wires	36
Electrical connection 1, occupied pins/wires	36
Electrical connection 2, function	Controller side
Electrical connection 2, design	有角的
Electrical connection 2, connection type	端子條
Electrical connection 2, cable outlet	直的
Electrical connection 2, connection technology	螺紋介面
Electrical connection 2, number of pins/wires	36
Electrical connection 2, occupied pins/wires	36
Electrical connection 2, type of mounting	On H-rail
工作電壓範圍 DC	0 ... 30 V
工作電壓範圍 AC	0 ... 30 V
在40°C時的可接受電流負載	1.5 A
浪湧強度	0.5 kV
電纜長度	0.5 m
電纜屬性	標準
Bending radius, fixed cable installation	>= 74 mm
Bending radius, flexible cable installation	>= 110 mm
電纜直徑	7.4 mm
電纜結構	18x2x0,09
導體的額定截面	0.09 mm <sup>2</sup>
防護等級	IP20
Note on degree of protection	裝配狀態
環境溫度	-40 ... 80 °C
CE 符號 (參見符合的標準)	in accordance with EU RoHS directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
PWIS conformity	VDMA24364 zone III
材料備註	符合 RoHS
污染程度	1
耐腐蝕等級 CRC	0 - No corrosion stress
Material cable sheath	PVC
電纜外套顏色	黑色
Material housing	PA PBT
外殼顏色	綠色 黑色
Material insulation	PVC