


# 電源插座 NEBU-G78W5-K-2-N-LE5

料號: 573855

FESTO



## 技術參數

特性	值
基於標準	NFPA/T3.5.29 R1-2007
Cable identification	Without inscription label holder
連接頻率	100
產品重量	680 g
Electrical connection 1, function	Field device side
Electrical connection 1, design	圓形
Electrical connection 1, connection type	插頭插座
Electrical connection 1, cable outlet	Angled
Electrical connection 1, note about the cable outlet	Cable outlet not according to industry standard. Matched with CPX protective hood.
Electrical connection 1, connection technology	G7/8 coded to NFPA/T3.5.29 R1-2007
Electrical connection 1, number of pins/wires	5
Electrical connection 1, occupied pins/wires	5
Electrical connection 1, type of mounting	Screw lock
Electrical connection 2, function	Controller side
Electrical connection 2, connection type	電纜
Electrical connection 2, connection technology	開放式終端
Electrical connection 2, number of pins/wires	5
Electrical connection 2, occupied pins/wires	5
工作電壓範圍 DC	0 ... 300 V
工作電壓範圍 AC	0 ... 300 V
在40°C時的可接受電流負載	9 A
浪湧強度	4 kV
電纜長度	2 m
電纜屬性	標準
電纜的測試條件	視需求的測試條件
Bending radius, fixed cable installation	>= 65 mm
電纜直徑	8.7 mm
電纜直徑公差	± 0,2 mm
電纜結構	5x1,5
導體的額定截面	1.5 mm <sup>2</sup>
防護等級	IP65 IP67
Note on degree of protection	裝配狀態
環境溫度	-20 ... 80 °C
CE 符號 (參見符合的標準)	根據 EU 低電壓設備指導原則
UKCA marking (see declaration of conformity)	To UK instructions for electrical equipment
PWIS conformity	VDMA24364-B2-L
材料備註	符合 RoHS
污染程度	3
耐腐蝕等級 CRC	1 - Low corrosion stress
Material cable sheath	TPE-U(PUR)
電纜外套顏色	黑色
Material housing	TPE-U(PUR)
外殼顏色	黑色
Material screw-type lock	Nickel-plated brass
Material electrical contact	Brass, gold-plated