


分氣塊

NEDU-L1R2-M12G5-M12LE-1R

料號: 8091516

FESTO



技術參數

特性	值
基於標準	EN 61076-2-101
設計結構	Y-distributor with cable on controller side
Distributor type	1 to 2
附加功能	Additional supply for port B
Cable identification	Without inscription label holder
連接頻率	100
產品重量	72.5 g
Electrical connection 1, function	Field device side
Electrical connection 1, design	圓形
Electrical connection 1, connection type	插頭插座
Electrical connection 1, cable outlet	直的
Electrical connection 1, connection technology	M12x1, A-coded in accordance with EN 61076-2-101
Electrical connection 1, number of pins/wires	5
Electrical connection 1, occupied pins/wires	5
Electrical connection 1, type of mounting	Screw-type lock with hex A/F 18 mm and longitudinal knurl
Electrical connection 2, function	Communication IO-Link
Electrical connection 2, design	圓形
Electrical connection 2, connection type	插頭
Electrical connection 2, cable outlet	直的
Electrical connection 2, connection technology	M12x1, A-coded in accordance with EN 61076-2-101
Electrical connection 2, number of pins/wires	3
Electrical connection 2, occupied pins/wires	3
Electrical connection 2, type of mounting	Screw-type lock with hex A/F 13 mm and longitudinal knurl
Electrical connection 3, function	額外電源供應
Electrical connection 3, connection type	2 single wires
Electrical connection 3, connection technology	開放式終端
Electrical connection 3, number of pins/wires	2
Electrical connection 3, occupied pins/wires	2
工作電壓範圍 DC	0 ... 30 V
額定工作電壓 DC	24 V
在40°C時的可接受電流負載	4 A
浪湧強度	0.8 kV
保護性接地	還未上市
Shielding	否
電纜長度	1 m
Cable length 1	1 m
Cable length 2	1 m
電纜屬性	用於靜態應用
Bending radius 1, fixed cable installation	>= 11.7 mm
Bending radius 2, fixed cable installation	>= 6 mm
Cable diameter 1	3.8 mm
Tolerance for cable diameter 1	± 0,1 mm
Cable diameter 2	1.75 mm
Tolerance for cable diameter 2	± 0,05 mm
Cable design 1	3x0,25

特性	值
Cable design 2	2x0,5
導體的額定截面	0.25 mm ² 0.5 mm ²
防護等級	IP65 IP68 IP69K
Note on degree of protection	IP40 for socket M12 裝配狀態
環境溫度	-30 ... 80 °C
儲藏溫度	-30 ... 80 °C
CE 符號 (參見符合的標準)	in accordance with EU RoHS directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
PWIS conformity	VDMA24364-B2-L
材料備註	符合 RoHS
污染程度	3
耐腐蝕等級 CRC	1 - Low corrosion stress
Material cable sheath	TPE-U(PUR)
電纜外套顏色	灰色
Material housing	PA TPE-U(PUR)
外殼顏色	黑色
Material screw-type lock	Nickel-plated brass Nickel-plated die-cast zinc
Material seals	NBR
Material electrical contact	Nickel-plated and gold-plated bronze Brass, gold-plated
Material insulation	PVC