
Solenoid valve **MN2H-5/3G-D-01-S-230AC** Part number: 161903


In accordance with ISO 15407/-1, with solenoid coil and manual override, without plug socket. Products to be discontinued. Available until 2009.



Data sheet

| Feature | Value |
|---|--|
| Valve function | 5/3 closed |
| Type of actuation | electrical |
| Width | 26 mm |
| Standard nominal flow rate | 1,000 l/min |
| Operating pressure | -0.9 16 bar |
| Design structure | Piston slide |
| Type of reset | mechanical spring |
| Protection class | IP65 |
| Nominal size | 8 mm |
| Grid dimension | 27 mm |
| Exhaust-air function | throttleable |
| Sealing principle | soft |
| Assembly position | Any |
| Conforms to standard | ISO 15407-1 |
| | VDMA 24563 |
| Manual override | with accessories, detenting |
| Type of piloting | Piloted |
| Pilot air supply | external |
| Flow direction | reversible |
| Pilot pressure | 3 10 bar |
| Switching time off | 52 ms |
| Switching time on | 23 ms |
| Characteristic coil data | 230 V AC: 60 Hz, switching power: 2 VA |
| Operating medium | filtered compressed air, grade of filtration 40 μm, lubricated or unlubricated |
| | Vacuum |
| Corrosion resistance classification CRC | 2 |
| Medium temperature | -10 50 °C |
| Pilot medium | filtered compressed air, grade of filtration 40 μm , lubricated or unlubricated |
| Ambient temperature | -10 50 °C |
| Product weight | 340 g |
| Electrical connection | Plug |
| | to DIN 43650 |
| | Design C |
| Mounting type | with through hole |
| Auxiliary pilot air port 12/14 | Sub-base VDMA 24563 size 1 |
| Pilot exhaust port 82/84 | Connection plate size 26 mm, according to ISO 15407-1 |
| | Sub-base VDMA 24563 size 1 |
| Pneumatic connection, port 1 | Connection plate size 26 mm, according to ISO 15407-1 |
| | Sub-base VDMA 24563 size 1 |
| Pneumatic connection, port 2 | Connection plate size 26 mm, according to ISO 15407-1 |

FESTO



FESTO

| Feature | Value |
|---------------------------------|---|
| | Sub-base VDMA 24563 size 1 |
| Pneumatic connection, port 3 | Connection plate size 26 mm, according to ISO 15407-1 |
| | Sub-base VDMA 24563 size 1 |
| Pneumatic connection, port 4 | Connection plate size 26 mm, according to ISO 15407-1 |
| | Sub-base VDMA 24563 size 1 |
| Pneumatic connection, port 5 | Connection plate size 26 mm, according to ISO 15407-1 |
| | Sub-base VDMA 24563 size 1 |
| Materials information for seals | NBR |
| Materials information, housing | Aluminium die cast |