
## Filter regulator PCRP-64-N14-7-C-R1-M-T18 Part number: 4787799



## **Data sheet**

| Feature   | Value  |
|---|--|
| Size  | 64   |
| Series  | P  |
| Actuator lock   | Adjusting screw with lock  |
| Mounting position                                     | Vertical +/-5°   |
| Grade of filtration                                   | 5 μm   |
| Condensate drain                                      | Manually rotating  |
| Design  | Filter regulator without pressure gauge  |
| Conforms to standard                                  | NACE MR0175/ISO 15156 (housing and bowl)   |
| Max. condensate volume                                | 30 cm <sup>3</sup>   |
| Controller function                                   | Via primary pressure compensation<br>With secondary venting  |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | Prepared for G1/4  |
| Operating pressure                                    | 0.1 MPa2 MPa<br>1 bar20 bar  |
| Pressure regulation range                             | 0.5 bar7 bar   |
| Max. pressure hysteresis                              | 0.2 bar  |
| Max. standard flow rate                               | 2410 l/min   |
| Standard nominal flow rate (standardised to DIN 1343) | 2040 l/min   |
| Explosion protection                                  | The information in the certificate must be observed!<br>Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [-:4:-]<br>Inert gases   |
| Note on operating and pilot medium                    | Lubricated operation possible (in which case lubricated operation will always be required)                                 |
| LABS (PWIS) conformity                                | VDMA24364 zone III   |
| Storage temperature                                   | -20 °C80 °C  |
| Air purity class at output                            | Compressed air to ISO 8573-1:2010 [6:4:4]  |
| Media temperature                                     | -20 °C80 °C  |
| Ambient temperature                                   | -20 °C80 °C  |
| Product weight  | 1965 g   |

## **FESTO**

| Feature                           | Value   |
|-----------------------------------|---|
| Type of mounting                  | Either:<br>In-line installation<br>Via mounting kit |
| Pressure gauge connection         | G1/4  |
| Pneumatic connection, port 1      | NPT1/4-18   |
| Pneumatic connection, port 2      | NPT1/4-18   |
| Material of drain screw           | High-alloy stainless steel                          |
| Material number of drain screw    | 1.4404/316L   |
| Material filter carrier           | Stainless steel casting                             |
| Material number of filter support | 1.4409/CF3M(316L)                                   |
| Note on materials                 | RoHS-compliant                                      |
| Material mounting bracket         | High-alloy stainless steel                          |
| Material seals                    | CR<br>NBR   |
| Material spring                   | High-alloy stainless steel                          |
| Material filter                   | High-alloy stainless steel                          |
| Material number of filter         | 1.4404/316L   |
| Material housing                  | Stainless steel casting                             |
| Material number housing           | 1.4409/CF3M(316L)                                   |
| Material adjusting screw          | High-alloy stainless steel                          |
| Material bowl                     | Stainless steel casting                             |
| Material number of bowl           | 1.4409/CF3M (316L)                                  |