

# Operator unit CDPX-X-E1-W-15

Part number: 8155218

FESTO



## Data sheet

Feature	Value
Width	422 mm
Mounting depth	56 mm
Height	267 mm
Length	64 mm
Max. front panel thickness	8 mm
Real-time clock	Yes
Supported PLC protocol	CoDeSys 3.X Modbus RTU client Modbus RTU server Modbus TCP client ModbusTCP server
Deviation, real-time clock	< 100 ppm bei 25°C
Number of colours	16 M
Display	With backlighting
Display type	TFT colour
Display characteristics	Touchscreen
Display size	15.6"
Backup battery	Rechargeable lithium battery
Operational voltage range DC	10 V...32 V
Display resolution	1366x768 pixels
Nominal operating voltage DC	24 V
Current consumption at nominal operating voltage	1.2 A
Approval	c UL us listed (OL)
CE mark (see declaration of conformity)	To EU EMC Directive In accordance with EU RoHS Directive
CE marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
LABS (PWIS) conformity	VDMA24364 zone III
Storage temperature	-20 °C...70 °C
Relative air humidity	5 - 85 % Non-condensing
Degree of protection	IP20 IP66

<b>Feature</b>	<b>Value</b>
Note on degree of protection	IP20 rear IP66 front
Ambient temperature	-20 °C...60 °C
Note on ambient temperature	for vertical mounting
Product weight	4100 g
SD card slot	1
Additional functions	RS232 communication function
Type of mounting	Front panel mounting
Note on materials	RoHS-compliant
Ethernet interface, connection type	Socket
Ethernet interface, connection system	RJ45
Ethernet interface, number of pins/wires	8
Ethernet interface, transmission rate	10/100 Mbit/s 1000 Mbps
Ethernet interface, function	Programming
Ethernet interface 2, type of connection	2x socket
Ethernet interface 2, connection technology	RJ45
Ethernet interface 2, number of pins/wires	8
Ethernet interface 2, transmission rate	10/100 Mbps
Ethernet interface 2, function	Programming
USB interface, function	File transfer
USB interface, type of connection	2 x socket
USB interface, connection technology	USB 2.0 type A
Programming software	Designer Studio
CPU data	2 GB RAM