
## Push-in T connector QST3-3/8T-5/16-U Part number: 153809

**FESTO** 

Rotatable 360°, 4 outlets.

This product is only available if ordered from the Festo Corporation, USA. Type to be discontinued. Available until 2011.



## **Data sheet**

| Feature                                 | Value                              |
|---|------------------------------------|
| Size                                    | Standard                           |
| Nominal size                            | 4.9 mm                             |
| Assembly position                       | Any                                |
| Design structure                        | Push/pull principle                |
| Container size                          | 1                                  |
| Working pressure                        | -0.95 10 bar                       |
| Temperature dependent working pressure  | -0.95 10 bar                       |
| Operating medium                        | Filtered compressed air            |
|   | Vacuum                             |
| Corrosion resistance classification CRC | 1                                  |
| Ambient temperature                     | -10 60 °C                          |
| Authorization                           | Germanischer Lloyd                 |
| Product weight                          | 33 g                               |
| Number of outputs                       | 4                                  |
| Number of supply lines                  | 1                                  |
| Pneumatic connection, supply line       | for tubing, 3/8" outside diameter  |
| Pneumatic connection, output            | for tubing, 3/8" outside diameter  |
|   | for tubing, 5/16" outside diameter |
| color of release ring                   | Grey                               |
| Materials note                          | Conforms to RoHS                   |
| Materials information, housing          | PBT                                |
| Release ring material data              | POM                                |
| Materials information for tubing seal   | NBR                                |
| Hose clamping segment material data     | High alloy steel, non-corrosive    |