
## Solenoid valve MN2H-5/2-D-01-S-110AC Part number: 161881

In accordance with ISO 15407/-1, with solenoid coil and manual override, without plug socket. Type to be discontinued. Available until 2009.



## **Data sheet**

Feature	Value
Valve function	5/2 single solenoid
Type of actuation	electrical
Width	26 mm
Standard nominal flow rate	1,000 l/min
Working pressure	-0.9 16 bar
Design structure	Piston slide
Type of reset	Air spring
Protection class	IP65
Authorization	Germanischer Lloyd
Nominal size	8 mm
Grid dimension	27 mm
Exhaust-air function	throttleable
Sealing principle	soft
Assembly position	Any
Conforms to standard	ISO 15407-1
	VDMA 24563
Manual override	with accessories, detenting
Type of piloting	Piloted
Pilot air supply	external
Flow direction	reversible
Pilot pressure	2 10 bar
Switching time off	43 ms
Switching time on	31 ms
Characteristic coil data	110 V AC: 50 Hz, switching power: 2 VA
Operating medium	filtered compressed air, grade of filtration 40 µm, lubricated or
	unlubricated
	Vacuum
Corrosion resistance classification CRC	2
Medium temperature	-10 50 °C
Pilot medium	filtered compressed air, grade of filtration 40 µm, lubricated or
	unlubricated
Ambient temperature	-10 50 °C
Product weight	270 g
Electrical connection	Plug
	to DIN 43650
	Design C
Mounting type	with through hole
Auxiliary pilot air port 12/14	Subbase VDMA 24563 size 1
Pilot exhaust port 82/84	Connection plate size 26 mm, according to ISO 15407-1
	Subbase VDMA 24563 size 1
Pneumatic connection, port 1	Connection plate size 26 mm, according to ISO 15407-1
	Subbase VDMA 24563 size 1

## **FESTO**



## FESTO

Feature	Value
Pneumatic connection, port 2	Connection plate size 26 mm, according to ISO 15407-1
	Subbase VDMA 24563 size 1
Pneumatic connection, port 3	Connection plate size 26 mm, according to ISO 15407-1
	Subbase VDMA 24563 size 1
Pneumatic connection, port 4	Connection plate size 26 mm, according to ISO 15407-1
	Subbase VDMA 24563 size 1
Pneumatic connection, port 5	Connection plate size 26 mm, according to ISO 15407-1
	Subbase VDMA 24563 size 1
Materials information for seals	NBR
Materials information, housing	Aluminum die cast