## Semi-rotary actuator DRE-14-F05-Q06-FS-O-PS Part number: 190077

**FESTO** 

Single-acting, air connection as per VDI/VDE 3845, Namur valves can be directly flange-mounted  $\,$ 

This product is only available if ordered from the Festo Corporation, USA.





## **Data sheet**

Feature	Value
Size of actuator	14
Flange hole pattern	F05
Swivel angle	90 deg
Fitting connection conforms to standard	ISO 5211
Cushioning	No cushioning
Assembly position	Any
Mode of operation	single-acting
Design structure	Rack and pinion
Position detection	No
Valve connection conforms to standard	VDI/VDE 3845 (NAMUR)
Operating pressure	2 10 bar
ATEX identification	II 2 GD c X
ATEX ambient temperature	-20°C <= Ta <= +60°C
Operating medium	Dried compressed air, lubricated or unlubricated
CE symbol (see declaration of conformity)	according to EU-Ex protection guideline (ATEX)
Corrosion resistance classification CRC	3
Ambient temperature	-20 80 °C
Air consumption at 6 bar per cycle 0°-90°-0°	61
Product weight	3,800 g
Shaft connection	V14
Pneumatic connection	Subbase
	G1/4
Materials note	Contains PWIS substances