


Positioning drive DNM-32- -

Part number: 528940

FESTO

With attached displacement encoder.



Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Stroke	100 ... 500 mm
Stroke shortening in the end-positions	≥ 10 mm
Smallest positioning stroke	3% of max. stroke However, not more than 20 mm
Piston diameter	32 mm
Based on the standard	ISO 15552 (previously also VDMA 24652, ISO 6431, NF E49 003.1, UNI 10290)
Cushioning	P: Flexible cushioning rings/plates at both ends
Mounting position, positioning	Any
Mounting position, soft stop	Horizontal
Measuring method: displacement encoder	Analog
Design structure	Piston Piston rod Profile barrel
Position detection	For proximity sensor With attached displacement encoder
Variants	Through piston rod through, hollow piston rod
Protection against torque/guide	Guide rod with yoke
Working pressure	4 ... 8 bar
Working pressure, positioning / soft stop	4 ... 8 bar
Max. travel speed	> 1.5 m/s
Min. travel speed	0.05 m/s
Typical short stroke positioning time, horizontal	0,35/0,55 s
Typical long stroke positioning time, horizontal	0,45/0,7 s
Recommended wiper current	< 1 µA
Mode of operation	double-acting
Max. operating voltage, DC	42 V
Max. intermittent wiper current	10 mA
Max. current consumption	4 mA
Nominal operating voltage DC	10 V
Connection resistance tolerance	20 %
Permissible voltage fluctuation	< 1 %
Operating medium	Compressed air in accordance with ISO8573-1:2010 [6:4:4]
Note on operating and pilot medium	Lubricated operation not possible
CE symbol (see declaration of conformity)	according to EU-EMV guideline
Corrosion resistance classification CRC	1
Protection class	IP54
Ambient temperature	-10 ... 80 °C
Impact energy in end positions	0.1 Nm
Max. load, horizontal	45 kg
Max. load, vertical	15 kg

Feature	Value
Min. load, horizontal	3 kg
Min. load, vertical	3 kg
Theoretical force at 6 bar, return stroke	415 N
Theoretical force at 6 bar, advance stroke	483 N
Moving mass with 0 mm stroke	198 g
Additional weight per 10 mm stroke	51 g
Basic weight for 0 mm stroke	650 g
Additional mass factor per 10 mm of stroke	11 g
Travel resolution	≤ 0.01 mm
Output signal	Analog
Temperature coefficient	≤ 5 ppm/K
Repetition accuracy, soft stop end-position	< 0,1 mm
Repetition accuracy, soft stop intermediate position	+/- 2 mm
Electrical connection, displacement encoder	4-pin
Mounting type	with accessories
Pneumatic connection	G1/8
Materials information for cover	Wrought Aluminum alloy
Materials information for seals	NBR TPE-U(PU)
Materials information for piston rod	High alloy steel
Material information, plug housing	PPE reinforced
Materials information for cylinder barrel	Wrought Aluminum alloy