


Micro filter MS9-LFM-N3/4-AUM-DA

Part number: 553094

FESTO



Data sheet

| Feature | Value |
|---|--|
| Series | MS |
| Size | 9 |
| Structural design | Fiber filter |
| Grade of filtration | 0.01 µm |
| Condensate drain | Manually rotating |
| Operating pressure | 0 bar...20 bar |
| Operating medium | Compressed air as per ISO 8573-1:2010 [6:8:4] |
| Air quality class at the output | Compressed air as per ISO 8573-1:2010 [1:7:2] |
| Max. standard flow rate for air quality class | 6500 l/min |
| Min. standard flow rate for air quality class | 325 l/min |
| Filter efficiency | 99.9999 % |
| Max. condensate volume | 225 ml |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Temperature of medium | -10 °C...60 °C |
| Ambient temperature | -10 °C...60 °C |
| Storage temperature | -10 °C...60 °C |
| Residual oil content | 0.01 mg/m ³ |
| Differential pressure display | Visual display |
| Type of mounting | Optionally: Line installation With accessories |
| Mounting position | Vertical +/- 5° |
| Pneumatic connection 1 | 3/4 NPT |
| Pneumatic connection 2 | 3/4 NPT |
| Housing material | Die-cast aluminum |
| Covering material | PA |
| Compressed air filter material | Borosilicate fiber |
| Material of bowl | Wrought aluminum alloy |
| Inspection window material | PA |

| Feature | Value |
|----------------|--------|
| Seals material | NBR |
| Product weight | 2000 g |