



Utikač SEA-GS-7

Broj artikla: 18666

FESTO

za ventilske blokove.



Tehnički podaci

Svojstvo	Vrednost
Zasnovano na normi	EN 61076-2-101
Vrsta pričvršćenja	sa navojnom šipkom
Cable outlet	Ravno
Težina proizvoda	17 g
Electrical connection 1, design	okruglo
Electrical connection 1, connection type	Utikači
Electrical connection 1, connection technology	M12x1, A-coded in accordance with EN 61076-2-101
Electrical connection 1, number of pins/wires	4
Electrical connection 1, type of mounting	Screw-type lock with longitudinal knurl
Electrical connection 2, connection technology	Vijčana stezaljka
Electrical connection 2, number of pins/wires	4
Područje pogonskog napona DC	0 ... 250 V
Područje pogonskog napona AC	0 ... 250 V
Strujna opteretivost kod 40°C	4 A
Čvrstoća na udarno naprezanje	2,5 kV
Navojni spoj kabla	Pg7
Prečnik kabla	3,3 ... 6 mm
Dozvoljeni prečnik kabla	4 ... 6 mm
Nazivni presek provodnika	0,14 ... 0,75 mm ²
Mehanička zaštita	IP67
Note on degree of protection	u montiranom stanju
Temperatura okoline	-40 ... 85 °C
CE znak (vidi izjavu o usklađenosti)	prema EU-niski napon-smernica
UKCA marking (see declaration of conformity)	To UK instructions for electrical equipment
PWIS conformity	VDMA24364-B2-L
Materijal - napomena	RoHS komformnost
Stepen zagađenja	3
Klasa korozione otpornosti KBK	2 - Moderate corrosion stress
Material housing	PBT
Boja kućišta	crno
Material screw-type lock	PBT
Material seals	CR FPM
Material electrical contact	Mesing Bela obložena bronza