

Standardni cilindar DSBG-320- -P-N3

Broj artikla: 3178601

FESTO



Prikaz primera



Tehnički podaci

Svojstvo	Vrednost
Hod	1 ... 2.250 mm
Prečnik klipa	320 mm
Navoj klipnjače	M48x2
Prigušivanje	P: elastični prigušni prsteni/ploče obostrano
Položaj ugradnje	proizvoljno
Kraj klipnjače	Spoljašnji navoj
Konstruktivna struktura	Klip Klipnjača Vučna motka Cev cilindra
Varijante	jednostrana klipnjača
Operating pressure MPa	0,06 ... 1 MPa
Pogonski pritisak	0,6 ... 10 bar
Način funkcionisanja	dvosmerno
Pogonski medijum	Kompresovani vazduh prema ISO 8573-1:2010 [7:4:4]
Napomena o mediju pogona i upravljanja	Nauljeni pogon je moguć (u daljnjem pogonu potreban)
Klasa korozione otpornosti KBK	2 - Moderate corrosion stress
PWIS conformity	VDMA24364-B1/B2-L
Temperatura okoline	-20 ... 80 °C
Energija naleta u krajnjim položajima	12,6 J
Theoretical force at 0.6 MPa (6 bar, 87 psi), retracting	46.385 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), advance	48.255 N
Pokretna masa kod hoda 0 mm	16.912 g
Dodatni faktor mase po 10 mm hoda	249 g
Osnovna težina kod hoda 0 mm	50.231 g
Dodatna težine po 10 mm hoda	623 g
Vrsta pričvršćenja	sa unutrašnjim navojem sa priborom po izboru:
Pneumatski priključak	G1
Materijal - napomena	RoHS komfornost
Material cover	Die-cast aluminium, coated
Material piston seal	NBR
Material piston	Die-cast aluminium
Material piston rod	visokolegirani čelik
Material piston rod wiper seal	NBR
Buffer seal material	TPE-U(PU)
Cushion piston material	POM
Material cylinder barrel	Smooth-anodised wrought aluminium alloy
Material nut	Čelik, pocinkovan
Material bearing	Metal polymer compound
Collar nut material	Galvanised steel
Material tie rod	visokolegirani čelik