



## 連接電纜

### NEBS-L1G4-K-1-N-M12G4

料號: 8091514

FESTO



## 技術參數

特性	值
Cable identification	Without inscription label holder
連接頻率	100
產品重量	40 g
Electrical connection 1, function	Field device side
Electrical connection 1, design	有角的
Electrical connection 1, connection type	插頭插座
Electrical connection 1, cable outlet	直的
Electrical connection 1, connection technology	Connection pattern L1J
Electrical connection 1, number of pins/wires	4
Electrical connection 1, occupied pins/wires	4
Electrical connection 1, type of mounting	Snap-in locking
Electrical connection 2, function	Controller side
Electrical connection 2, design	圓形
Electrical connection 2, connection type	插頭
Electrical connection 2, cable outlet	直的
Electrical connection 2, connection technology	M12x1, A-coded in accordance with EN 61076-2-101
Electrical connection 2, number of pins/wires	4
Electrical connection 2, occupied pins/wires	4
Electrical connection 2, type of mounting	Screw-type lock with hex A/F 13 mm and longitudinal knurl
工作電壓範圍 DC	0 ... 30 V
在40°C時的可接受電流負載	1 A
浪湧強度	0.8 kV
電纜長度	1 m
電纜屬性	標準
電纜的測試條件	視需求的測試條件
Bending radius, fixed cable installation	$\geq 14$ mm
Bending radius, flexible cable installation	$\geq 46$ mm
電纜直徑	4.5 mm
電纜直徑公差	$\pm 0,1$ mm
電纜結構	4x0,25
導體的額定截面	0.25 mm <sup>2</sup>
防護等級	IP65 IP67 IP69K
Note on degree of protection	IP40 for plug connection pattern L1J 裝配狀態
環境溫度	-20 ... 60 °C
Ambient temperature with flexible cable installation	-5 ... 60 °C
儲藏溫度	-20 ... 60 °C
CE 符號 (參見符合的標準)	in accordance with EU RoHS directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
PWIS conformity	VDMA24364-B2-L
材料備註	符合 RoHS 不含鹵素
污染程度	2
耐腐蝕等級 CRC	2 - Moderate corrosion stress

特性	值
Material cable sheath	TPE-U(PUR)
電纜外套顏色	灰色
Material housing	PA TPE-U(PUR)
外殼顏色	黑色 白色
Material screw-type lock	Nickel-plated brass
Material electrical contact	Tin-plated bronze Brass, gold-plated
Material insulation	PP