


Automation system CPX-E /-EX1E

Broj artikla: 5237644

FESTO



Prikaz primera

Tehnički podaci

Ukupni list podataka - Pojedinačne vrednosti zavise od Vaše konfiguracije.

Svojstvo	Vrednost
Električno aktiviranje	Fieldbus integrisani kontroler
Mera mreže	18,9 mm
Vrsta pričvršćenja	sa H - profilom
Maks. broj modula	10
Temperatura okoline	-5 ... 50 °C
Note on ambient temperature	-5 - 60°C for vertical installation
Temperatura ležaja	-20 ... 70 °C
Relativna vlažnost vazduha	95 % ne kondenzira se
Mehanička zaštita	IP20
Klasa korozione otpornosti KBK	0 - No corrosion stress
Otpornost na vibracije	Transport application test with severity level 1 as per FN 942017-4 and EN 60068-2-6
Udarna čvrstoća	Shock test with severity level 1 in accordance with FN 942017-5 and EN 60068-2-27
Zaštita od direktnog i indirektnog dodira	Protective extra-low voltage with safe disconnection (PELV)
PWIS conformity	VDMA24364 zone III
CE znak (vidi izjavu o usklađenosti)	prema EU-EMV-smernici prema EU-Ex-zaštita-smernica (ATEX) in accordance with EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK EX instructions To UK RoHS instructions
KC mark	KC-EMV
Dozvola	RCM Mark c UL us - Listed (OL)
Odobrenje Eksplozivne zaštite izvan EU	EPL Gc (GB)
Mesto izdavanja sertifikata	UL E239998
Material housing	PA
Dijagnoza	via bus via LED Module-specific
Maksimalna zapremina adrese za ulaze	64 Byte
Maksimalna zapremina adrese za izlaze	64 Byte
Interno vreme ciklusa	< 1 ms
Nominal operating voltage DC for electronics/sensors	24 V
Permissible voltage fluctuations for electronics/sensors	± 25 %
Maks. Napajanje	8 A
Premošćenje kvara mreže	10 ms
Zaštita od zamene polova	Da