


Spojni vod VMPA-KMS1-8-10

Broj artikla: 533197

FESTO

za multipol priključak na ventilski blok MPA-S.



Tehnički podaci

| Svojstvo | Vrednost |
|--|--------------------------------------|
| Zasnovano na normi | DIN 41652 |
| Cable identification | sa priborom |
| Frekvencija priključivanja | 50 |
| Težina proizvoda | 956 g |
| Electrical connection 1, function | Field device side |
| Electrical connection 1, design | ugaono |
| Electrical connection 1, connection type | Utičnica |
| Electrical connection 1, cable outlet | Angled |
| Electrical connection 1, connection technology | Sub-D |
| Electrical connection 1, number of pins/wires | 25 |
| Electrical connection 1, occupied pins/wires | 9 |
| Electrical connection 1, type of mounting | 3x M3 screws |
| Electrical connection 2, function | Controller side |
| Electrical connection 2, connection type | Kabl |
| Electrical connection 2, connection technology | otvoreni kraj |
| Electrical connection 2, number of pins/wires | 10 |
| Electrical connection 2, occupied pins/wires | 9 |
| Područje pogonskog napona DC | 0 ... 30 V |
| Nazivni pogonski napon DC | 24 V |
| Dozvoljeno strujno opterećenje | 3 A |
| Čvrstoća na udarno naprezanje | 1 kV |
| Dužina kabla | 10 m |
| Svojstvo kabla | Standard |
| Uslovi ispitivanja kabla | Uslovi ispitivanja na zahtev |
| Bending radius, fixed cable installation | 28,6 mm |
| Bending radius, flexible cable installation | 71,5 mm |
| Navojni spoj kabla | M20x1,5 |
| Prečnik kabela | 7,15 mm |
| Odstupanje prečnika kabla | ± 0,3 mm |
| Struktura kabla | 10x0,34 |
| Nazivni presek provodnika | 0,34 mm ² |
| Krajevi žica | Cut off bluntly |
| Mehanička zaštita | IP65 prema IEC 60529 |
| Note on degree of protection | u montiranom stanju |
| Temperatura okoline | -25 ... 80 °C |
| Temperatura okoline kod pokretnog postepenja kablova | -5 ... 70 °C |
| CE znak (vidi izjavu o usklađenosti) | in accordance with EU RoHS directive |
| UKCA marking (see declaration of conformity) | To UK RoHS instructions |
| PWIS conformity | VDMA24364-B2-L |
| Materijal - napomena | RoHS komformnost |
| Stepen zagađenja | 3 |
| Klasa korozione otpornosti KBK | 2 - Moderate corrosion stress |
| Material cable sheath | PVC |

| Svojstvo | Vrednost |
|-----------------------------|--------------------------|
| Boja izolacije | sivo |
| Material housing | PA |
| Boja kućišta | sivo |
| Material of union nut | PA |
| Material seals | CR NBR |
| Material electrical contact | Gold-plated copper alloy |