



# Spojni vod NEBV-S1WA44-K-2.5-N-LE44-S9

Broj artikla: 575420

FESTO



## Tehnički podaci

| Svojstvo   | Vrednost                             |
|--|--------------------------------------|
| Zasnovano na normi                                   | DIN 47100                            |
| Cable identification                                 | Without inscription label holder     |
| Frekvencija priključivanja                           | 50                                   |
| Težina proizvoda                                     | 460 g                                |
| Electrical connection 1, function                    | Field device side                    |
| Electrical connection 1, design                      | ugaono                               |
| Electrical connection 1, connection type             | Utičnica                             |
| Electrical connection 1, cable outlet                | Angled                               |
| Electrical connection 1, connection technology       | Sub-D                                |
| Electrical connection 1, number of pins/wires        | 44                                   |
| Electrical connection 1, occupied pins/wires         | 44                                   |
| Electrical connection 1, type of mounting            | 2 screws 4-40 UNC                    |
| Electrical connection 2, function                    | Controller side                      |
| Electrical connection 2, connection type             | Kabl                                 |
| Electrical connection 2, connection technology       | otvoreni kraj                        |
| Electrical connection 2, number of pins/wires        | 44                                   |
| Electrical connection 2, occupied pins/wires         | 44                                   |
| Područje pogonskog napona DC                         | 0 ... 30 V                           |
| Strujna opteretivost kod 40°C                        | 0,86 A                               |
| Čvrstoća na udarno naprezanje                        | 2,4 kV                               |
| Zaštita od zamene polova                             | Da                                   |
| Dužina kabla   | 2,5 m                                |
| Svojstvo kabla                                       | Standard                             |
| Uslovi ispitivanja kabla                             | Uslovi ispitivanja na zahtev         |
| Bending radius, fixed cable installation             | ≥ 42 mm                              |
| Bending radius, flexible cable installation          | ≥ 126 mm                             |
| Navojni spoj kabla                                   | M20x1,5                              |
| Prečnik kabela                                       | 10,2 mm                              |
| Odstupanje prečnika kabla                            | ± 0,3 mm                             |
| Struktura kabla                                      | 44x0,14                              |
| Nazivni presek provodnika                            | 0,14 mm <sup>2</sup>                 |
| Krajevi žica   | Cut off bluntly                      |
| Mehanička zaštita                                    | IP65<br>IP67                         |
| Note on degree of protection                         | u montiranom stanju                  |
| Temperatura okoline                                  | -35 ... 80 °C                        |
| Temperatura okoline kod pokretnog postepenja kablova | -5 ... 80 °C                         |
| Temperatura ležaja                                   | -35 ... 80 °C                        |
| CE znak (vidi izjavu o usklađenosti)                 | in accordance with EU RoHS directive |
| UKCA marking (see declaration of conformity)         | To UK RoHS instructions              |
| PWIS conformity                                      | VDMA24364-B2-L                       |
| Materijal - napomena                                 | RoHS komformnost                     |
| Stepen zagađenja                                     | 3                                    |
| Klasa korozione otpornosti KBK                       | 2 - Moderate corrosion stress        |
| Material cable sheath                                | PVC                                  |
| Boja izolacije                                       | sivo                                 |

| Svojstvo                    | Vrednost            |
|-----------------------------|---------------------|
| Material housing            | PA66-GF30           |
| Boja kućišta                | crno                |
| Material screws             | Čelik               |
| Material seals              | NBR                 |
| Material electrical contact | Bronza<br>pozlačeno |
| Material insulation         | PVC                 |