

Compact cylinders ADN/AEN, to ISO 21287

FESTO



Compact cylinders ADN/AEN, to ISO 21287


Key features

FESTO

Sensor slots on three sides for flush mounting of proximity sensors

Piston rod with choice of male or female thread

Mounting option: Female thread and through-hole



Centring hole in the end cap matches centring pins ZBS

Magnet for contactless position sensing

Integrated cushioning rings for absorbing residual energy at high speeds and machine cycles

More than the standard

- Series ADN/AEN compact cylinders comply with the standard ISO 21287
- The ADN/AEN is distinguished by its compact design and broad area of application thanks to the large number of variants
- The variants can be configured according to individual needs thanks to the modular product system

Powerful

- Flexible cushioning rings as standard for absorbing the residual energy facilitate high speeds and machine cycles
- Long service life thanks to exceptional cushioning characteristics and minimal friction factors
- The ADNP with bearing and end caps made of polymer and integrated QS push-in fittings is distinguished by its low weight

Convenient


- Easy to mount with a comprehensive range of mounting accessories for just about every type of installation
- Highly flexible thanks to the wide range of variants
- Contactless position sensing using proximity sensors

Reliable


- Optimised manufacturing methods, patented technology and more than 40 years of experience in the field of cylinders make Festo and ADN/AEN a great team

Mounting options


With through screw



Direct mounting



Size




- Space savings of up to 50% compared with the standard ISO 15552

Compact cylinders ADN, to ISO 21287

FESTO

Key features

Variants from the modular system		
Symbol	Key features	Description
	S1 Reinforced piston rod	Increased lateral forces. Absorbs many times more lateral force than a basic cylinder
	S2 Through piston rod	For working at both ends with the same forces in the advance and return stroke, for attaching external stops
	S6 Heat-resistant seals	Temperature resistance up to max. 120 °C
	S10 Constant (slow speed) operation at low piston speeds	Suitable for slow stroke movements at a constant, judder-free speed over the full stroke of the cylinder. Seal contains silicone grease (not free of paint-wetting impairment substances)
	S11 Low friction	The special seals considerably reduce system wear. This corresponds to a considerably lower response pressure. Seal contains silicone grease (not free of paint-wetting impairment substances)
	S20 Through, hollow piston rod	For carrying vacuum, small parts, media, etc.
	K2 Extended male piston rod thread	–
	K5 Special piston rod thread	Metric standard thread to ISO
	K8 Extended piston rod	–
	K10 Smooth anodised aluminium piston rod	Ideal for use in welding environments: – Protection against welding spatter – Small moving loads – Harder surface compared to steel – Long service life
	KP With clamping unit	Integrated clamping unit on the piston rod
	EL With end position lock	Positive lock in the end position as drop guard. If there is a drop in pressure, the piston rod is secured in its end position to prevent it from dropping
	Q Square piston rod	Protection against torsion. For correctly oriented feeding
	R3 High corrosion protection	All external cylinder surfaces comply with corrosion resistance class 3 to Festo standard 940 070. The piston rod is made from corrosion and acid resistant steel
	R8 Dust protection	–
	TL Captive rating plate	Laser etched rating plate. For easy identification when it comes to replacement, even after years in a harsh environment
	TT Low temperature	Temperature resistance up to max. –40 °C



- - Note

Software tools and configuration of
Festo product modules
→ www.festo.com

Compact cylinders ADN, to ISO 21287

Product range overview

FESTO

Function	Version	Type	Piston Ø	Stroke		Position sensing	Cushioning
			[mm]				
Double-acting	Basic version						
		ADN	12	5, 10, 15, 20, 25, 30, 40	1 ... 300	■	■
			16	5, 10, 15, 20, 25, 30, 40, 50	1 ... 300		
			20, 25	5, 10, 15, 20, 25, 30, 40, 50, 60	1 ... 300		
			32, 40, 50	5, 10, 15, 20, 25, 30, 40, 50, 60, 80	1 ... 400		
			63	10, 15, 20, 25, 30, 40, 50, 60, 80	1 ... 400		
			80, 100	10, 15, 20, 25, 30, 40, 50, 60, 80	1 ... 500		
			125	–	1 ... 500		
		ADN-...-S2 Through piston rod	12, 16, 20, 25	–	1 ... 300	■	■
			32, 40, 50	–	1 ... 400		
			63, 80, 100, 125	–	1 ... 500		
	Reinforced piston rod						
		ADN-...-S1	25	–	5 ... 300	■	■
			40, 63	–	10 ... 400		
			100	–	10 ... 500		
	Non-rotating with square piston rod						
		ADN-...-Q	12, 16, 20, 25	–	1 ... 300	■	■
			32, 40, 50, 63	–	1 ... 400		
			80, 100, 125	–	1 ... 500		
		ADN-...-Q-S2 Through piston rod	12, 16, 20, 25	–	1 ... 300	■	■
			32, 40, 50, 63	–	1 ... 400		
			80, 100, 125	–	1 ... 500		
	Standard port pattern, with clamping unit						
		ADN-...-KP 	20, 25	–	10 ... 300	■	■
			32, 40, 50, 63		10 ... 400		
			80, 100		10 ... 500		
	Standard port pattern, with end position lock						
		ADN-...-EL 	20, 25	–	10 ... 300	■	■
			32, 40, 50, 63		10 ... 400		
			80, 100		10 ... 500		
	With polymer end cap						
		ADNP 	20, 25	5, 10, 15, 20, 25, 30, 40, 50, 60	–	■	■
			32, 40, 50	10, 15, 20, 25, 30, 40, 50, 60, 80			



Compact cylinders ADN, to ISO 21287

Product range overview




FESTO

Type	Male piston rod thread	Female piston rod thread	Through, hollow piston rod	Extended male piston rod thread	Special thread	Extended piston rod	Smooth anodised piston rod	Heat-resistant seals up to max. 120 °C	Slow speed (constant motion)	Low friction	High corrosion protection	Dust protection	Low temperature	→ Page/Internet
	A	I	S20	K2	K5	K8	K10	S6	S10	S11	R3	R8	TT	
Basic version														
ADN	■	■	■ Ø 16 and above	■	■	■	■ Ø 20 and above	■	■	■	■	■ Ø 20 and above	■ Ø 20 ... 100	13
ADN-...-S2 Through piston rod	■	■	-	■	■	■	-	■	-	-	-	-	■ Ø 20 ... 100	13
Reinforced piston rod														
ADN-...-S1	■	■	-	■	■	■	-	■	-	-	■	-	-	13
Non-rotating with square piston rod														
ADN-...-Q	■	■	■ Ø 16 and above	■	■	■	-	■	-	-	-	-	-	13
ADN-...-Q-S2 Through piston rod	■	■	■ Ø 16 and above	■	■	■	-	■	-	-	-	-	-	13
Standard port pattern, with clamping unit														
ADN-...-KP	■	■	-	■	■	■	-	-	-	-	-	-	-	38
Standard port pattern, with end position lock														
ADN-...-EL	■	■	-	■	■	■	-	-	-	-	-	-	-	45
With polymer end cap														
ADNP	■	■	-	-	-	-	-	-	-	-	-	-	-	67

Compact cylinders ADN, to ISO 21287

Product range overview

FESTO

Function	Version	Type	Piston Ø	Stroke	Position sensing	Cushioning	
			[mm]	[mm]			A
Double-acting	Standard port pattern, non-rotating with yoke						
		ADNGF	12	5, 10, 15, 20, 25, 30, 40 	1 ... 200		
			16	5, 10, 15, 20, 25, 30, 40, 50 	1 ... 200		
			20, 25	5, 10, 15, 20, 25, 30, 40, 50, 60 	3 ... 200		
			32, 40, 50	5, 10, 15, 20, 25, 30, 40, 50, 60, 80 	5 ... 300		
			63, 80	10, 15, 20, 25, 30, 40, 50, 60, 80 	5 ... 300		
			100	10, 15, 20, 25, 30, 40, 50, 60, 80 	5 ... 400		
		ADNGF-...-S2 Through piston rod	12, 16	–	1 ... 200		
			20, 25		3 ... 200		
			32, 40, 50, 63, 80, 100		5 ... 250		
	Standard port pattern, high-force cylinder						
		ADNH	25	–	1 ... 150		
			40				
			63				
			100				
	Standard port pattern, multi-position cylinder						
		ADNM	25	–	1 ... 2000		
			40				
			63				
			100				

Compact cylinders ADN, to ISO 21287

Product range overview


FESTO

Type	Male piston rod thread	Female piston rod thread	Extended male piston rod thread	Special thread	Extended piston rod	Heat-resistant seals up to max. 120 °C	→ Page/Internet
	A	I	K2	K5	K8	S6	
Standard port pattern, non-rotating with yoke							
ADNGF	-	-	-	-	-	■	4
ADNGF-...-S2 Through piston rod	-	-	-	-	-	■	4
Standard port pattern, high-force cylinder							
ADNH	■	■	■	■	■	■	39
Standard port pattern, multi-position cylinder							
ADNM	■	■	■	■	■	■	8

Compact cylinders AEN, to ISO 21287

Product overview

FESTO

Function	Version	Type	Piston Ø	Stroke	Position sensing	Cushioning
			[mm]	[mm]	A	P
Single-acting	Basic version					
		AEN	12	1 ... 10	■	■
			16, 20, 25, 32, 40, 50, 63, 80, 100	1 ... 25		
		AEN-...-Z pulling	12	1 ... 10	■	■
			16, 20, 25, 32, 40, 50, 63, 80, 100	1 ... 25		
	Non-rotating with square piston rod					
		AEN-...-Q	16	1 ... 25	■	■
			20, 25, 32, 40, 50, 63, 80, 100	1 ... 25		

Compact cylinders AEN, to ISO 21287

Product overview


FESTO

Type	Male piston rod thread	Female piston rod thread	Extended male piston rod thread	Special piston rod thread	Extended piston rod	Smooth anodised piston rod	Heat-resistant seals up to max. 120 °C	→ Page/Internet
	A	I	K2	K5	K8	K10	S6	
Basic version								
AEN	■	■	■	■	■	■ Ø 20 and above	■	53
AEN-...-Z pulling	■	■	■	■	■	■ Ø 20 and above	■	53
Non-rotating with square piston rod								
AEN-...-Q	■	■	■	■	■	–	■	53

Compact cylinders ADN/AEN, to ISO 21287

Peripherals overview

FESTO



Compact cylinders ADN/AEN, to ISO 21287

Peripherals overview

FESTO

Mounting attachments and accessories		
	Brief description	→ Page/Internet
1	Foot mounting HNA	71
2	Flange mounting FNC	72
3	Swivel flange SNCL	73
4	Swivel flange SNCB	77
5	Clevis foot LBN/CRLBN	76
6	Multi-position kit DPNA	75
7	Trunnion flange ZNCF/CRZNG	78
8	Trunnion support LNZG	79
9	Swivel flange SNCS	74
10	Clevis foot LBG	74
11	Rod eye SGS/CRSGS	80
12	Coupling piece KSG/KSZ	80
13	Adapter AD	80
14	Rod clevis SG/CRSG	80
15	Self-aligning rod coupler FK	80
16	Right-angle clevis foot LQG	81
17	Rod clevis SGA	80
18	Proximity sensor SME/SMT-8	83
19	Proximity sensor SME/SMT-8M	83
20	Slot cover ABP-5-S	83
21	Proximity sensor SMPO-8E	83
22	Mounting kit SMB-8E	83
23	One-way flow control valve GRLA/GRLZ	81
24	Push-in fitting QS	quick star

Compact cylinders ADN, to ISO 21287

Type codes

FESTO


		ADN	–	50	–	50	–	A	–	P	–	A	–	S2
Type														
Double-acting														
ADN	Compact cylinder													
Piston Ø [mm]														
Stroke [mm]														
Piston rod thread														
A	Male thread													
I	Female thread													
Cushioning														
P	Flexible cushioning rings/pads at both ends													
Position sensing														
A	Via proximity sensor													
Variant														
Q	Square piston rod													
S1	Reinforced piston rod													
S2	Through piston rod													
S20	Through, hollow piston rod													
K2	Extended male piston rod thread													
K5	Special piston rod thread													
K8	Extended piston rod													
K10	Smooth anodised piston rod													
S6	Heat-resistant seals up to max. 120 °C													
S10	Slow speed (constant motion)													
S11	Low friction													
R3	High corrosion protection													
R8	Dust protection													
TL	Captive rating plate (laser etched)													
TT	Low temperature													

Compact cylinders ADN, to ISO 21287

Technical data

FESTO

Function





Variants → 3



Ø - Diameter
12 ... 125 mm

█ - Stroke length
1 ... 500 mm

www.festo.com



General technical data											
Piston Ø	12	16	20	25	32	40	50	63	80	100	125
Constructional design	Piston										
	Piston rod										
	Cylinder barrel										
Cushioning	Flexible cushioning rings/pads at both ends										
Position sensing	Via proximity sensor										
Type of mounting	Via through-holes										–
	Via female threads										
	Via accessories										
Mounting position	Any										

Technical data – Basic version and variants							
Piston Ø	12	16	20	25	32	40	
Pneumatic connection	M5	M5	M5	M5	G¼	G¼	
Female piston rod thread	M3	M4	M6	M6	M8	M8	
K5	–	–	M5	M5	M6	M6	
Male piston rod thread	M5	M6	M8	M8	M10x1.25	M10x1.25	
K5	M6	M8	M10, M10x1.25	M10, M10x1.25	M10, M12	M10, M12	
Max. torsional backlash of piston rod [°]	Q	2	1.8	1.6	1.6	1.2	1.2

Piston Ø	50	63	80	100	125
Pneumatic connection	G¼	G¼	G¼	G¼	G¼
Female piston rod thread	M10	M10	M12	M12	M16
K5	M8	M8	M10	M10	–
Male piston rod thread	M12x1.25	M12x1.25	M16x1.5	M16x1.5	M20x1.5
K5	M12, M16	M12, M16	M16, M20	M16, M20, M20x1.5	M20
Max. torsional backlash of piston rod [°]	Q	1	0.8	0.8	0.8

Compact cylinders ADN, to ISO 21287

Technical data

FESTO

Technical data – Variant S1					
Piston Ø		25	40	63	100
Pneumatic connection		M5	M5	G1/8	G1/8
Piston rod thread	Female	M6	M10	M12	M16
	Male	M8	M12x1.25	M16x1.5	M20x1.5
Special thread variant K5	Female	M5	M8	M10	–
	Male	M10, M10x1.25	M10x1.25, M12	M12x1.25, M16	M16x1.5, M20

Operating and environmental conditions													
Piston Ø		12	16	20	25	32	40	50	63	80	100	125	
Operating medium		Filtered compressed air, lubricated or unlubricated											
Operating pressure [bar]		1 ... 10		0.6 ... 10									
	Q	1.3 ... 10		1 ... 10		0.8 ... 10			0.6 ... 10				
	S1	–			1 ... 10	–	1 ... 10	–	1 ... 10	–	1 ... 10	–	
	S2, S20	1.5 ... 10	1.3 ... 10	1.2 ... 10		1 ... 10			0.8 ... 10				
	S6	1 ... 10		0.6 ... 10									
	S11	0.45 ... 10				0.25 ... 10							
	R8, TT	–		1,5 ... 10			1 ... 10			–			
	Ambient temperature ¹⁾ [°C]		–20 ... +80										
	S6	0 ... +120											
	R3	–20 ... +80											
	TT	–		–40 ... +80								–	
Corrosion resistance class CRC ²⁾		2											
	R3	3											

1) Note operating range of proximity sensors

2) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Corrosion resistance class 3 to Festo standard 940 070

Components with heavy corrosion exposure. Externally visible components in direct contact with normal industrial atmosphere or media such as solvents and cleaning agents, where the surface requirement is predominantly functional.

Forces [N] and impact energy [J]												
Piston Ø		12	16	20	25	32	40	50	63	80	100	125
Theoretical force at 6 bar, advancing		68	121	188	295	483	754	1178	1870	3016	4712	7363
	S1	–	–	–	295	–	754	–	1870	–	4712	–
	S2	51	90	141	247	415	686	1057	1750	2827	4524	7069
Theoretical force at 6 bar, retracting		51	90	141	247	415	686	1057	1750	2827	4524	7069
	S1	–	–	–	247	–	633	–	1681	–	4417	–
	S2	51	90	141	247	415	686	1057	1750	2827	4524	7069
Max. impact energy at the end positions		0.07	0.15	0.2	0.3	0.4	0.7	1	1.3	1.8	2.5	3.3
	S1	–	–	–	0.3	–	0.7	–	1.3	–	2.5	–
	S6	0.035	0.075	0.1	0.15	0.2	0.35	0.5	0.65	0.9	1.25	1.75
	K10	–	–	0.16	0.24	0.32	0.56	0.8	1	1.4	2	2.6
	S20	–	0.016	0.024	0.083	0.15	0.39	0.48	0.62	0.8	0.9	0.95

Permissible impact velocity:

$$v_{\text{perm.}} = \sqrt{\frac{2 \times E_{\text{perm.}}}{m_{\text{dead}} + m_{\text{load}}}}$$

$v_{\text{perm.}}$ Permissible impact velocity

$E_{\text{perm.}}$ Max. impact energy

m_{dead} Moving load (drive)

m_{load} Moving work load

Maximum permissible load:

$$m_{\text{load}} = \frac{2 \times E_{\text{perm.}}}{v^2} - m_{\text{dead}}$$



Note

These specifications represent the maximum values which can be reached. Note the maximum permitted impact energy.


Compact cylinders ADN, to ISO 21287

Technical data

FESTO


Max. lateral force F_q as a function of the projection x

Ø 12 ... 63



— Ø 12
 - - - Ø 16
 - - - Ø 20
 - - - Ø 25
 - - - Ø 32/40
 - - - Ø 50/63

Ø 80 ... 125



- - - Ø 80/100
 - - - Ø 125

Compact cylinders ADN, to ISO 21287


Technical data

FESTO

Max. lateral force F_q as a function of the projection x and the lever arm a


Q – Square piston rod

Ø 12




— $a = 5$ mm
 - - - $a = 10$ mm
 - - - $a = 15$ mm
 - - - $a = 20$ mm
 - - - $a = 25$ mm
 - - - $a = 30$ mm

Ø 16




— $a = 5$ mm
 - - - $a = 10$ mm
 - - - $a = 15$ mm
 - - - $a = 20$ mm
 - - - $a = 25$ mm
 - - - $a = 30$ mm

Ø 20/25



— $a = 5$ mm
 - - - $a = 10$ mm
 - - - $a = 15$ mm
 - - - $a = 20$ mm
 - - - $a = 25$ mm
 - - - $a = 30$ mm

Ø 32/40



— $a = 10$ mm
 - - - $a = 20$ mm
 - - - $a = 30$ mm
 - - - $a = 40$ mm
 - - - $a = 50$ mm
 - - - $a = 60$ mm

- Note

• Torques on the piston rod are to be excluded with projections greater than those shown in the graphs.

• If $a = 0$, the corresponding lateral load line of the basic ADN version can be used (→ 15).

Compact cylinders ADN, to ISO 21287


Technical data

FESTO

Max. lateral force F_q as a function of the projection x and the lever arm a


Q – Square piston rod

Ø 50/63




----- a = 10 mm
 a = 20 mm
 ----- a = 30 mm
 ----- a = 40 mm
 ----- a = 50 mm
 ----- a = 60 mm

Ø 80/100



----- a = 10 mm
 a = 20 mm
 ----- a = 30 mm
 ----- a = 40 mm
 ----- a = 50 mm
 ----- a = 60 mm

Ø 125



----- a = 10 mm
 a = 20 mm
 ----- a = 30 mm
 ----- a = 40 mm
 ----- a = 50 mm
 ----- a = 60 mm

- Note

• Torques on the piston rod are to be excluded with projections greater than those shown in the graphs.

• If $a = 0$, the corresponding lateral load line of the basic ADN version can be used (→ 15).


Compact cylinders ADN, to ISO 21287

Technical data

FESTO

Max. lateral force F_q as a function of the projection x

S1 – Reinforced piston rod




Weight [g]

Piston Ø	12	16	20	25	32	40	50	63	80	100	125
Product weight with 0 mm stroke	77	79	131	156	265	346	540	722	1300	2154	2880
Additional weight per 10 mm stroke	12	14	21	23	30	37	51	59	79	98	117
Moving load with 0 mm stroke	9	15	30	50	60	80	140	180	400	570	1080
Additional load per 10 mm stroke	2	4	6	6	9	9	16	16	25	25	39

Materials

Sectional view



Compact cylinder	Basic version, Q	S6, S10, S11	R3	K10
1 Cover	Anodised aluminium			
2 Cylinder barrel	Anodised aluminium			
3 Piston rod	High-alloy steel			Anodised aluminium
4 Flange screws	Ø 12 ... 16	High-alloy steel	High-alloy steel	–
	Ø 20 ... 25	Galvanised steel	High-alloy steel	Galvanised steel
	Ø 32 ... 63	Galvanised steel	Steel, zinc flake coating	Galvanised steel
	Ø 80 ... 125	Standard screws, galvanised steel	Standard screws, high-alloy steel	Standard screws, galvanised steel
– Seals	Polyurethane	Fluoro elastomer	Polyurethane	

Compact cylinders ADN, to ISO 21287


Technical data

FESTO


Dimensions – Basic version

Download CAD data → www.festo.com

Ø 12 ... 63



Ø 80 ... 125



Ø [mm]	BG	D1 Ø H9	D5 Ø F9	E	EE	G	J2	J3	L2 max.	L3 +0.2	MM Ø	PL +0.2	RT	T2 +0.1	TG ±0.2	ZJ +1	≡C1 h13
12	17	9	6	27.5+0.3	M5	10.5	2	—	35	3.5	6	6	M4	2.1	16	39.2	5
16				29+0.3		11	2.6				8				18	39.9	7
20	35.5+0.3		12	37		10			M5	22	42.7				9		
25	39.5+0.3			39	26		44.7										
32	27		9	47+0.3	G1/8	15	6	44	5	12	M6	32.5	50.2		10		
40				54.5+0.3			8	45				38	51.2				
50		12	65.5+0.3	49		16	M8	46.5		53.2	13						
63			75.5+0.3	56.5				57.2									
80	17	12	15	95.5+0.6		16.5	11.5	54	2.6	20	M10	72	63	17			
100	21.5			113.5+0.6		21.5		20	67			2.6	89		76		
125	20		—	134.6+0.3	G3/4	20	21.15	81	—	25	10.5	M12	110	92	21		

Compact cylinders ADN, to ISO 21287



Technical data

FESTO

Dimensions – Variants



Download CAD data → www.festo.com

Basic version





+ = plus stroke length

R8 – Dust protection / TT – Low temperature




+ = plus stroke length

S2 – Through piston rod



+ = plus stroke length
++ = plus 2x stroke length

S20 – Through, hollow piston rod



+ = plus stroke length
++ = plus 2x stroke length

Compact cylinders ADN, to ISO 21287

Technical data

Ø [mm]	AF min.	AM −0.5	B Ø R8/TT	D7 Ø	D8	D9	L5	KF	KK	T4	VD R8/TT	WH		ZJ		ZM
												+1	+1 R8/TT		R8/TT	
12	8	10	−	−	−	−	−	M3	M5	1.5	−	4.2	−	39.2	−	43.4
16	10	12		4.5		3.2	3	M4	M6			4.9		39.9		44.8
20	14	16	18	6		3.8	2	M6	M8	2.6	5.2	5.7	10.85	42.7	48.2	48.4
25														44.7	50.2	50.4
32	16	19	27	8		4.5	3	M8	M10x1.25	3.3	6.4	6.2	12.55	50.2	56.4	56.4
40														51.2	57.4	57.4
50	20	22	31	10		6	3.5	M10	M12x1.25	4.7		8.2	14.65	53.2	59.4	61.4
63														57.2	63.4	65.4
80	20	28	35	−	G1/8	8	−	M12	M16x1.5	6.1		9	15.4	63	69.4	71
100					G1/4									76	82.4	84
125					G1/4									92	−	103

Compact cylinders ADN, to ISO 21287


Technical data

FESTO

Dimensions – Variants



Download CAD data → www.festo.com

K2 – Extended male piston rod thread





+ = plus stroke length

K5 – Special piston rod thread



+ = plus stroke length

K8 – Extended piston rod



- Note
Piston rod extension is performed at one end in combination with the S2/S20 variants (at the square piston rod in combination with the Q variant).

+ = plus stroke length

Ø	A1	A2	A3	AM	K1	K2	KK	T3	WH	ZJ	
[mm]			min.	−0.5					+1	+1	
12	1 ... 10	1 ... 300	−	10	M6	−	M5	−	4.2	40	
16				12	M8		M6		4.85		
20	12		16	M10	M5	M8	2	5.65	43		
25				M10x1.25					M10	45	
				M10x1.25							
32	1 ... 20	1 ... 400	14	19	M10	M6	M10x1.25	2.6	6.15	50	
40					M12					M12	51
					M10						
					M12						
50			16	22	M12	M8	M12x1.25	3.3	8.25	53	
63	M16	M12			57						
	M12										
	M16										
80	1 ... 30	1 ... 500	20	28	M16	M10	M16x1.5	4.7	9	63	
100					M20						
					M20x1.5						
					M16					76	
					M20						
	M20x1.5										
125	1 ... 40	−	40	M20	−	M20x1.5	−	10.8	92		

Compact cylinders ADN, to ISO 21287


Technical data

FESTO


Dimensions – Variants

Download CAD data → www.festo.com


Q – Square piston rod



Q-S2 – Square, through piston rod



Q-S20 – Square, through, hollow piston rod



Ø	AF	AM	B1 □	D7 Ø	D8	D9	KF	KK	L5	T4	WH	ZJ	ZM	
[mm]	min.	-0.5									+1	+1		
12	8	10	5.5	–	–	–	M3	M5	3	1.5	4.2	39.2	43.4	
16	10	12	7	4.5		3.2	M4	M6			4.9	39.9	44.8	
20	12	16	9	6		3.8	M5	M8	2	2	5.7	42.7	48.4	
25												44.7	50.4	
32	14	19	10	8		4.5	M6	M10x1.25	3	2.6	6.2	50.2	56.4	
40												51.2	57.4	
50	16	22	12	10		6	M8	M12x1.25	3.5	3.3	8.2	53.2	61.4	
63												57.2	65.4	
80	20	28	16	–		G1/8	8.5	M10	M16x1.5	–	4.7	9	63	71
100							8.8						76	84
125	24	40	20		G1/4	11.5	M12	M20x1.5		6.1	11	92	103	

Compact cylinders ADN, to ISO 21287

Technical data


FESTO

Dimensions – Variants

Download CAD data → www.festo.com


S1 – Reinforced piston rod

Ø 25



+ = plus stroke length


Ø 40 ... 100




- 1 Cylinder advancing
- 2 Cylinder retracting

+ = plus stroke length

S1 – Reinforced piston rod



S1-K5 – Extended piston rod with special piston rod thread



Compact cylinders ADN, to ISO 21287

Technical data

FESTO

Ø	A3	AF	AM	B Ø	BG	D1 Ø	E	EE	J3	K2	KF	KK	L2
[mm]	min.	min.	−0.5	F8	min.	H9	+0.3						
25	12	14	16	22	15	9	39.5	M5	–	M5	M6	M8	39
40	16	20	22	35	16		54.5		15	M8	M10	M12x1.25	45
63	20		28	42		12	75.5	G½	23	M10	M12	M16x1.5	49
100	–	25	40	55	17		113.5		40	–	M16	M20x1.5	67

∅ [mm]	L3	MM ∅	PM	RT	T2	T3	T4	TG	VD	WH +1.3	ZJ	≈G1 h13
25	5	10	6	M5	2.1	2	2.6	26	6	11.65	50.65	9
40		16	8.2	M6		3.3	4.7	38	9.5	17.75	62.75	13
63		20		M8	2.6	4.7	6.1	56.5	12	21	70	17
100		25	10.5	M10		–	7	89	15.5	26.3	93.3	21

Compact cylinders ADN, to ISO 21287

Technical data

FESTO

Ordering data						
Type	Piston Ø [mm]	Stroke [mm]	Female piston rod thread		Male piston rod thread	
			Part No.	Type	Part No.	Type
	12	5	536 211	ADN-12-5-I-P-A	536 204	ADN-12-5-A-P-A
		10	536 212	ADN-12-10-I-P-A	536 205	ADN-12-10-A-P-A
		15	536 213	ADN-12-15-I-P-A	536 206	ADN-12-15-A-P-A
		20	536 214	ADN-12-20-I-P-A	536 207	ADN-12-20-A-P-A
		25	536 215	ADN-12-25-I-P-A	536 208	ADN-12-25-A-P-A
		30	536 216	ADN-12-30-I-P-A	536 209	ADN-12-30-A-P-A
		40	536 217	ADN-12-40-I-P-A	536 210	ADN-12-40-A-P-A
	16	5	536 226	ADN-16-5-I-P-A	536 219	ADN-16-5-A-P-A
		10	536 227	ADN-16-10-I-P-A	536 220	ADN-16-10-A-P-A
		15	536 228	ADN-16-15-I-P-A	536 221	ADN-16-15-A-P-A
		20	536 229	ADN-16-20-I-P-A	536 222	ADN-16-20-A-P-A
		25	536 230	ADN-16-25-I-P-A	536 223	ADN-16-25-A-P-A
		30	536 231	ADN-16-30-I-P-A	536 224	ADN-16-30-A-P-A
		40	536 232	ADN-16-40-I-P-A	536 225	ADN-16-40-A-P-A
		50	536 341	ADN-16-50-I-P-A	536 331	ADN-16-50-A-P-A
	20	5	536 242	ADN-20-5-I-P-A	536 234	ADN-20-5-A-P-A
		10	536 243	ADN-20-10-I-P-A	536 235	ADN-20-10-A-P-A
		15	536 244	ADN-20-15-I-P-A	536 236	ADN-20-15-A-P-A
		20	536 245	ADN-20-20-I-P-A	536 237	ADN-20-20-A-P-A
		25	536 246	ADN-20-25-I-P-A	536 238	ADN-20-25-A-P-A
		30	536 247	ADN-20-30-I-P-A	536 239	ADN-20-30-A-P-A
		40	536 248	ADN-20-40-I-P-A	536 240	ADN-20-40-A-P-A
		50	536 249	ADN-20-50-I-P-A	536 241	ADN-20-50-A-P-A
		60	536 362	ADN-20-60-I-P-A	536 352	ADN-20-60-A-P-A
	25	5	536 259	ADN-25-5-I-P-A	536 251	ADN-25-5-A-P-A
		10	536 260	ADN-25-10-I-P-A	536 252	ADN-25-10-A-P-A
		15	536 261	ADN-25-15-I-P-A	536 253	ADN-25-15-A-P-A
		20	536 262	ADN-25-20-I-P-A	536 254	ADN-25-20-A-P-A
		25	536 263	ADN-25-25-I-P-A	536 255	ADN-25-25-A-P-A
		30	536 264	ADN-25-30-I-P-A	536 256	ADN-25-30-A-P-A
		40	536 265	ADN-25-40-I-P-A	536 257	ADN-25-40-A-P-A
		50	536 266	ADN-25-50-I-P-A	536 258	ADN-25-50-A-P-A
		60	536 383	ADN-25-60-I-P-A	536 373	ADN-25-60-A-P-A
	32	5	536 278	ADN-32-5-I-P-A	536 268	ADN-32-5-A-P-A
		10	536 279	ADN-32-10-I-P-A	536 269	ADN-32-10-A-P-A
		15	536 280	ADN-32-15-I-P-A	536 270	ADN-32-15-A-P-A
		20	536 281	ADN-32-20-I-P-A	536 271	ADN-32-20-A-P-A
		25	536 282	ADN-32-25-I-P-A	536 272	ADN-32-25-A-P-A
		30	536 283	ADN-32-30-I-P-A	536 273	ADN-32-30-A-P-A
		40	536 284	ADN-32-40-I-P-A	536 274	ADN-32-40-A-P-A
		50	536 285	ADN-32-50-I-P-A	536 275	ADN-32-50-A-P-A
		60	536 286	ADN-32-60-I-P-A	536 276	ADN-32-60-A-P-A
		80	536 287	ADN-32-80-I-P-A	536 277	ADN-32-80-A-P-A

Compact cylinders ADN, to ISO 21287

Technical data

FESTO

Ordering data						
Type	Piston Ø [mm]	Stroke [mm]	Female piston rod thread		Male piston rod thread	
			Part No.	Type	Part No.	Type
	40	5	536 299	ADN-40-5-I-P-A	536 289	ADN-40-5-A-P-A
		10	536 300	ADN-40-10-I-P-A	536 290	ADN-40-10-A-P-A
		15	536 301	ADN-40-15-I-P-A	536 291	ADN-40-15-A-P-A
		20	536 302	ADN-40-20-I-P-A	536 292	ADN-40-20-A-P-A
		25	536 303	ADN-40-25-I-P-A	536 293	ADN-40-25-A-P-A
		30	536 304	ADN-40-30-I-P-A	536 294	ADN-40-30-A-P-A
		40	536 305	ADN-40-40-I-P-A	536 295	ADN-40-40-A-P-A
		50	536 306	ADN-40-50-I-P-A	536 296	ADN-40-50-A-P-A
		60	536 307	ADN-40-60-I-P-A	536 297	ADN-40-60-A-P-A
		80	536 308	ADN-40-80-I-P-A	536 298	ADN-40-80-A-P-A
	50	5	536 320	ADN-50-5-I-P-A	536 310	ADN-50-5-A-P-A
		10	536 321	ADN-50-10-I-P-A	536 311	ADN-50-10-A-P-A
		15	536 322	ADN-50-15-I-P-A	536 312	ADN-50-15-A-P-A
		20	536 323	ADN-50-20-I-P-A	536 313	ADN-50-20-A-P-A
		25	536 324	ADN-50-25-I-P-A	536 314	ADN-50-25-A-P-A
		30	536 325	ADN-50-30-I-P-A	536 315	ADN-50-30-A-P-A
		40	536 326	ADN-50-40-I-P-A	536 316	ADN-50-40-A-P-A
		50	536 327	ADN-50-50-I-P-A	536 317	ADN-50-50-A-P-A
		60	536 328	ADN-50-60-I-P-A	536 318	ADN-50-60-A-P-A
		80	536 329	ADN-50-80-I-P-A	536 319	ADN-50-80-A-P-A
	63	10	536 342	ADN-63-10-I-P-A	536 332	ADN-63-10-A-P-A
		15	536 343	ADN-63-15-I-P-A	536 333	ADN-63-15-A-P-A
		20	536 344	ADN-63-20-I-P-A	536 334	ADN-63-20-A-P-A
		25	536 345	ADN-63-25-I-P-A	536 335	ADN-63-25-A-P-A
		30	536 346	ADN-63-30-I-P-A	536 336	ADN-63-30-A-P-A
		40	536 347	ADN-63-40-I-P-A	536 337	ADN-63-40-A-P-A
		50	536 348	ADN-63-50-I-P-A	536 338	ADN-63-50-A-P-A
		60	536 349	ADN-63-60-I-P-A	536 339	ADN-63-60-A-P-A
		80	536 350	ADN-63-80-I-P-A	536 340	ADN-63-80-A-P-A
	80	10	536 363	ADN-80-10-I-P-A	536 353	ADN-80-10-A-P-A
		15	536 364	ADN-80-15-I-P-A	536 354	ADN-80-15-A-P-A
		20	536 365	ADN-80-20-I-P-A	536 355	ADN-80-20-A-P-A
		25	536 366	ADN-80-25-I-P-A	536 356	ADN-80-25-A-P-A
		30	536 367	ADN-80-30-I-P-A	536 357	ADN-80-30-A-P-A
		40	536 368	ADN-80-40-I-P-A	536 358	ADN-80-40-A-P-A
		50	536 369	ADN-80-50-I-P-A	536 359	ADN-80-50-A-P-A
		60	536 370	ADN-80-60-I-P-A	536 360	ADN-80-60-A-P-A
		80	536 371	ADN-80-80-I-P-A	536 361	ADN-80-80-A-P-A
	100	10	536 384	ADN-100-10-I-P-A	536 374	ADN-100-10-A-P-A
		15	536 385	ADN-100-15-I-P-A	536 375	ADN-100-15-A-P-A
		20	536 386	ADN-100-20-I-P-A	536 376	ADN-100-20-A-P-A
		25	536 387	ADN-100-25-I-P-A	536 377	ADN-100-25-A-P-A
		30	536 388	ADN-100-30-I-P-A	536 378	ADN-100-30-A-P-A
		40	536 389	ADN-100-40-I-P-A	536 379	ADN-100-40-A-P-A
		50	536 390	ADN-100-50-I-P-A	536 380	ADN-100-50-A-P-A
		60	536 391	ADN-100-60-I-P-A	536 381	ADN-100-60-A-P-A
		80	536 392	ADN-100-80-I-P-A	536 382	ADN-100-80-A-P-A

 New
Variant R8, TT

Compact cylinders ADN, to ISO 21287

Ordering data – Modular products, basic version and variants

FESTO

M Mandatory data →							
Module No.	Function		Stroke		Cushioning		
	Piston Ø		Piston rod thread		Position sensing		
536 203	ADN	12	1 ... 500	A	P	A	
536 218		16		I			
536 233		20					
536 250		25					
536 267		32					
536 288		40					
Order example							
536 309	ADN	- 40	- 250	- A	- P	- A	

Ordering table										
Size		12	16	20	25	32	40	Condi- tions	Code	Enter Code
<										

1 I Not with piston rod type S20
Not with extended male thread K2

Transfer order code

ADN - - - - P - A

Compact cylinders ADN, to ISO 21287

Ordering data – Modular products, basic version and variants

0 Options									
Type of piston rod		Special thread		Improved running performance		Corrosion protection		Low temperature	
Male thread extended		Piston rod extended		Temperature resistance		Captive rating plate		Wiper seal	
S2 S20	...K2	"...K5 ...K8		K10 S6		R3 TL		TT R8	
- S2	- 15K2	- "M16"K5	- 50K8	-	- S6	-	-	-	-

Ordering table										
Size	12	16	20	25	32	40	Condi- tions	Code		Enter Code
0 Type of piston rod	Through piston rod						2	-S2		
	Through, hollow piston rod						2	-S20		
	Restricted stroke									
	1 ... 200									
	1 ... 300									
Male thread extended		Extended male piston rod thread								
[mm]		1 ... 10						-...K2		
Special piston rod thread		Male thread						"...K5		
		M6	M8	M10x1,25	M10x1,25	M10	M10			
				M10	M10	M12	M12			
		Female thread								
		-	-	M5	M5	M6	M6			
Piston rod extended		Extended piston rod								
[mm]		1 ... 300						-...K8		
		1 ... 400								
Improved running performance		Smooth anodised aluminium coated piston rod						4	-K10	
Temperature resistance		Heat-resistant seals up to max. 120 °C							-S6	
Corrosion protection		High corrosion protection						5	-R3	
Captive rating plate		Laser etched rating plate							-TL	
Low temperature [°C]		-40 ... +80						6 7	-TT	
Wiper seal		Dust protection						6	-R8	

2 S2, S20 Not with improved running performance K10

Not with corrosion protection R3

3 K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

4 K10 Not with extended male thread K2
Not with special piston rod thread K5
Not with corrosion protection R3

5 R3 Not with captive rating plate TL

Not with low temperature TT

Not with wiper seal R8

6 TT, R8 Not with improved running performance K10

Not with temperature resistance S6

7 TT Not with wiper seal R8

Transfer order code

- [] - [] - [] - [] - [] - [] - [] - [] - [] - []

Compact cylinders ADN, to ISO 21287

Ordering data – Modular products, basic version and variants

FESTO

M Mandatory data →							
Module No.	Function		Stroke		Cushioning		
	Piston Ø		Piston rod thread		Position sensing		
536 309	ADN	50	1 ... 500	A	P	A	
536 330		63		I			
536 351		80					
536 372		100					
536 393		125					
Order example							
536 309	ADN	- 50	- 350	- A	- P	- A	

Ordering table									
Size	50	63	80	100	125	Condi- tions	Code	Enter Code	
M ↓	Module No.	536 309	536 330	536 351	536 372	536 393			
	Function	Compact cylinder, double-acting, based on ISO 21287						ADN	ADN
	Piston Ø [mm]	50	63	80	100	125	-...		
	Stroke [mm]	1 ... 400		1 ... 500				-...	
	Piston rod thread	Male thread						-A	
		Female thread					1	-I	
	Cushioning	Flexible cushioning rings/pads at both ends						-P	-P
	Position sensing	Via proximity sensor						-A	-A

1 I Not with piston rod type S20
Not with extended male thread K2

Transfer order code

ADN - - - - **P** - **A**

Compact cylinders ADN, to ISO 21287

Ordering data – Modular products, basic version and variants

0 Options									
Type of piston rod		Special thread		Improved running performance		Corrosion protection		Low temperature	
Male thread extended		Piston rod extended		Temperature resistance		Captive rating plate		Wiper seal	
S2	...K2	"...K5	...K8	K10	S6	R3	TL	TT	R8
S20									
- S2	- 15K2	- "M16"K5	- 50K8	-	- S6	-	-	-	-

Ordering table										
Size		50	63	80	100	125	Condi- tions	Code	Enter Code	
0	Type of piston rod	Through piston rod					2	-S2		
		Through, hollow piston rod					2	-S20		
		Restricted stroke								
	[mm]	1 ... 300				1 ... 400				
	Male thread extended		Extended male piston rod thread							
	[mm]	1 ... 20		1 ... 30		1 ... 40		-...K2		
	Special piston rod thread	Male thread	M12	M12	M16	M16	M20	-"...K5		
			M16	M16	M20	M20	M20x1,5			M20x1,5
		Female thread	M8	M8	M10	M10	-			
	Piston rod extended		Extended piston rod							
[mm]	1 ... 400				1 ... 500		3	-...K8		
Improved running performance		Smooth anodised aluminium coated piston rod					4	-K10		
[mm]	2 ... 400		5 ... 400	5 ... 500						
Temperature resistance		Heat-resistant seals up to max. 120 °C						-S6		
Corrosion protection		High corrosion protection					5	-R3		
Captive rating plate		Laser etched rating plate						-TL		
Low temperature		[°C]	-40 ... +80				-	6 7	-TT	
Wiper seal		Dust protection					-	6	-R8	

2 S2, S20 Not with improved running performance K10

Not with corrosion protection R3

3 K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

4 K10 Not with extended male thread K2

Not with special piston rod thread K5

Not with corrosion protection R3

5 R3 Not with captive rating plate TL

Not with low temperature TT

Not with wiper seal R8

6 TT, R8 Not with improved running performance K10

Not with temperature resistance S6

7 TT Not with wiper seal R8

Transfer order code

- [] - [] - [] - [] - [] - [] - [] - [] - [] - []

Compact cylinders ADN, to ISO 21287

FESTO

Ordering data – Modular products, S10 – Version with constant motion, S11 – Version with low friction

Mandatory data							→
Module No.	Function	Piston Ø	Stroke	Piston rod thread	Cushioning	Position sensing	
536 203	ADN	12	1 ... 500	A I	P	A	
536 218		16					
536 233		20					
536 250		25					
536 267		32					
536 288		40					
536 309		50					
536 330		63					
536 351		80					
536 372		100					
536 393		125					
Order example							
536 309	ADN	50	350	A	P	A	

Ordering table												
Size	12	16	20	25	32	40	Condi- tions	Code		Enter code		
M	Module No.	536 203	536 218	536 233	536 250	536 267	536 288					
	Function	Compact cylinder, double-acting, based on ISO 21287							ADN		ADN	
	Piston Ø [mm]	12	16	20	25	32	40		-...			
	Stroke [mm]	1 ... 300				1 ... 400			-...			
	Piston rod thread	Male thread							-A			
		Female thread						1	-I			
	Cushioning	Flexible cushioning rings/pads at both ends							-P		-P	
	Position sensing	Via proximity sensor							-A		-A	
O	Male thread extended [mm]	Extended male piston rod thread 1 ... 10				1 ... 20			-...K2			
	Special piston rod thread	Male thread	M6	M8	M10x1.25 M10	M10x1.25 M10	M10 M12	M10 M12			-“...”K5	
		Female thread	–	–	M5	M5	M6	M6				
	Piston rod extended [mm]	Extended piston rod 1 ... 300				1 ... 400		2	-...K8			
	Improved running performance	–	–	Smooth anodised aluminium coated piston rod				3	-K10			
	Constant motion [mm]	Slow speed (constant motion at low piston speeds)						4	-S10			
		Restricted stroke 20 ... 300										
	Low friction	Low friction						5	-S11			
	Corrosion protection	High corrosion protection						6	-R3			
	Captive rating plate	Laser etched rating plate							-TL			

- | | | | |
|-------|---|-------|----------------------------------|
| 1 I | Not with extended male thread K2 | 4 S10 | Not with low friction S11 |
| 2 K8 | The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length | 5 S11 | Not with constant motion S10 |
| 3 K10 | Not with extended male thread K2
Not with special piston rod thread K5
Not with corrosion protection R3 | 6 R3 | Not with captive rating plate TL |

Transfer order code

ADN – 50 – 350 – A – P – A

Compact cylinders ADN, to ISO 21287

FESTO

Ordering data – Modular products, S10 – Version with constant motion, S11 – Version with low friction

Options							
Male thread extended	Special thread	Piston rod extended	Improved running performance	Constant motion	Low friction	Corrosion protection	Captive rating plate
...K2	"..."K5	...K8	K10	S10	S11	R3	TL
-	- "M16"K5	- 50K8	-	- S10	-	- R3	-

Ordering table									
Size		50	63	80	100	125	Condi- tions	Code	Enter code
M	Module No.		536 309	536 330	536 351	536 372	536 393		
	Function		Compact cylinder, double-acting, based on ISO 21287						ADN
	Piston Ø	[mm]	50	63	80	100	125	-...	
	Stroke	[mm]	1 ... 400			1 ... 500			-...
	Piston rod thread	Male thread							-A
		Female thread						1	-I
	Cushioning	Flexible cushioning rings/pads at both ends							-P
Position sensing		Via proximity sensor						-A	
O	Male thread extended		Extended male piston rod thread						
		[mm]	1 ... 20		1 ... 30		1 ... 40		-...K2
	Special piston rod thread	Male thread	M12	M12	M16	M16	M20		-“...”K5
			M16	M16	M20	M20	M20x1.5		
		Female thread	M8	M8	M10	M10	—		
	Piston rod extended	Extended piston rod							
		[mm]	1 ... 400		1 ... 500			2	-...K8
	Improved running performance	Smooth anodised aluminium coated piston rod						3	-K10
		[mm]	2 ... 400		5 ... 400	5 ... 500			
	Constant motion	Slow speed (constant motion at low piston speeds)						4	-S10
		[mm]	20 ... 400		20 ... 500				
	Low friction	Low friction						5	-S11
Corrosion protection	High corrosion protection						6	-R3	
Captive rating plate		Laser etched rating plate						-TL	

[1] I Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[3] K10 Not with extended male thread K2
Not with special piston rod thread K5
Not with corrosion protection R3

[4] S10 Not with low friction S11

[5] S11 Not with constant motion S10

[6] R3 Not with captive rating plate TL

Transfer order code

- [] - [] - [] - [] - [] - [] - [] - []

Compact cylinders ADN, to ISO 21287

FESTO

Ordering data – Modular products, Q – Version with square piston rod, non-rotating

Mandatory data							→
Module No.	Function	Piston Ø	Stroke	Piston rod thread	Cushioning	Position sensing	
536 203	ADN	12	1 ... 500	A	P	A	
536 218		16		I			
536 233		20					
536 250		25					
536 267		32					
536 288		40					
536 309		50					
536 330		63					
536 351		80					
536 372		100					
536 393	125						
Order example							
536 309	ADN	- 50	- 350	- A	- P	- A	

Ordering table										
Size	12	16	20	25	32	40	Condi- tions	Code		Enter code
M	Module No.	536 203	536 218	536 233	536 250	536 267	536 288			
	Function	Compact cylinder, double-acting, based on ISO 21287							ADN	ADN
	Piston Ø [mm]	12	16	20	25	32	40		-...	
	Stroke [mm]	1 ... 300				1 ... 400			-...	
	Piston rod thread	Male thread							-A	
		Female thread						1	-I	
	Cushioning	Flexible cushioning rings/pads at both ends							-P	-P
	Position sensing	Via proximity sensor							-A	-A
O	Protection against torsion	Square piston rod							-Q	-Q
	Type of piston rod	Through piston rod							-S2	
		–	Through, hollow piston rod					-S20		
	[mm]	1 ... 200				1 ... 300				
	Male thread extended	Extended male piston rod thread								
	[mm]	1 ... 10		1 ... 20					-...K2	
	Special piston Male thread rod thread	M6	M8	M10x1.25 M10	M10x1.25 M10	M10	M10		-“...”K5	
	Piston rod extended	Extended piston rod								
	[mm]	1 ... 300				1 ... 400		2	-...K8	
	Temperature resistance	Heat-resistant seals up to max. 120 °C							-S6	
	Captive rating plate	Laser etched rating plate							-TL	

1 I Not with piston rod type S20
Not with extended male thread K2

2 K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

	ADN	–		–		–		–	P	–	A
--	-----	---	--	---	--	---	--	---	---	---	---

Compact cylinders ADN, to ISO 21287

FESTO

Ordering data – Modular products, Q – Version with square piston rod, non-rotating

Options						
Protection against torsion	Type of piston rod	Male thread extended	Special thread	Piston rod extended	Temperature resistance	Captive rating plate
Q	S2 S20	...K2	"..."K5	...K8	S6	TL
- Q	- S2	- 15K2	- "M16"K5	- 50K8	- S6	-

Ordering table									
Size		50	63	80	100	125	Condi- tions	Code	Enter code
M	Module No.	536 309	536 330	536 351	536 372	536 393			
	Function	Compact cylinder, double-acting, based on ISO 21287						ADN	ADN
	Piston Ø [mm]	50	63	80	100	125		-...	
	Stroke [mm]	1 ... 400		1 ... 500				-...	
	Piston rod thread	Male thread						-A	
		Female thread					1	-I	
	Cushioning	Flexible cushioning rings/pads at both ends						-P	-P
	Position sensing	Via proximity sensor						-A	-A
Q	Protection against torsion	Square piston rod						-Q	-Q
	Type of piston rod	Through piston rod						-S2	
		Through, hollow piston rod						-S20	
		Restricted stroke							
	[mm]	1 ... 300			1 ... 400				
	Male thread extended	Extended male piston rod thread							
	[mm]	1 ... 20		1 ... 30		1 ... 40		-...K2	
	Special piston rod thread	Male thread	M12	M12	M16	M16	M20	-“...”K5	
	Piston rod extended	Extended piston rod							
	[mm]	1 ... 400			1 ... 500		2	-...K8	
	Temperature resistance	Heat-resistant seals up to max. 120 °C						-S6	
	Captive rating plate	Laser etched rating plate						-TL	

¹ I Not with piston rod type S20
Not with extended male thread K2

² K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

- Q - - - - -

Compact cylinders ADN, to ISO 21287

FESTO

Ordering data – Modular products, S1 – Version with reinforced piston rod

M Mandatory data							O Options					
Module No.	Function	Piston 	Stroke	Piston rod thread	Cushioning	Position sensing	Male thread extended	Special thread	Piston rod extended	Temperature resistance	Reinforced piston rod	Captive rating plate
536 250	ADN	25	5 ... 500	A	P	A	...K2	“ ... ”K5	...K8	S6	S1	TL
536 288		40		I								
536 330		63										
536 372		100										
Order example												
536 288	ADN	40	320	I	P	A			50K8	S6	S1	TL

Ordering table													
Size			25	40	63	100	Condi- tions	Code	Enter code				
M	Module No.		536 250		536 288		536 330		536 372				
	Function		Compact cylinder, double-acting, based on ISO 21287							ADN	ADN		
	Piston Ø	[mm]	25	40	63	100		-...					
	Stroke	[mm]	5 ... 300	10 ... 400	10 ... 500			-...					
	Piston rod thread		Male thread							-A			
			Female thread						1	-I			
	Cushioning		Flexible cushioning rings/pads at both ends							-P	-P		
	Position sensing		Via proximity sensor							-A	-A		
O	Male thread extended [mm]		Extended male piston rod thread										
			1 ... 20				1 ... 30			-...K2			
	Special piston rod thread	Male thread	M10x1.25	M10x1.25	M12x1.25	M16x1.5		-“...”K5					
			M10	M12	M16	M20							
		Female thread	M5	M8	M10	-							
	Piston rod extended [mm]		Extended piston rod										
			1 ... 300		1 ... 400		1 ... 500		2	-...K8			
	Temperature resistance		Heat-resistant seals up to max. 120 °C							-S6			
Reinforced piston rod		Reinforced piston rod or extended piston rod bearing							-S1	-S1			
Captive rating plate		Laser etched rating plate							-TL				

[1] I Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

	ADN	-		-		-	P	-	A	-		-		-	S1	-	
--	-----	---	--	---	--	---	---	---	---	---	--	---	--	---	----	---	--

Compact cylinders ADN-KP, standard port pattern, with clamping unit

FESTO

Type codes


		ADN	–	20	–	50	–	KP	–	A	–	P	–	A	–	K2
Type																
Double-acting																
ADN	Compact cylinder															
Piston Ø [mm]																
Stroke [mm]																
Clamping unit																
KP	Integrated															
Piston rod thread																
A	Male thread															
I	Female thread															
Cushioning																
P	Flexible cushioning rings/pads at both ends															
Position sensing																
A	Via proximity sensor															
Variant																
K2	Extended male piston rod thread															
K5	Special piston rod thread															
K8	Extended piston rod															
TL	Captive rating plate															

Compact cylinders ADN-KP, standard port pattern, with clamping unit

FESTO

Technical data

Function



- $\varnothing$ - Diameter
20 ... 100 mm
-  - Stroke length
10 ... 500 mm

Variants



K2



K5



K8



Note

Additional measures are required for use in safety-related control systems; in Europe, for example, the standards listed under the EC Machinery Directive must be observed. Without

additional measures in accordance with statutory minimum requirements, the product is not suitable for use in safety-related sections of control systems.

General technical data									
Piston Ø		20	25	32	40	50	63	80	100
Pneumatic connection	Cylinder	M5	M5	G½	G½	G½	G½	G½	G½
	KP	M5	M5	M5	G½	G½	G½	G½	G½
Female piston rod thread		M6		M8		M10		M12	
	K5	M5		M6		M8		M10	
Male piston rod thread		M8		M10x1.25		M12x1.25		M16x1.5	
	K5	M10, M10x1.25		M10, M12		M12, M16		M16, M20, M20x1.5	
Max. axial backlash with clamped piston rod without load [mm]		0.5				0.7			
Constructional design		Piston							
		Piston rod							
		Cylinder barrel							
Cushioning		Flexible cushioning rings/pads at both ends							
Position sensing		Via proximity sensor							
Type of mounting		Via through-holes							
		Via female threads							
		Via accessories							
Mounting position		Any							
Clamping type with effective direction of action		From both sides							

Operating and environmental conditions	
Operating medium	Filtered compressed air, lubricated or unlubricated
Operating pressure [bar]	1.5 ... 10
Min. release pressure [bar]	3
Ambient temperature ¹⁾ [°C]	-10 ... +80
Corrosion resistance class CRC ²⁾	2

1) Note operating range of proximity sensors

2) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Compact cylinders ADN-KP, standard port pattern, with clamping unit

Technical data

FESTO

Impact energy [J]								
Piston Ø	20	25	32	40	50	63	80	100
Max. impact energy at the end positions	0.2	0.3	0.4	0.7	1	1.3	1.8	2.5

Permissible impact velocity:

$$v_{perm.} = \sqrt{\frac{2 \times E_{perm.}}{m_{dead} + m_{load}}}$$

$v_{perm.}$ Permissible impact velocity

$E_{perm.}$ Max. impact energy

m_{dead} Moving load (drive)

m_{load} Moving work load



Note

These specifications represent the maximum values which can be reached. Note the maximum permitted impact energy.

Maximum permissible load:

$$m_{load} = \frac{2 \times E_{perm.}}{v^2} - m_{dead}$$

Forces [N]								
Piston Ø	20	25	32	40	50	63	80	100
Theoretical force at 6 bar, advancing	188	295	483	754	1178	1870	3016	4712
Theoretical force at 6 bar, retracting	141	247	415	633	990	1682	2721	4418
Static holding force	350	350	600	1000	1400	2000	5000	5000



Note

The specified holding force refers to a static load. If this value is exceeded, slippage may occur. Dynamic forces occurring during operation must not


exceed the static holding force. The clamping unit is not backlash-free in the clamped condition if varying loads are applied to the piston rod.

Activation:

The clamping unit may only be released if the forces at the piston have reached equilibrium. Otherwise, there is a risk of accidents due to sudden

movement of the piston rod. Blocking off the air supply at both ends (e.g. with a 5/3-way valve) does not provide any safety.

Max. lateral force F_q as a function of the projection x



- Ø 20
- - - Ø 25
- ... Ø 32/40
- · - · - Ø 50/63
- - - - - Ø 80/100

Weight [g]								
Piston Ø	20	25	32	40	50	63	80	100
Product weight with 0 mm stroke	282	344	503	789	1268	1894	3973	5497
Additional weight per 10 mm stroke	22	26	29	45	60	68	93	112
Moving load with 0 mm stroke	53	63	100	173	296	368	755	932
Additional load per 10 mm stroke	6	6	9	16	25	25	39	39


Compact cylinders ADN-KP, standard port pattern, with clamping unit

FESTO

Technical data

Materials

Sectional view




Compact cylinder

1	Cover	Anodised aluminium
2	Cylinder barrel	Anodised aluminium
3	Piston rod	High-alloy steel
4	Flange	Galvanised steel
	screws	Standard screws, galvanised steel
-	Seals	Polyurethane, nitrile rubber

Dimensions – Basic version

Download CAD data → www.festo.com

Ø 20 ... 63



+ = plus stroke length

Ø [mm]	BG	D1 Ø H9	D2 Ø	D5 Ø F9	E +0.3	E1	EE	G	G1	H1	J2
20	19.5	9	20	9	35.5	M5	M5	49.8	12	63	2.6
25					39.5			50.6		65	
32					47			56.4		68	
40	27	12	24	12	54.5	G1/8	G1/8	60.4	15	89	8
50			30		65.5			67.4		108	
63			38		75.5			76.8		120	

Ø [mm]	J3	L2 max.	L3 +0.2	MM Ø h8	PL	PL1	RT	T2 +0.2	TG ±0.2	ZJ h13	⌀C1
20	-	74.9	5	10	42.8	6	M5	2.1	22	81.6	9
25		77.7			44.6				26	83.9	
32		85.5			49.6				32.5	92.2	
40		90.5		20	53.6	8.2	M6	2.6	38	97.3	13
50		97.5			60.6				46.5	106.4	
63		110.9			70				56.5	119.7	

Compact cylinders ADN-KP, standard port pattern, with clamping unit


Technical data

FESTO

Dimensions – Basic version

Download CAD data → www.festo.com

Ø 80, 100




Ø	BG	D1 Ø H9	D2 Ø	D5 Ø F9	E +0.6	E1	EE	G	G1	H1	J2
[mm]											
80	17	12	48	15	95.5	G ¹ / ₈	G ¹ / ₈	99	16.5	167	-
100	21.5				113.5			99.6	21.5	176	

Ø	J3	L2	L3	MM Ø h8	PL	PL1	RT	T2	TG	ZJ	≈C1
[mm]		max.	+0.2					+0.2	±0.2	h13	
80	11.5	136.6	2.6	25	90.7	8.2	M10	2.6	72	146.2	21
100	20	145.2			88.6	10.5			89	154.9	

Dimensions – Variants

Download CAD data → www.festo.com

Basic version



Ø	AF	AM	KF	KK	T4	WH	ZJ
[mm]	min.				min.	+1	
20	14	16	M6	M6	2.6	5.7	81.6
25				M8			83.9
32	16	19	M8	M10x1.25	3.3	6.15	92.2
40						6.8	97.3
50	20	22	M10	M12x1.25	4.7	8.85	106.4
63						8.8	119.7
80		28		M16x1.5	6.1	9.55	146.2
100						9.7	154.9

Compact cylinders ADN-KP, standard port pattern, with clamping unit

FESTO

Ordering data – Modular products

M Mandatory data								→
Module No.	Function	Piston Ø	Stroke	Clamping unit	Piston rod thread	Cushioning	Position sensing	
548 206	ADN	20	10 ... 500	KP	A	P	A	
548 207		25			I			
548 208		32						
548 209		40						
548 210		50						
548 211		63						
548 212		80						
548 213	100							
Order example								
548 209	ADN	- 40	- 350	- KP	- A	- P	- A	

Ordering table								
Size	20	25	32	40	Condi- tions	Code	Enter code	
M Module No.	548 206	548 207	548 208	548 209				
Function	Compact cylinder, double-acting, standard port pattern, with clamping unit					ADN		ADN
Piston Ø [mm]	20	25	32	40		-...		
Stroke [mm]	10 ... 300		10 ... 400			-...		
Clamping unit	Integrated					-KP		-KP
Piston rod thread	Male thread					-A		
	Female thread					1 -I		
Cushioning	Flexible cushioning rings/pads at both ends					-P		-P
Position sensing	Via proximity sensor					-A		-A
0 Male thread extended [mm]	Extended male piston rod thread 1 ... 20					-...K2		
Special piston rod thread	Male thread	M10x1.25 M10	M10x1.25 M10	M10 M12	M10 M12	-“...”K5		
	Female thread	M5	M5	M6	M6			
Piston rod extended [mm]	Extended piston rod 1 ... 300 1 ... 400					2 -...K8		
Captive rating plate	Laser etched rating plate					-TL		

- 1 I Not with extended male thread K2
- 2 K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

ADN

-

-

-

KP

-

-

P

-

A

Compact cylinders ADN-KP, standard port pattern, with clamping unit

FESTO

Ordering data – Modular products

Options			
Male thread extended	Special thread	Piston rod extended	Captive rating plate
...K2	"..."K5	...K8	TL
- 20K2	- "M10"K5	-	- TL

Ordering table									
Size		50	63	80	100	Condi- tions	Code	Enter code	
M	Module No.		548 210	548 211	548 212	548 213			
	Function		Compact cylinder, double-acting, standard port pattern, with clamping unit				ADN	ADN	
	Piston Ø	[mm]	50	63	80	100	- ...		
	Stroke	[mm]	10 ... 400		10 ... 500		- ...		
	Clamping unit		Integrated				-KP	-KP	
	Piston rod thread	Male thread					-A		
		Female thread				1	-I		
	Cushioning		Flexible cushioning rings/pads at both ends				-P	-P	
	Position sensing		Via proximity sensor				-A	-A	
0	Male thread extended		Extended male piston rod thread						
		[mm]	1 ... 20		1 ... 30		-...K2		
	Special piston rod thread	Male thread	M12 M16	M12 M16	M16 M20 M20x1.5	M16 M20 M20x1.5	-“...”K5		
		Female thread	M8	M8	M10	M10			
	Piston rod extended		Extended piston rod						
		[mm]	1 ... 400		1 ... 500		2	-...K8	
Captive rating plate		Laser etched rating plate				-TL			

- ¹ **I** Not with extended male thread K2
- ² **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

--	--	--	--

Compact cylinders ADN-EL, standard port pattern, with end position lock

FESTO


Type codes

		ADN	–	20	–	100	–	ELV	–	A	–	P	–	A	–	K2
Type																
Double-acting																
ADN	Compact cylinder															
Piston Ø [mm]																
Stroke [mm]																
End position lock																
ELB	At both ends															
ELV	At front															
ELH	At rear															
Piston rod thread																
A	Male thread															
I	Female thread															
Cushioning																
P	Flexible cushioning rings/pads at both ends															
Position sensing																
A	Via proximity sensor															
Variant																
K2	Extended male piston rod thread															
K5	Special piston rod thread															
K8	Extended piston rod															
TL	Captive rating plate															

FESTO

FESTO

Function



-  - Diameter
20 ... 100 mm
-  - Stroke length
10 ... 500 mm

Variants



K2



K5



K8



Note

Additional measures are required for use in safety-related control systems; in Europe, for example, the standards listed under the EC Machinery Directive must be observed. Without

additional measures in accordance with statutory minimum requirements, the product is not suitable for use in safety-related sections of control systems.

General technical data										
Piston Ø		20	25	32	40	50	63	80	100	
Pneumatic connection		M5	M5	G1/8	G1/8	G1/8	G1/8	G1/8	G1/8	
Female piston rod thread		M6	M8			M10		M12		
	K5	M5		M6		M8		M10		
Male piston rod thread		M8		M10x1.25		M12x1.25		M16x1.5		
	K5	M10		M10		M12		M16		
Max. axial backlash with end position locked		[mm]	1.3						2.1	
Constructional design		Piston								
		Piston rod								
		Cylinder barrel								
End position lock	ELB	At both ends								
	ELV	At front								
	ELH	At rear								
Cushioning		Flexible cushioning rings/pads at both ends								
Position sensing		Via proximity sensor								
Type of mounting		Via female threads								
		Via accessories								
Mounting position		Any								



Note

- | | | | |
|--|---|--|---|
| <ul style="list-style-type: none"> • No screws with a head or similar may be used in place of the end position lock, as there is a risk that the function will be impaired if they are screwed in too deeply. • The exhaust hole must not be closed. • Locking can be performed from any stroke position, once the drive is | <p>brought mechanically into its end position.</p> <ul style="list-style-type: none"> • The end position lock has been designed to guard against the load dropping in case of pressure failure. • Operation of the cylinder in conjunction with a 3-way valve (especially with the function “mid- | <p>position closed” and those with “metallic sealing”) should be avoided. The residual pressure that is enclosed on the locking side of the cylinder can release the locking function.</p> <ul style="list-style-type: none"> • The cylinder must not be operated with external stops (e.g. shock absorber, buffer, oil brake, etc.): | <ul style="list-style-type: none"> – It may not be possible to reliably reach the internal end position. – The locking mechanism can wear out prematurely. (In the event of pressure drop in the opposite chamber to less than the locking pressure, the locking piston will prematurely fall to its end position.) |
|--|---|--|---|

Compact cylinders ADN-EL, standard port pattern, with end position lock

Technical data

FESTO

Operating and environmental conditions								
Piston Ø	20	25	32	40	50	63	80	100
Operating medium	Filtered compressed air, lubricated or unlubricated							
Operating pressure [bar]	2.5 ... 10				1.5 ... 10			
Ambient temperature ¹⁾ [°C]	-20 ... +80							
Corrosion resistance class CRC ²⁾	2							

1) Note operating range of proximity sensors

2) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Forces [N]								
Piston Ø	20	25	32	40	50	63	80	100
Theoretical force at 6 bar, advancing	188	295	483	754	1178	1870	3016	4712
Theoretical force at 6 bar, retracting	141	247	415	686	1057	1750	2827	4524
Static holding force	250	500			2000		5000	

Sizing example



Note

When sizing pneumatic cylinders it is recommended as a basic principle that only 50% of the indicated theoretical forces (see above) be used.

Given:

Installation position = Vertical

Workpiece load = 44 kg

$$F = m \times g = 44 \text{ kg} \times 9.81 \text{ m/s}^2 = 431.6 \text{ N}$$

To be calculated:

Suitable piston Ø

Analysis with 32 mm piston Ø:

Theoretical force at 6 bar, advancing = 483 N

50% of the theoretical force = 241.5 N

Static holding force with 32 mm piston Ø = 500 N

The static force on the end position lock is within the permissible range (max. 500 N) with a workpiece load of 44 kg (431.6 N), however the cylinder would be at 89% capacity.

Result:

A cylinder with a piston Ø of 40 mm is therefore recommended for this application.

Impact energy [J]								
Piston Ø	20	25	32	40	50	63	80	100
Max. impact energy at the end positions	0.2	0.3	0.4	0.7	1	1.3	1.8	2.5

Permissible impact velocity:

$$v_{\text{perm.}} = \sqrt{\frac{2 \times E_{\text{perm.}}}{m_{\text{dead}} + m_{\text{load}}}}$$

$v_{\text{perm.}}$ Permissible impact velocity

$E_{\text{perm.}}$ Max. impact energy

m_{dead} Moving load (drive)

m_{load} Moving work load

Maximum permissible load:


$$m_{\text{load}} = \frac{2 \times E_{\text{perm.}}}{v^2} - m_{\text{dead}}$$



Note

These specifications represent the maximum values which can be reached. Note the maximum permitted impact energy.

Max. lateral force F_q as a function of the projection x



- Ø 20
- - - - - Ø 25
- · - · - Ø 32/40
- · · · · Ø 50/63
- - - - - Ø 80/100

Compact cylinders ADN-EL, standard port pattern, with end position lock


Technical data

FESTO

Weight [g]								
Piston Ø	20	25	32	40	50	63	80	100
End position lock at both ends								
Product weight with 0 mm stroke	234	339	518	665	1334	1734	3300	4735
Additional weight per 10 mm stroke	22	26	29	38	51	59	79	98
Moving load with 0 mm stroke								
Additional load per 10 mm stroke	6	6	9	9	16	16	25	25
End position lock at front								
Product weight with 0 mm stroke	177	248	387	498	922	1228	2296	3448
Additional weight per 10 mm stroke	22	26	29	38	51	59	79	98
Moving load with 0 mm stroke								
Additional load per 10 mm stroke	6	6	9	9	16	16	25	25
End position lock at rear								
Product weight with 0 mm stroke	181	252	380	505	920	1217	2233	3409
Additional weight per 10 mm stroke	22	26	29	38	51	59	79	98
Moving load with 0 mm stroke								
Additional load per 10 mm stroke	6	6	9	9	16	16	25	25

Materials

Sectional view



Compact cylinder		
1	Cover	Anodised aluminium
2	Cylinder barrel	Anodised aluminium
3	Piston rod	High-alloy steel
4	Flange	Galvanised steel
	screws	Standard screws, galvanised steel
-	Seals	Polyurethane, nitrile rubber

Compact cylinders ADN-EL, standard port pattern, with end position lock

FESTO


Technical data

Dimensions – Basic version


Download CAD data → www.festo.com

ELB – End position lock at both ends

Ø 20 ... 63




Ø 80 ... 100



ELV – End position lock at front

ELH – End position lock at rear



Compact cylinders ADN-EL, standard port pattern, with end position lock

Technical data

FESTO

Ø [mm]	BG	D1 Ø H9	D2 Ø	D5 Ø F9	E +0.3	EE	G	G1	H1	J2	L2	
											ELB	ELV, ELH
20	18	9	9	9	35.5	M5	25	12	45.5	2.6	63	50
25					39.5		29.5		53.3		74	56.5
32			13		47	G1/8	33	15	58	6	80	62
40									61.8	8	81	63
50	20	12	20	12	G1/8		43	15	77	11.5	101	73
63									75.5		82	105
80			30	15		95.5	55	16.5	103.5	131	92.5	
100						113.5	57	21.5	113.5	20	138	102.5


Ø	L3	L4	L5	MM Ø	PL	PL1	RT	T2	TG	ZJ		≈G1	
[mm]	+0.2	max.		h8				+0.1	±0.2	ELB	ELV, ELH	h13	
20	5	18.5	12.5	10	6	6	M5	2.1	22	69	56	9	
25		20.8	14						26	80	62.5		
32		22.5	15	12	16	8.2	M6		2.6	32.5	86	68	10
40										38	87	69	
50	2.6	27.5	20.5	16	21		M8	46.5		109	81	13	
63								56.5		113	85		
80		2.6	34	25	20	28	10.5	M10	72	140	101.5	17	
100			35	27					89	147	111.5		

Dimensions – Variants

Download CAD data → www.festo.com

Basic version

K5 – Special piston rod thread



Ø [mm]	A3	AF	AM	K2	KF	KK	T3 min.	T4 min.	WH +1	ZJ	
										ELB	ELV, ELH
20	12	14	16	M5	M6	M8	2	2.6	5.7	69	56
25										80	62.5
32	14	16	19	M6	M8	M10x1.25	2.6	3.3	6.2	86	68
40										87	69
50	16	20	22	M8	M10	M12x1.25	3.3	4.7	8.2	109	81
63										113	85
80	20		28	M10	M12	M16x1.5	4.7	6.1	9	140	101.5
100										147	111.5

Compact cylinders ADN-EL, standard port pattern, with end position lock

Ordering data – Modular products

FESTO

M Mandatory data							
Module No.	Function	Piston Ø	Stroke	End position lock	Piston rod thread	Cushioning	Position sensing
548 214	ADN	20	10 ... 500	ELB	A	P	A
548 215		25		ELV	I		
548 216		32		ELH			
548 217		40					
548 218		50					
548 219		63					
548 220		80					
548 221		100					
Order example							
548 220	ADN	- 80	- 450	- ELV	- I	- P	- A

Ordering table									
Size		20	25	32	40	Condi- tions	Code	Enter code	
M	Module No.	548 214	548 215	548 216	548 217				
	Function	Compact cylinder, double-acting, standard port pattern, with end position lock					ADN		ADN
	Piston Ø [mm]	20	25	32	40		-...		
	Stroke [mm]	10 ... 300		10 ... 400			-...		
	End position lock	At both ends					-ELB		
		At front					-ELV		
		At rear					-ELH		
	Piston rod thread	Male thread					-A		
		Female thread				1	-I		
	Cushioning	Flexible cushioning rings/pads at both ends					-P		-P
Position sensing	Via proximity sensor					-A	-A		
O	Male thread extended [mm]	Extended male piston rod thread 1 ... 20					-...K2		
	Special piston rod thread	Male thread	M10x1.25 M10	M10x1.25 M10	M10 M12		-“...”K5		
		Female thread	M5	M5	M6	M6			
	Piston rod extended [mm]	Extended piston rod 1 ... 300			1 ... 400	2	-...K8		
	Captive rating plate	Laser etched rating plate					-TL		

- ¹ I Not with extended male thread K2
² K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

ADN - - - - - P - A

Compact cylinders ADN-EL, standard port pattern, with end position lock

Ordering data – Modular products

→ **0 Options**

Male thread extended	Special thread	Piston rod extended	Captive rating plate
...K2	"..."K5	...K8	TL
-	- "M10"K5	- 50K8	- TL

Ordering table

Size		50	63	80	100	Conditions	Code	Enter code
M	Module No.	548 218	548 219	548 220	548 221			
	Function	Compact cylinder, double-acting, standard port pattern, with end position lock					ADN	ADN
	Piston Ø [mm]	50	63	80	100		-...	
	Stroke [mm]	10 ... 400		10 ... 500			-...	
	End position lock	At both ends					-ELB	
		At front					-ELV	
		At rear					-ELH	
	Piston rod thread	Male thread					-A	
		Female thread				1	-I	
	Cushioning	Flexible cushioning rings/pads at both ends					-P	-P
	Position sensing	Via proximity sensor					-A	-A
O	Male thread extended [mm]	Extended male piston rod thread 1 ... 20			1 ... 30		-...K2	
	Special piston rod thread	Male thread	M12 M16	M12 M16	M16 M20 M20x1.5	M16 M20 M20x1.5	-“...”K5	
		Female thread	M8	M8	M10	M10		
	Piston rod extended [mm]	Extended piston rod 1 ... 400			1 ... 500	2	-...K8	
	Captive rating plate	Laser etched rating plate					-TL	

- | | | |
|---|----|---|
| 1 | I | Not with extended male thread K2 |
| 2 | K8 | The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length |

Transfer order code

- [] - [] - [] - []

Compact cylinders AEN, to ISO 21287

Type codes

FESTO


		AEN	–	50	–	25	–	A	–	P	–	A	–	Q
Type														
Single-acting														
AEN	Compact cylinder													
Piston Ø [mm]														
Stroke [mm]														
Piston rod thread														
A	Male thread													
I	Female thread													
Cushioning														
P	Flexible cushioning rings/pads at both ends													
Position sensing														
A	Via proximity sensor													
Variant														
Z	Single-acting, pulling													
Q	Square piston rod													
K2	Extended male piston rod thread													
K5	Special piston rod thread													
K8	Extended piston rod													
K10	Smooth anodised piston rod													
S6	Heat-resistant seals up to max. 120 °C													
TL	Captive rating plate													

Compact cylinders AEN, to ISO 21287

Technical data

FESTO

Function



Ø - Diameter
12 ... 100 mm

l - Stroke length
1 ... 25 mm

 - www.festo.com

Variants



S6



K2



K5





K8



K10



Q



General technical data											
Piston Ø	12	16	20	25	32	40	50	63	80	100	
Pneumatic connection	M5	M5	M5	M5	G $\frac{1}{8}$	G $\frac{1}{8}$	G $\frac{1}{8}$	G $\frac{1}{8}$	G $\frac{1}{8}$	G $\frac{1}{8}$	G $\frac{1}{8}$
Piston rod thread	Female	M3	M4	M6	M6	M8	M8	M10	M10	M12	M12
	Male	M5	M6	M8	M8	M10x1.25	M10x1.25	M12x1.25	M12x1.25	M16x1.5	M16x1.5
Constructional design	Piston										
	Piston rod										
	Cylinder barrel										
Cushioning	Flexible cushioning rings/pads at both ends										
Position sensing	Via proximity sensor										
Type of mounting	Via through-holes										
	Via female threads										
	Via accessories										
Mounting position	Any										

Operating and environmental conditions										
Piston Ø	12	16	20	25	32	40	50	63	80	100
Operating medium	Filtered compressed air, lubricated or unlubricated									
Operating pressure	1.5 ... 10		1 ... 10							
[bar]	Z	1.7 ... 10	2.2 ... 10	1.3 ... 10		0.7 ... 10	0.6 ... 10			
	Q	1.5 ... 10		1 ... 10						
Ambient temperature ¹⁾	-20 ... +80									
[°C]	S6	0 ... +120								
Corrosion resistance class CRC ²⁾	2									

1) Note operating range of proximity sensors

2) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Compact cylinders AEN, to ISO 21287

Technical data

FESTO

Forces [N] and impact energy [J]										
Piston Ø	12	16	20	25	32	40	50	63	80	100
AEN										
Theoretical force at 6 bar, advancing	59	95	161	260	440	700	1100	1780	2870	4510
AEN-...-Z, pulling										
Theoretical force at 6 bar, retracting	40	65	115	210	380	632	980	1660	2700	4324
	0.04	0.04	0.04	0.08	0.1	0.15	0.18	0.28	0.35	0.7

Permissible impact velocity:

$$v_{perm.} = \sqrt{\frac{2 \times E_{perm.}}{m_{dead} + m_{load}}}$$

$v_{perm.}$ Permissible impact velocity

$E_{perm.}$ Max. impact energy

m_{dead} Moving load (drive)

m_{load} Moving work load

-  - Note


These specifications represent the maximum values which can be reached. Note the maximum permitted impact energy.

Maximum permissible load:


$$m_{load} = \frac{2 \times E_{perm.}}{v^2} - m_{dead}$$

Spring return force F as a function of the stroke l

Ø 12 ... 20



Ø 25 ... 100



-  - Note

The degree of friction depends upon the assembly position and the type of load involved. Single-acting cylinders should as far as possible be operated without lateral forces.

Compact cylinders AEN, to ISO 21287


Technical data

FESTO

Weight [g]										
Piston Ø	12	16	20	25	32	40	50	63	80	100
Product weight with 0 mm stroke	77	79	131	156	265	346	540	722	1300	2154
Additional weight per 10 mm stroke	12	14	21	23	30	37	51	59	79	98
Moving load with 0 mm stroke	9	15	30	50	60	80	140	180	400	570
Additional load per 10 mm stroke	2	4	6	6	9	9	16	16	25	25

Materials

Sectional view



Compact cylinder			Basic version	S6
1	Cover		Anodised aluminium	
2	Cylinder barrel		Anodised aluminium	
3	Piston rod		High-alloy steel	
4	Flange screws	Ø 12 ... 16	High-alloy steel	
		Ø 20 ... 63	Galvanised steel	
		Ø 80 ... 100	Standard screws, galvanised steel	
–	Seals		Polyurethane	Fluoro elastomer

Compact cylinders AEN, to ISO 21287


Technical data

FESTO


Dimensions – Basic version

Download CAD data → www.festo.com

Ø 12 ... 63



Ø 80 ... 100



Ø [mm]	BG	D1 Ø H9	D5 Ø F9	E	EE	G	J2	J3	L2 max.	L3 +0.2	MM Ø h8	PL +0.2	RT	T2 +0.1	TG ±0.2	ZJ +1	≡G1 h13
12	17	9	6	27.5 ^{+0.3}	M5	10.5	2	–	35	3.5	6	6	M4	2.1	16	39.2	5
16				29 ^{+0.3}		11		2.6			37				8	18	39.9
20	19.5		9	35.5 ^{+0.3}		12			39	10			M5		22	42.7	9
25	39.5 ^{+0.3}			G1/8	15						–	44			12	M6	
32	47 ^{+0.3}					6			5	16			8.2				M8
40	54.5 ^{+0.3}	8	45				16	M8				38		51.2			
50	27					12			12	65.5 ^{+0.3}		G1/8	15	–	11.5	49	20
63		75.5 ^{+0.3}	54	2.6	56.5		57.2										
80		17			15		95.5 ^{+0.6}	16.5	54	20	72				63	17	
100	21.5	113.5 ^{+0.6}	21.5	67			20	89	76								

Compact cylinders AEN, to ISO 21287


Technical data

FESTO


Dimensions – Variants

Download CAD data → www.festo.com

Basic version



Z – Pulling



Ø	AF	AM	KF	KK	T4	WH	ZJ
[mm]	min.	−0.5				+1	+1
12	8	10	M3	M5	1.5	4.2	39.2
16	10	12	M4	M6		4.9	39.9
20	14	16	M6	M8	2.6	5.7	42.7
25							44.7
32	16	19	M8	M10x1.25	3.3	6.2	50.2
40							51.2
50	20	22	M10	M12x1.25	4.7	8.2	53.2
63							57.2
80		28	M12	M16x1.5	6.1	9	63
100							76

Compact cylinders AEN, to ISO 21287


Technical data

FESTO

Dimensions – Variants



Download CAD data → www.festo.com

K2 – Extended male piston rod thread





+ = plus stroke length

K5 – Special piston rod thread



K8 – Extended piston rod



Ø [mm]	A1	A2	A3 min.	AM -0.5	K1	K2	KK	T3	WH +1	ZJ +1
12	1 ... 10	1 ... 10	-	10	M6	-	M5	-	4.2	39.2
16				12	M8		M6		4.9	39.9
20	1 ... 20	1 ... 25	14	16	M10	M5	M8	2	5.7	42.7
25					M10x1.25					44.7
32					M10					50.2
40			16	19	M10x1.25	M6	M10x1.25	2.6	6.2	51.2
50					M12					53.2
63					M12					57.2
80	1 ... 30	1 ... 25	20	22	M16	M8	M12x1.25	3.3	8.2	53.2
100					M12					57.2
					M16					63
					M20					76
					M20x1.5					76

Compact cylinders AEN, to ISO 21287



Technical data

FESTO

Dimensions – Variants



Download CAD data → www.festo.com

Q – Square piston rod



+ = plus stroke length


Z – Pulling



+ = plus stroke length

++ = plus 2x stroke length

Q-K5 – Square piston rod with special piston rod thread



Ø	A3	AF	AM	B1	K2	KF	KK	T3	T4	WH	ZJ
[mm]	min.	min.	-0.5	□						+1	+1
16	–	10	12	7	–	M4	M6	–	1.5	4.9	39.9
20	12	12	16	9	M5	M5	M8	2	2	5.7	42.7
25											44.7
32	14	14	19	10	M6	M6	M10x1.25	2.6	2.6	6.2	50.2
40											51.2
50	16	16	22	12	M8	M8	M12x1.25	3.3	3.3	8.2	53.2
63											57.2
80	20	20	28	16	M10	M10	M16x1.5	4.7	4.7	9	63
100											76

Compact cylinders AEN, to ISO 21287

FESTO

Ordering data – Modular products, basic version and variants

Mandatory data							→
Module No.	Function	Piston Ø	Stroke	Type of thread	Cushioning	Position sensing	
536 414	AEN	12	1 ... 25	A	P	A	
536 415		16		I			
536 416		20					
536 417		25					
536 418		32					
536 419		40					
536 420		50					
536 421		63					
536 422		80					
536 423		100					
Order example							
536 423	AEN	- 100	- 21	- A	- P	- A	

Ordering table									
Size	12	16	20	25	32	Condi- tions	Code	Enter code	
M	Module No.	536 414	536 415	536 416	536 417	536 418			
	Function	Compact cylinder, single-acting, based on ISO 21287						AEN	
	Piston Ø [mm]	12	16	20	25	32		-...	
	Stroke [mm]	1 ... 10	1 ... 25					-...	
	Type of thread	Male thread						-A	
		Female thread					1	-I	
	Cushioning	Flexible cushioning rings/pads at both ends						-P	
	Position sensing	Via proximity sensor						-A	
O	Effective direction of action	Single-acting, pulling						-Z	
	Male thread extended [mm]	Extended male piston rod thread 1 ... 10					2	-...K2	
	Special piston rod thread	Male thread	M6	M8	M10x1.25 M10	M10x1.25 M10	M10 M12	2	-“...”K5
		Female thread	–	–	M5	M5	M6		
	Piston rod extended [mm]	Extended piston rod 1 ... 10					3	-...K8	
	Improved running performance	–	–	Smooth anodised aluminium coated piston rod				-K10	
	Temperature resistance	Heat-resistant seals up to max. 120 °C						-S6	
	Captive rating plate	Laser etched rating plate						-TL	

- 1 I Not with extended male thread K2
2 K2, K5 Not with improved running performance K10

- 3 K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

	AEN	–		–		–	P	–	A
--	-----	---	--	---	--	---	---	---	---

Compact cylinders AEN, to ISO 21287

Ordering data – Modular products, basic version and variants

FESTO

Options						
Effective direction of action	Male thread extended	Special thread	Piston rod extended	Improved running performance	Temperature resistance	Captive rating plate
Z	...K2	"..."K5	...K8	K10	S6	TL
-	- 25K2	-	- 4K8	-	- S6	- TL

Ordering table									
Size	40	50	63	80	100	Condi- tions	Code		Enter code
M Module No.	536 419	536 420	536 421	536 422	536 423				
Function	Compact cylinder, single-acting, based on ISO 21287						AEN		AEN
Piston Ø [mm]	40	50	63	80	100		-...		
Stroke [mm]	1 ... 25						-...		
Type of thread	Male thread						-A		
	Female thread					1	-I		
Cushioning	Flexible cushioning rings/pads at both ends						-P		-P
Position sensing	Via proximity sensor						-A		-A
0 Effective direction of action	Single-acting, pulling						-Z		
Male thread extended [mm]	Extended male piston rod thread				1 ... 30	2	-...K2		
	1 ... 20								
Special piston rod thread	Male thread	M10	M12	M12	M16	M16	2	-..."K5	
		M12	M16	M16	M20	M20			
					M20x1.5	M20x1.5			
Female thread	M6	M8	M8	M10	M10				
Piston rod extended [mm]	Extended piston rod					3	-...K8		
1 ... 25									
Improved running performance	Smooth anodised aluminium coated piston rod						-K10		
Temperature resistance	Heat-resistant seals up to max. 120 °C						-S6		
Captive rating plate	Laser etched rating plate						-TL		

- 1** I Not with extended male thread K2
2 K2, K5 Not with improved running performance K10

- 3** K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

- - - - - - -

Compact cylinders AEN, to ISO 21287

FESTO

Ordering data – Modular products, Q – Version with square piston rod, non-rotating

Mandatory data							→
Module No.	Function	Piston Ø	Stroke	Type of thread	Cushioning	Position sensing	
536 415	AEN	16	1 ... 25	A	P	A	
536 416		20		I			
536 417		25					
536 418		32					
536 419		40					
536 420		50					
536 421		63					
536 422		80					
536 423		100					
Order example							
536 423	AEN	- 100	- 21	- A	- P	- A	

Ordering table							
Size	16	20	25	32	Condi- tions	Code	Enter code
M Module No.	536 415	536 416	536 417	536 418			
Function	Compact cylinder, single-acting, based on ISO 21287					AEN	AEN
Piston Ø [mm]	16	20	25	32		-...	
Stroke [mm]	1 ... 25					-...	
Type of thread	Male thread					-A	
	Female thread					-I	
						1	
Cushioning	Flexible cushioning rings/pads at both ends					-P	-P
Position sensing	Via proximity sensor					-A	-A
O Effective direction of action	Single-acting, pulling					-Z	
Protection against torsion	Square piston rod					-Q	-Q
Male thread extended [mm]	Extended male piston rod thread					-...K2	
	1 ... 10	1 ... 20					
Special piston rod thread	Male thread M8	M10x1.25 M10	M10x1.25 M10	M10		-“...”K5	
Piston rod extended [mm]	Extended piston rod					-...K8	
	1 ... 25					2	
Temperature resistance	Heat-resistant seals up to max. 120 °C					-S6	
Captive rating plate	Laser etched rating plate					-TL	

1 I Not with extended male thread K2

2 K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Transfer order code

	AEN	-		-		-	P	-	A
--	-----	---	--	---	--	---	---	---	---

Compact cylinders AEN, to ISO 21287

FESTO

Ordering data – Modular products, Q – Version with square piston rod, non-rotating

Options						
Effective direction of action	Protection against torsion	Male thread extended	Special thread	Piston rod extended	Temperature resistance	Captive rating plate
Z	Q	...K2	"..."K5	...K8	S6	TL
- Z	- Q	- 25K2	-	- 4K8	-	- TL

Ordering table									
Size	40	50	63	80	100	Condi- tions	Code		Enter code
M Module No.	536 419	536 420	536 421	536 422	536 423				
Function	Compact cylinder, single-acting, based on ISO 21287						AEN		AEN
Piston Ø [mm]	40	50	63	80	100		-...		
Stroke [mm]	1 ... 25						-...		
Type of thread	Male thread						-A		
	Female thread					¹	-I		
Cushioning	Flexible cushioning rings/pads at both ends						-P		-P
Position sensing	Via proximity sensor						-A		-A
0 Effective direction of action	Single-acting, pulling						-Z		
Protection against torsion	Square piston rod						-Q		-Q
Male thread extended [mm]	Extended male piston rod thread						-...K2		
Special piston rod thread	Male thread	M10	M12	M12	M16	M16	-..."K5		
Piston rod extended [mm]	Extended piston rod						-...K8		
Temperature resistance	Heat-resistant seals up to max. 120 °C					²	-S6		
Captive rating plate	Laser etched rating plate						-TL		

¹ I Not with extended male thread K2

² K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length


Transfer order code

- - Q - - - - - -

Compact cylinders ADNP, to ISO 21287, with polymer end caps

Peripherals overview

FESTO



Compact cylinders ADNP, to ISO 21287, with polymer end caps

Peripherals overview

FESTO

Mounting attachments and accessories		
	Brief description	→ Page/Internet
1	Foot mounting HNA	For bearing or end caps 71
2	Flange mounting FNC	For bearing or end caps 72
3	Swivel flange SNCL	For end caps 73
4	Swivel flange SNCB	For swivel flange SNCL 77
5	Clevis foot LBN/CRLBN	For swivel flange SNCL 76
6	Multi-position kit DPNA	For connecting two cylinders with identical piston $\varnothing$ to form a multi-position cylinder 75
7	Trunnion flange ZNCF/CRZNG	For bearing caps 78
8	Trunnion support LNZG	For trunnion flange ZNCF/CRZNG 79
9	Swivel flange SNCS	For end caps 74
10	Clevis foot LBG	For swivel flange SNCS 74
11	Rod eye SGS/CRSGS	With spherical bearing 80
12	Coupling piece KSG/KSZ	For compensating radial deviations 80
13	Adapter AD	For mounting a vacuum suction cup on a hollow cylinder piston rod 80
14	Rod clevis SG/CRSG	Permits a swivelling movement of the cylinder in one plane 80
15	Self-aligning rod coupler FK	For compensating radial and angular deviations 80
16	Right-angle clevis foot LQG	For rod eye SGS 81
17	Rod clevis SGA	With male thread 80
18	Proximity sensor SME/SMT-8	Can be integrated in the sensor slot of the cylinder profile barrel 83
19	Proximity sensor SME/SMT-8M	Can be integrated in the sensor slot of the cylinder profile barrel 83
20	Slot cover ABP-5-S	For protecting the sensor cable and keeping dirt out of the sensor slots 83
21	Proximity sensor SMPO-8E	Pneumatic output signal 83
22	Mounting kit SMB-8E	For proximity sensor SMPO-8E 83
23	One-way flow control valve VFOC	For speed regulation 82

Compact cylinders ADNP, to ISO 21287, with polymer end caps

FESTO


Type codes

		ADNP	–	20	–	50	–	A	–	P	–	A	–	QS-4
Type														
Double-acting														
ADNP	Compact cylinder													
Piston Ø [mm]														
Stroke [mm]														
Piston rod thread														
A	Male thread													
I	Female thread													
Cushioning														
P	Flexible cushioning rings/pads at both ends													
Position sensing														
A	Via proximity sensor													
Connection														
QS-4	Integrated push-in fitting for connecting compressed air tubing with standard external Ø 4 mm													
QS-6	Integrated push-in fitting for connecting compressed air tubing with standard external Ø 6 mm													

Compact cylinders ADNP, to ISO 21287, with polymer end caps

Technical data


Function



-  - Diameter
20 ... 50 mm

-  - Stroke length
5 ... 80 mm

-  - www.festo.com



General technical data						
Piston Ø	20	25	32	40	50	
Pneumatic connection	QS-4	QS-4	QS-6	QS-6	QS-6	
Piston rod thread	Female	M6	M6	M8	M8	M10
	Male	M8	M8	M10x1.25	M10x1.25	M10x1.25
Constructional design	Piston					
	Piston rod					
	Cylinder barrel					
Cushioning	Flexible cushioning rings/pads at both ends					
Position sensing	Via proximity sensor					
Type of mounting	Via through-holes					
	Via female threads					
	Via accessories					
Mounting position	Any					

Operating and environmental conditions	
Operating medium	Filtered compressed air, lubricated or unlubricated
Operating pressure [bar]	0.6 ... 10
Ambient temperature ¹⁾ [°C]	-10 ... +60
Corrosion resistance class CRC ²⁾	2

1) Note operating range of proximity sensors

2) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents


Compact cylinders ADNP, to ISO 21287, with polymer end caps

FESTO

Technical data

Forces [N] and impact energy [J]					
Piston Ø	20	25	32	40	50
Theoretical force at 6 bar, advancing	188	295	483	754	1178
Theoretical force at 6 bar, retracting	141	247	415	686	1057
Max. impact energy at the end positions	0.16	0.24	0.32	0.56	0.80


Max. lateral force F_q as a function of the projection x



Weight [g]					
Piston Ø	20	25	32	40	50
Product weight with 0 mm stroke	115	116	204	240	380
Additional weight per 10 mm stroke	17	19	24	32	41
Moving load with 0 mm stroke	20	20	45	55	94
Additional load per 10 mm stroke	2	2	3	3	6

Materials

Sectional view



Compact cylinder		
1	Cover	Polyarylamide
2	Cylinder barrel	Smooth anodised aluminium
3	Piston rod	Smooth anodised aluminium, steel insert with male thread
4	Flange screws	Galvanised steel
-	Seals	Polyurethane, nitrile rubber


Compact cylinders ADNP, to ISO 21287, with polymer end caps

Technical data

Dimensions – Basic version

Download CAD data → www.festo.com

Ø 20 ... 50




Ø [mm]	BG	D1 Ø H9	D2 Ø	E +0.3	G	L2 max.	L3	MM Ø	PL	RT	T2	TG ±0.2	ZJ +1	≈C1
20	19.5	9	4	35.5	12	37	5	10	6	M5	2.1	22	42.7	8
25				39.5		39						26	44.7	
32	26		6	47	15	44		12	8.2	M6		32.5	50.2	10
40				54.5		45						38	51.2	
50	27	12		65.5						16		M8	2.6	46.5

Dimensions – Variants

Download CAD data → www.festo.com

Basic version



Ø [mm]	AF min.	AM -0.5	D9	KF	KK	T4	WH +1	ZJ +1
20	14	16	3.8	M6	M8	2.6	5.7	42.7
25								44.7
32	16	19	4.5	M8	M10x1.25	3.3	6.2	50.2
40								51.2
50	20	22	6	M10	M12x1.25	4.7	8.2	53.2

Compact cylinders ADNP, to ISO 21287, with polymer end caps

Technical data

FESTO

Ordering data						
Type	Piston Ø [mm]	Stroke [mm]	Female piston rod thread		Male piston rod thread	
			Part No.	Type	Part No.	Type
	20	5	539 435	ADNP-20-5-I-P-A-QS-4	539 390	ADNP-20-5-A-P-A-QS-4
		10	539 436	ADNP-20-10-I-P-A-QS-4	539 391	ADNP-20-10-A-P-A-QS-4
		15	539 437	ADNP-20-15-I-P-A-QS-4	539 392	ADNP-20-15-A-P-A-QS-4
		20	539 438	ADNP-20-20-I-P-A-QS-4	539 393	ADNP-20-20-A-P-A-QS-4
		25	539 439	ADNP-20-25-I-P-A-QS-4	539 394	ADNP-20-25-A-P-A-QS-4
		30	539 440	ADNP-20-30-I-P-A-QS-4	539 395	ADNP-20-30-A-P-A-QS-4
		40	539 441	ADNP-20-40-I-P-A-QS-4	539 396	ADNP-20-40-A-P-A-QS-4
		50	539 442	ADNP-20-50-I-P-A-QS-4	539 397	ADNP-20-50-A-P-A-QS-4
		60	539 443	ADNP-20-60-I-P-A-QS-4	539 398	ADNP-20-60-A-P-A-QS-4
	25	5	539 444	ADNP-25-5-I-P-A-QS-4	539 399	ADNP-25-5-A-P-A-QS-4
		10	539 445	ADNP-25-10-I-P-A-QS-4	539 400	ADNP-25-10-A-P-A-QS-4
		15	539 446	ADNP-25-15-I-P-A-QS-4	539 401	ADNP-25-15-A-P-A-QS-4
		20	539 447	ADNP-25-20-I-P-A-QS-4	539 402	ADNP-25-20-A-P-A-QS-4
		25	539 448	ADNP-25-25-I-P-A-QS-4	539 403	ADNP-25-25-A-P-A-QS-4
		30	539 449	ADNP-25-30-I-P-A-QS-4	539 404	ADNP-25-30-A-P-A-QS-4
		40	539 450	ADNP-25-40-I-P-A-QS-4	539 405	ADNP-25-40-A-P-A-QS-4
		50	539 451	ADNP-25-50-I-P-A-QS-4	539 406	ADNP-25-50-A-P-A-QS-4
		60	539 452	ADNP-25-60-I-P-A-QS-4	539 407	ADNP-25-60-A-P-A-QS-4
	32	10	539 453	ADNP-32-10-I-P-A-QS-6	539 408	ADNP-32-10-A-P-A-QS-6
		15	539 454	ADNP-32-15-I-P-A-QS-6	539 409	ADNP-32-15-A-P-A-QS-6
		20	539 455	ADNP-32-20-I-P-A-QS-6	539 410	ADNP-32-20-A-P-A-QS-6
		25	539 456	ADNP-32-25-I-P-A-QS-6	539 411	ADNP-32-25-A-P-A-QS-6
		30	539 457	ADNP-32-30-I-P-A-QS-6	539 412	ADNP-32-30-A-P-A-QS-6
		40	539 458	ADNP-32-40-I-P-A-QS-6	539 413	ADNP-32-40-A-P-A-QS-6
		50	539 459	ADNP-32-50-I-P-A-QS-6	539 414	ADNP-32-50-A-P-A-QS-6
		60	539 460	ADNP-32-60-I-P-A-QS-6	539 415	ADNP-32-60-A-P-A-QS-6
		80	539 461	ADNP-32-80-I-P-A-QS-6	539 416	ADNP-32-80-A-P-A-QS-6
	40	10	539 462	ADNP-40-10-I-P-A-QS-6	539 417	ADNP-40-10-A-P-A-QS-6
		15	539 463	ADNP-40-15-I-P-A-QS-6	539 418	ADNP-40-15-A-P-A-QS-6
		20	539 464	ADNP-40-20-I-P-A-QS-6	539 419	ADNP-40-20-A-P-A-QS-6
		25	539 465	ADNP-40-25-I-P-A-QS-6	539 420	ADNP-40-25-A-P-A-QS-6
		30	539 466	ADNP-40-30-I-P-A-QS-6	539 421	ADNP-40-30-A-P-A-QS-6
		40	539 467	ADNP-40-40-I-P-A-QS-6	539 422	ADNP-40-40-A-P-A-QS-6
		50	539 468	ADNP-40-50-I-P-A-QS-6	539 423	ADNP-40-50-A-P-A-QS-6
		60	539 469	ADNP-40-60-I-P-A-QS-6	539 424	ADNP-40-60-A-P-A-QS-6
		80	539 470	ADNP-40-80-I-P-A-QS-6	539 425	ADNP-40-80-A-P-A-QS-6
	50	10	539 471	ADNP-50-10-I-P-A-QS-6	539 426	ADNP-50-10-A-P-A-QS-6
		15	539 472	ADNP-50-15-I-P-A-QS-6	539 427	ADNP-50-15-A-P-A-QS-6
		20	539 473	ADNP-50-20-I-P-A-QS-6	539 428	ADNP-50-20-A-P-A-QS-6
		25	539 474	ADNP-50-25-I-P-A-QS-6	539 429	ADNP-50-25-A-P-A-QS-6
		30	539 475	ADNP-50-30-I-P-A-QS-6	539 430	ADNP-50-30-A-P-A-QS-6
		40	539 476	ADNP-50-40-I-P-A-QS-6	539 431	ADNP-50-40-A-P-A-QS-6
		50	539 477	ADNP-50-50-I-P-A-QS-6	539 432	ADNP-50-50-A-P-A-QS-6
		60	539 478	ADNP-50-60-I-P-A-QS-6	539 433	ADNP-50-60-A-P-A-QS-6
		80	539 479	ADNP-50-80-I-P-A-QS-6	539 434	ADNP-50-80-A-P-A-QS-6

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO


Foot mounting HNA

Material:

HNA: Galvanised steel

HNA-...-R3: Steel with protective coating

Free of copper, PTFE and silicone



Dimensions and ordering data											
For Ø	AB Ø	AH	AO	AT	AU	SA	TR	US	XA		
[mm]	H14	JS14		±0.5	±0.2		±0.2	−0.5			
12	5.8	21	5	3	13	61	16	26	52.2		
16		22	4.75				18	27.5	52.9		
20	7	27	6.25	4	16	69	22	34.5	58.7		
25		29					26	38.5	60.7		
32		33.5					7	32	46	66.2	
40	10	38	9	5	18	81	36	54	69.2		
50		45	8				21	87	45	64	74.2
63		50							91	50	75
80	12	63	10.5	6	26	106	63	63	89		
100	14.5	74	12.5				75	110	103		

For Ø [mm]	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part No.	Type	CRC ¹⁾	Weight [g]	Part No.	Type
12	2	25	537 237	HNA-12	3	25	537 252	HNA-12-R3
16	2	30	537 238	HNA-16	3	30	537 253	HNA-16-R3
20	2	50	537 239	HNA-20	3	50	537 254	HNA-20-R3
25	2	55	537 240	HNA-25	3	55	537 255	HNA-25-R3
32	2	70	537 241	HNA-32	3	70	537 256	HNA-32-R3
40	2	90	537 242	HNA-40	3	90	537 257	HNA-40-R3
50	2	160	537 243	HNA-50	3	160	537 258	HNA-50-R3
63	2	180	537 244	HNA-63	3	180	537 259	HNA-63-R3
80	2	380	537 249	HNA-80	3	380	537 260	HNA-80-R3
100	2	470	537 250	HNA-100	3	470	537 261	HNA-100-R3

1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.

Corrosion resistance class 3 to Festo standard 940 070

Components requiring higher corrosion resistance. External visible parts in direct contact with industrial atmospheres or media such as solvents and cleaning agents, with a predominantly functional requirement for the surface

Compact cylinders ADN/AEN, to ISO 21287

Accessories


FESTO

Flange mounting FNC

Material:

Galvanised steel

Free of copper, PTFE and silicone



Dimensions and ordering data											
For Ø	E	FB Ø	MF	R	TF	UF	ZF	CRC ¹⁾	Weight	Part No.	Type
[mm]						±1			[g]		
12	28	5.5	8	-	40	50	47.2	2	80	537 245	FNC-12
16	29				43	55	47.9	2	90	537 246	FNC-16
20	36	6.6			55	70	50.7	2	145	537 247	FNC-20
25	40				60	76	52.7	2	170	537 248	FNC-25
32	45	7	10	32	64	80	60.2	2	240	174 376	FNC-32
40	54	9		36	72	90	61.2	2	280	174 377	FNC-40
50	65		12	45	90	110	65.2	2	520	174 378	FNC-50
63	75			50	100	120	69.2	2	690	174 379	FNC-63
80	93	12	16	63	126	150	79	2	1650	174 380	FNC-80
100	110	14		75	150	175	92	2	2400	174 381	FNC-100
125	132	16	20	90	180	210	112	2	3750	174 382	FNC-125

1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO



Swivel flange SNCL

Material:

SNCL: Die-cast aluminium

SNCL-...-R3: Die-cast aluminium with protective coating

Free of copper, PTFE and silicone



Dimensions and ordering data						
For Ø	CD Ø	EW	FL ±0.2	L	MR	XC
[mm]	H9					
12	6	12 _{h12}	16	10	6	55.2
16						55.9
20	8	16 _{h12}	20	14	8	62.7
25						64.7
32	10	26 _{-0.2/-0.6}	22	13	10	72.2
40	12	28 _{-0.2/-0.6}	25	16	12	75.2
50		32 _{-0.2/-0.6}	27			80.2
63	16	40 _{-0.2/-0.6}	32	21	16	89.2
80		50 _{-0.2/-0.6}	36	22		99
100	20	60 _{-0.2/-0.6}	41	27	20	117
125	25	70 _{-0.2/-0.6}	50	30		142

For Ø	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part No.	Type	CRC ¹⁾	Weight [g]	Part No.	Type
[mm]								
12	2	20	537 790	SNCL-12	3	20	537 794	SNCL-12-R3
16	2	25	537 791	SNCL-16	3	25	537 795	SNCL-16-R3
20	2	40	537 792	SNCL-20	3	40	537 796	SNCL-20-R3
25	2	45	537 793	SNCL-25	3	45	537 797	SNCL-25-R3
32	2	85	174 404	SNCL-32	–	–	–	–
40	2	115	174 405	SNCL-40	–	–	–	–
50	2	180	174 406	SNCL-50	–	–	–	–
63	2	270	174 407	SNCL-63	–	–	–	–
80	2	480	174 408	SNCL-80	–	–	–	–
100	2	700	174 409	SNCL-100	–	–	–	–
125	2	1300	174 410	SNCL-125	–	–	–	–

1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.

Corrosion resistance class 3 to Festo standard 940 070

Components requiring higher corrosion resistance. External visible parts in direct contact with industrial atmospheres or media such as solvents and cleaning agents, with a predominantly functional requirement for the surface



Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO

Swivel flange SNCS

Material:
Die-cast aluminium



Dimensions and ordering data											
For Ø	CN	EP	EX	FL	LT	MS	XC	CRC ¹⁾	Weight	Part No.	Type
[mm]	Ø H7	±0.2		±0.2					[g]		
32	10	10.5	14	22	13	15	72.2	2	85	174 397	SNCS-32
40	12	12	16	25	16	17	75.2	2	125	174 398	SNCS-40
50	16	15	21	27	16	20	80.2	2	210	174 399	SNCS-50
63	16	15	21	32	21	22	89.2	2	280	174 400	SNCS-63
80	20	18	25	36	22	27	99	2	540	174 401	SNCS-80
100	20	18	25	41	27	29	117	2	700	174 402	SNCS-100
125	30	25	37	50	30	39	142	2	1410	174 403	SNCS-125


1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Clevis foot LBG

The clevis foot is secured against rotation with a dowel pin.

Material:
Nodular graphite cast iron
Free of copper, PTFE and silicone



Dimensions and ordering data														
For Ø	CL	CM	EK	FL	GL	HB	LE	MR	RF	RG	S1	UK	UX	CRC ¹⁾
[mm]			Ø			Ø					Ø			
32	28	14.1	10	32	16	6.8	24	12	42	20	4.8	56	36	2
40	30	16.1	12	36	20	6.8	26	14	44	26	5.8	58	41.5	2
50	40	21.1	16	45	25	9.2	33	15	56	31	5.8	70	47	2
63	40	21.1	16	50	25	9	38	17	56	31	7.8	70	47	2
80	50	25.1	20	63	30	11	49	18	70	36	7.8	89	57	2
100	50	25.1	20	71	41	11	56	22	70	46	9.8	89	67.5	2
125	80	37.2	30	90	60	14	70	26	106	70	11.8	128	96	2

1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO


Multi-position kit DPNA

Material:

Flange: Aluminium

Screws: Galvanised steel

Free of copper, PTFE and silicone



Note
The maximum overall stroke length may not be exceeded when combining cylinders and multi-position kits.

Dimensions and ordering data						
For Ø	L2	B1	Max. overall stroke length	CRC ¹⁾	Part No.	Type
[mm]			[mm]			
12	35	13	600	2	537 263	DPNA-12
16			600	2	537 264	DPNA-16
20			600	2	537 265	DPNA-20
25			600	2	537 266	DPNA-25
32	44	15	800	2	537 267	DPNA-32
40	45		800	2	537 268	DPNA-40
50			800	2	537 269	DPNA-50
63			800	2	537 270	DPNA-63
80	54	17	1000	2	537 271	DPNA-80
100	67	19.5	1000	2	537 272	DPNA-100

1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Compact cylinders ADN/AEN, to ISO 21287

Accessories



FESTO

Clevis foot LBN

Material:

Galvanised steel

Free of copper, PTFE and silicone



Dimensions and ordering data												
For Ø	CM	EK Ø	FL	GL	HB Ø	LE	MR	RG	UX	CRC ¹⁾	Weight [g]	Part No. Type
[mm]												
12/16	12.1	6	27 +0.3/-0.2	13	5.5	24	7	15	25	2	40	6 058 LBN-12/16
20/25	16.1	8	30 +0.4/-0.2	16	6.6	26	10	20	32	2	81	6 059 LBN-20/25

1) Corrosion resistance class 2 to Festo standard 940 070


Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Clevis foot CRLBN, stainless steel

Material:

High-alloy steel

Free of copper, PTFE and silicone



Dimensions and ordering data												
For Ø	CM	EK Ø	FL	GL	HB Ø	LE	MR	RG	UX	CRC ¹⁾	Weight [g]	Part No. Type
[mm]												
12/16	12.1	6	27 +0.3/-0.2	13	5.5	24	7	15	25	4	55	161 862 CRLBN-12/16
20/25	16.1	8	30 +0.4/-0.2	16	6.6	26	10	20	32	4	62	161 863 CRLBN-20/25

1) Corrosion resistance class 4 to Festo standard 940 070

Components requiring higher corrosion resistance. Parts used with aggressive media, e.g. food or chemical industry. These applications should be supported with special tests with the media if required

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO

Swivel flange


SNCB/SNCB-...-R3

Material:

SNCB: Die-cast aluminium

SNCB-...-R3: Die-cast aluminium with protective coating, high corrosion protection

Free of copper, PTFE and silicone



Dimensions and ordering data							
For Ø	CB	EK Ø	FL	L	MR	UB	XC
[mm]	H14	e8	±0.2			h14	
32	26	10	22	13	8.5	45	72
40	28	12	25	16	12	52	76
50	32	12	27	16	12	60	80
63	40	16	32	21	16	70	89
80	50	16	36	22	16	90	99
100	60	20	41	27	20	110	117
125	70	25	50	30	25	130	142

For Ø [mm]	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part No.	Type	CRC ¹⁾	Weight [g]	Part No.	Type
32	2	100	174 390	SNCB-32	3	100	176 944	SNCB-32-R3
40	2	150	174 391	SNCB-40	3	150	176 945	SNCB-40-R3
50	2	225	174 392	SNCB-50	3	225	176 946	SNCB-50-R3
63	2	365	174 393	SNCB-63	3	365	176 947	SNCB-63-R3
80	2	610	174 394	SNCB-80	3	610	176 948	SNCB-80-R3
100	2	925	174 395	SNCB-100	3	925	176 949	SNCB-100-R3
125	2	1785	174 396	SNCB-125	3	1785	176 950	SNCB-125-R3

1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.

Corrosion resistance class 3 to Festo standard 940 070

Components requiring higher corrosion resistance. External visible parts in direct contact with industrial atmospheres or media such as solvents and cleaning agents, with a predominantly functional requirement for the surface

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO


Trunnion flange ZNCF/CRZNG

Material:

ZNCF: Special steel casting

CRZNG: Electrolytically polished
special steel casting

Free of copper, PTFE and silicone



Dimensions and ordering data									
For Ø	C2	C3	TD Ø e9	TK	TL	TM	US	XH	XL
[mm]									
32	71	86	12	16	12	50	45	2	52
40	87	105	16	20	16	63	54	4	55
50	99	117	16	24	16	75	64	4	57
63	116	136	20	24	20	90	75	4	61
80	136	156	20	28	20	110	93	5	81
100	164	189	25	38	25	132	110	10	86
125	192	217	25	50	25	160	131	14	106

For Ø	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part No.	Type	CRC ¹⁾	Weight [g]	Part No.	Type
[mm]								
32	2	130	174 411	ZNCF-32	4	150	161 852	CRZNG-32
40	2	240	174 412	ZNCF-40	4	260	161 853	CRZNG-40
50	2	390	174 413	ZNCF-50	4	430	161 854	CRZNG-50
63	2	600	174 414	ZNCF-63	4	640	161 855	CRZNG-63
80	2	1150	174 415	ZNCF-80	4	1300	161 856	CRZNG-80
100	2	2030	174 416	ZNCF-100	4	2400	161 857	CRZNG-100
125	2	3490	174 417	ZNCF-125	4	3600	185 362	CRZNG-125

1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.

Corrosion resistance class 4 to Festo standard 940 070

Components requiring higher corrosion resistance. Parts used with aggressive media, e.g. food or chemical industry. These applications should be supported with special tests with the media if required

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO



Trunnion support LN2G

Material:

Trunnion support: Anodised aluminium

Plain bearing: Plastic

Free of copper, PTFE and silicone



Dimensions and ordering data															
For Ø	CR	DA	FK	FN	FS	H1	HB	KE	NH	TH	UL	CRC ¹⁾	Weight	Part No.	Type
[mm]	Ø D11	Ø H13	Ø ±0.1				Ø H13			±0.2			[g]		
32	12	11	15	30	10.5	15	6.6	6.8	18	32	46	2	125	32 959	LN2G-32
40, 50	16	15	18	36	12	18	9	9	21	36	55	2	400	32 960	LN2G-40/50
63, 80	20	18	20	40	13	20	11	11	23	42	65	2	480	32 961	LN2G-63/80
100, 125	25	20	25	50	16	24.5	14	13	28.5	50	75	2	960	32 962	LN2G-100/125



1) Corrosion resistance class 2 to Festo standard 940 070

Components subject to moderate corrosion stress. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO



Ordering data – Piston rod attachments				Technical data → Internet: piston-rod attachment			
Designation	For Ø	Part No.	Type	Designation	For Ø	Part No.	Type
Rod eye SGS				Rod clevis SGA used in combination with rod eye SGS			
	12	–			12, 16, 20, 25	–	
	16	9 254	SGS-M6		32, 40	32 954	SGA-M10x1,25
	20, 25	9 255	SGS-M8		50, 63	10 767	SGA-M12x1,25
	32, 40	9 261	SGS-M10x1,25		80, 100	10 768	SGA-M16x1,25
	50, 63	9 262	SGS-M12x1,25		125	10 769	SGA-M20x1,25
	80, 100	9 263	SGS-M16x1,5				
	125	9 264	SGS-M20x1,5				
				Self-aligning rod coupler FK			
	12		30 984	FK-M5			
	16		2 061	FK-M6			
	20, 25		2 062	FK-M8			
	32, 40		6 140	FK-M10x1,25			
	50, 63		6 141	FK-M12x1,25			
	80, 100		6 142	FK-M16x1,5			
	125		6 143	FK-M20x1,5			
				Coupling piece KSZ			
	12		–				
	16		36 123	KSZ-M6			
	20, 25		36 124	KSZ-M8			
	32, 40		36 125	KSZ-M10x1,25			
	50, 63		36 126	KSZ-M12x1,25			
	80, 100		36 127	KSZ-M16x1,5			
	125		36 128	KSZ-M20x1,5			
Coupling piece KSG							
	12, 16, 20, 25	–					
	32, 40	32 963	KSG-M10x1,25				
	50, 63	32 964	KSG-M12x1,25				
	80, 100	32 965	KSG-M16x1,5				
	125	32 966	KSG-M20x1,5				
Adapter AD							
	12		–				
	16	157 328	AD-M6-M5				
		157 329	AD-M6-1/8				
		157 330	AD-M6-1/4				
	20	157 331	AD-M8-1/8				
	25	157 332	AD-M8-1/4				
	32	157 333	AD-M10x1,25-1/8				
	40	157 334	AD-M10x1,25-1/4				
	50	160 256	AD-M12x1,25-1/4				
	63	160 257	AD-M12x1,25-3/8				

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO

Ordering data – Corrosion and acid resistant piston rod attachments				Technical data → Internet: crsg			
Designation	For Ø	Part No.	Type	Designation	For Ø	Part No.	Type
Rod eye CRS GS				Rod clevis CRS G			
	12	–			12	–	
	16	195 580	CRSGS-M6		16, 20	13 567	CRSG-M6
	20, 25	195 581	CRSGS-M8		20, 25	13 568	CRSG-M8
	32, 40	195 582	CRSGS-M10x1,25		32, 40	13 569	CRSG-M10x1,25
	50, 63	195 583	CRSGS-M12x1,25		50, 63	13 570	CRSG-M12x1,25
	80, 100	195 584	CRSGS-M16x1,5		80, 100	13 571	CRSG-M16x1,5
	125	195 585	CRSGS-M20x1,5		125	13 572	CRSG-M20x1,5

Ordering data – Mounting attachments				Technical data → Internet: clevis foot			
Designation	For Ø	Part No.	Type	Designation	For Ø	Part No.	Type
Clevis foot LBG for rod eye SGS				Right-angle clevis foot LQG for rod eye SGS			
	32, 40	31 761	LBG-32		32, 40	31 768	LQG-32
	50, 63	31 762	LBG-40		50, 63	31 769	LQG-40
	80, 100	31 763	LBG-50		80, 100	31 770	LQG-50
		31 764	LBG-63			31 771	LQG-63
	125	31 765	LBG-80		125	31 772	LQG-80
		31 766	LBG-100			31 773	LQG-100

Ordering data – One-way flow control valves					Technical data → Internet: grla	
	Connection		Material	Part No.	Type	
	For Ø	For tubing O.D.				
For exhaust air						
	12, 16, 20, 25	3	Metal design	193 137	GRLA-M5-QS-3-D	
		4		193 138	GRLA-M5-QS-4-D	
		6		193 139	GRLA-M5-QS-6-D	
	32, 40, 50, 63, 80, 100	3		193 142	GRLA-1/8-QS-3-D	
		4		193 143	GRLA-1/8-QS-4-D	
		6		193 144	GRLA-1/8-QS-6-D	
		8		193 145	GRLA-1/8-QS-8-D	
	125	6		193 146	GRLA-1/4-QS-6-D	
		8		193 147	GRLA-1/4-QS-8-D	
		10		193 148	GRLA-1/4-QS-10-D	



Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO

Ordering data – One-way flow control valves				Technical data → Internet: grlz	
	Connection		Material	Part No.	Type
	For Ø	For tubing O.D.			
For supply air					
	12, 16, 20, 25	3	Metal design	193 153	GRLZ-M5-QS-3-D
		4		193 154	GRLZ-M5-QS-4-D
		6		193 155	GRLZ-M5-QS-6-D
	32, 40, 50, 63, 80, 100	3		193 156	GRLZ-1/8-QS-3-D
		4		193 157	GRLZ-1/8-QS-4-D
		6		193 158	GRLZ-1/8-QS-6-D
		8		193 159	GRLZ-1/8-QS-8-D
		125		–	151 195

Ordering data – One-way flow control valves for cylinder ADNP			Technical data → Internet: vfoc	
	Connection		Part No.	Type
	For Ø			
Inline				
	20, 25		540 362	VFOC-E-S4-Q4
	32, 40, 50		540 363	VFOC-E-S6-Q6

Ordering data – Proximity sensors for T-slot, magneto-resistive					Technical data → Internet: smt	
	Type of mounting	Switch output	Electrical connection	Cable length [m]	Part No.	Type
N/O contact						
	Insertable in the slot from above, flush with cylinder profile	PNP	Cable, 3-wire	2.5	543 867	SMT-8M-PS-24V-K-2,5-OE
			Plug M8x1, 3-pin	0.3	543 866	SMT-8M-PS-24V-K-0,3-M8D
			Plug M12x1, 3-pin	0.3	543 869	SMT-8M-PS-24V-K-0,3-M12
		NPN	Cable, 3-wire	2.5	543 870	SMT-8M-NS-24V-K-2,5-OE
			Plug M8x1, 3-pin	0.3	543 871	SMT-8M-NS-24V-K-0,3-M8D
	Insertable in the slot lengthwise, flush with the cylinder profile	PNP	Cable, 3-wire	2.5	175 436	SMT-8-PS-K-LED-24-B
			Plug M8x1, 3-pin	0.3	175 484	SMT-8-PS-S-LED-24-B
N/C contact						
	Insertable in the slot from above, flush with cylinder profile	PNP	Cable, 3-wire	7.5	543 873	SMT-8M-PO-24V-K7,5-OE

Compact cylinders ADN/AEN, to ISO 21287

Accessories

FESTO

Ordering data – Proximity sensors for T-slot, magnetic reed					Technical data ➔ Internet: sme	
	Type of mounting	Switch output	Electrical connection	Cable length [m]	Part No.	Type
N/O contact						
	Insertable in the slot from above, flush with cylinder profile	Contacting	Cable, 3-wire	2.5	543 862	SME-8M-DS-24V-K-2,5-OE
				5.0	543 863	SME-8M-DS-24V-K-5,0-OE
			Cable, 3-wire	2.5	543 872	SME-8M-ZS-24V-K-2,5-OE
			Plug M8x1, 3-pin	0.3	543 861	SME-8M-DS-24V-K-0,3-M8D
	Insertable in the slot lengthwise, flush with the cylinder profile	Contacting	Cable, 3-wire	2.5	150 855	SME-8-K-LED-24
			Plug M8x1, 3-pin	0.3	150 857	SME-8-S-LED-24
N/C contact						
	Insertable in the slot lengthwise, flush with the cylinder profile	Contacting	Cable, 3-wire	7.5	160 251	SME-8-O-K-LED-24

Ordering data – Connecting cables				Technical data → Internet: nebu	
	Electrical connection, left	Electrical connection, right	Cable length [m]	Part No.	Type
	Straight socket, M8x1, 3-pin	Cable, open end, 3-wire	2.5	541 333	NEBU-M8G3-K-2.5-LE3
			5	541 334	NEBU-M8G3-K-5-LE3
	Straight socket, M12x1, 5-pin	Cable, open end, 3-wire	2.5	541 363	NEBU-M12G5-K-2.5-LE3
			5	541 364	NEBU-M12G5-K-5-LE3
	Angled socket, M8x1, 3-pin	Cable, open end, 3-wire	2.5	541 338	NEBU-M8W3-K-2.5-LE3
			5	541 341	NEBU-M8W3-K-5-LE3
	Angled socket, M12x1, 5-pin	Cable, open end, 3-wire	2.5	541 367	NEBU-M12W5-K-2.5-LE3
			5	541 370	NEBU-M12W5-K-5-LE3

Ordering data – Rectangular proximity sensors, pneumatic			Technical data → Internet: smpo	
	Pneumatic connection		Part No.	Type
3/2-way valve, normally closed				
	Female thread M5		178 563	SMPO-8E

Ordering data – Mounting kits for proximity sensors SMPO-8E			Technical data → Internet: smb	
	Assembly		Part No.	Type
	Clamped in T-slot		178 230	SMB-8E

Ordering data – Slot cover for T-slot					
	Assembly	Length		Part No.	Type
	Insertable from above	2x 0.5 m		151 680	ABP-5-S