FESTO



Sealing ring O/CRO

Sealing ring CRO for use in the chemicals and food processing industries

Pressure

-0.95 ... +10 bar

Material:


Sealing ring O: Polyvinyl chloride Sealing ring O-M3-B: Polyamide Note on materials:

Free of copper and PTFE

Conforms to RoHS (0-1/8 ... 0-3/4 only)

Sealing ring CRO: Polyvinylidenefluoride Note on materials: Conforms to RoHS





FESTO

Dimensions ar	nd ordering data							
For thread	Temperature range [°C]	D1	D2	B1	Part No.	Туре		PU*
Sealing ring O								
M3	-40 +100	2.8	4.8	0.3	30290	O-M3-B		1
M5	-10 +60	5.1	8	1	3565	O-M5		1
					534226	O-M5-500		500
G ¹ / ₈		10	13	1.5	2223	0-1/8		1
					534227	0-1/8-500		500
G1/4		13.2	18	2	2224	0-1/4		1
					534228	0-1/4-200		200
G3/8		16.8	22	2	2225	0-3/8		1
					534229	0-3/8-200		200
G1/2		21	28	2	2226	0-1/2		1
					534230	0-1/2-100		100
G3/4		26.5	33	2	2227	0-3/4		1
G1		33.3	38.9	2	210893	0-1		1
Sealing ring CF	RO							
M5	-40 +80	5.1	8	1	165191	CRO-M5		1
G1/8		10	13	2	575895	CRO-1/8	-0-	1
G1/4		13.2	18	2	165193	CRO-1/4		1
G3/8		16.8	22	2	165194	CRO-3/8		1
G ¹ / ₂		21	28	2	165195	CRO-1/2		1
G3/4		26.5	33	2	165196	CRO-3/4		1
G1		33.3	38.9	2	165197	CRO-1		1

^{*} Packaging unit quantity

-0.95 ... +30 bar


Sealing ring OL Temperature range with metal housing -40 ... +100 °C

• Based on ISO 16030 standard Pressure

 Seals at room temperature when tightened by hand

 Captive Note on materials: Reusable Free of copper and PTFE • Compatible with the existing O and Conforms to RoHS OK sealing rings





Dimensions a	nd ordering data											
For thread	Min. tightening	Max. tightening	D1	D2	D3	B1	B2	CRC ¹⁾	Weight	Part No.	Туре	PU*
	torque	torque										
	[Nm]	[Nm]							[g]			
Stainless stee	l, nitrile rubber											
M5	0.5	6	5.05	7.4	6.25	1.45	5 1	2	1	34634	OL-M5	1
										534231	OL-M5-500	500
G ¹ /8 1	1	26	9.8	12.8	11.1	1.8	3 1.3	2	1	33840	0L-1/8	1
										534232	OL-1/8-500	500
G1/4	2	40	13.2	16.8	14.4	.4 2.2	.2 1.6	2	1	34635	OL-1/4	1
										534233	OL-1/4-200	200
Aluminium, ni	itrile rubber											
G3/8	10	50	16.65	20.5	17.9	2.95	1.95	2	2	34636	OL-3/8	1
										534234	OL-3/8-200	200
G ¹ / ₂	18	8 80	21	25.5	22.2	2.6	1.95	95 2	2	34637	OL-1/2	1
										534235	OL-½-100	100
G3/4	-	120	26.5	32	28.4	2.6	1.95	2	2	34638	OL-3/4	1

¹⁾ Corrosion resistance class 2 according to Festo standard 940 070 Components requiring moderate corrosion resistance. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.

Packaging unit quantity

Sealing ring OK Temperature range with support ring

• Based on ISO 16030 standard

• Seals at room temperature when tightened by hand

• Captive design


• Compatible with the existing O and OL sealing rings

−10 ... +60 °C


Pressure -0.95 ... +10 bar

Note on materials: Free of copper and PTFE Conforms to RoHS









Dimensions an	d ordering data									
For thread	Min. tightening torque	Max. tightening torque	D1	D2	B1	CRC ¹⁾	Weight	Part No.	Туре	PU*
	[Nm]	[Nm]					[g]			
Stainless steel,	, nitrile rubber									
M3	0.15	0.8	2.5	5.5	0.5	2	0.04	130849	OK-M3	1
M5	0.25	2.4	4.3	7.8	0.5		0.1	130850	OK-M5	1
M7	0.3	6.4	6.4	9.8	0.5		0.1	130851	OK-M7	1
Polyamide, the	rmoplastic polyuretha	ne								
G1/8	2	5	9.9	13.15	1.60	2	0.12	531771	OK-1/8	1
G1/4	10	12	13.3	18.15	2.20		0.32	531772	OK-1/4	1
G3/8	10	15	16.8	22.15	2.20		0.44	531773	OK-3/8	1
G1/2	10	18	21.2	26.45	2.35		0.6	531774	OK-1/2	1
G3/4	30	40	26.7	32.45	2.95		1	531775	OK-3/4	1

Corrosion resistance class 2 according to Festo standard 940 070 Components requiring moderate corrosion resistance. Externally visible parts with primarily decorative surface requirements which are in direct contact with a normal industrial environment or media such as coolants or lubricating agents.

Packaging unit quantity

Sealing ring assortment OL-S1

This polymer assortment box contains OL sealing rings ranging in size from M5 to G3/4.



Ordering data									
Contents	Quantity	Min. tightening torque [Nm]	Max. tightening torque [Nm]	Weight [g]	Part No.	Туре			
OL-M5	50	0.5	6	1	161355	OL-S1			
0L-1/8	100	1	26	1					
OL-1/4	100	2	40	1					
OL-3/8	40	10	50	2					
0L-1/2	30	18	80	2					
OL-3/4	10	-	120	2					

Sealing ring assortment OK-S1

This assortment box contains OK sealing rings ranging in size from M3 to G3/4.

Note on materials: Conforms to RoHS



Ordering data									
Contents	Quantity	Min. tightening torque [Nm]	Max. tightening torque [Nm]	Weight [g]	Part No.	Туре			
OK-M3	50	0.15	0.8	0.04	570465	OK-S1			
OK-M5	100	0.25	2.4	0.1					
OK-M7	50	0.3	6.4	0.1					
OK-1/8	100	2	5	0.12					
OK-1/4	100	10	12	0.32					
OK-3/8	40	10	15	0.44					
OK-1/2	30	10	18	0.6					
OK-3/4	10	30	40	1					

Thread sealing tape GWB-0,1



Ordering data										
Width	Thickness	Length	Part No.	Туре						
[mm]	[mm]	[m]								
10	0.1	12.5	9076	GWB-0,1						

Product Range and Company Overview

A Complete Suite of Automation Services

Our experienced engineers provide complete support at every stage of your development process, including: conceptualization, analysis, engineering, design, assembly, documentation, validation, and production.



Custom Automation Components Complete custom engineered solutions



Custom Control Cabinets Comprehensive engineering support and on-site services



Complete Systems Shipment, stocking and storage services

The Broadest Range of Automation Components

With a comprehensive line of more than 30,000 automation components, Festo is capable of solving the most complex automation requirements.



Electromechanical Electromechanical actuators, motors, controllers & drives



Pneumatics Pneumatic linear and rotary actuators, valves, and air supply



PLCs and I/O Devices PLC's, operator interfaces, sensors and I/O devices

Supporting Advanced Automation... As No One Else Can!

Festo is a leading global manufacturer of pneumatic and electromechanical systems, components and controls for industrial automation, with more than 12,000 employees in 56 national headquarters serving more than 180 countries. For more than 80 years, Festo has continuously elevated the state of manufacturing with innovations and optimized motion control solutions that deliver higher performing, more profitable automated manufacturing and processing equipment. Our dedication to the advancement of automation extends beyond technology to the education and development of current and future automation and robotics designers with simulation tools, teaching programs, and on-site services.

Quality Assurance, ISO 9001 and ISO 14001 Certifications

Festo Corporation is committed to supply all Festo products and services that will meet or exceed our customers' requirements in product quality, delivery, customer service and satisfaction.

To meet this commitment, we strive to ensure a consistent, integrated, and systematic approach to management that will meet or exceed the requirements of the ISO 9001 standard for Quality Management and the ISO 14001 standard for Environmental Management.



© Copyright 2008, Festo Corporation. While every effort is made to ensure that all dimensions and specifications are correct, Festo cannot guarantee that publications are completely free of any error, in particular typing or printing errors. Accordingly, Festo cannot be held responsible for the same. For Liability and Warranty conditions, refer to our "Terms and Conditions of Sale", available from your local Festo office. All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, electronic, mechanical, photocopying or otherwise, without the prior written permission of Festo. All technical data subject to change according to technical update.



Festo North America

Festo Regional Contact Center

5300 Explorer Drive Mississauga, Ontario L4W 5G4 Canada

USA Customers:

For ordering assistance,

Call: 1.800.99.FESTO (1.800.993.3786) 1.800.96.FESTO (1.800.963.3786) Email: customer.service@us.festo.com For technical support,

Call: 1.866.GO.FESTO (1.866.463.3786) Fax: 1.800.96.FESTO (1.800.963.3786) Email: product.support@us.festo.com

Canadian Customers:

Call: 1.877.GO.FESTO (1.877.463.3786) Fax: 1.877.FX.FESTO (1.877.393.3786) Email: festo.canada@ca.festo.com

USA Headquarters

Festo Corporation 395 Moreland Road P.O. Box 18023 Hauppauge, NY 11788, USA www.festo.com/us

USA Sales Offices

Appleton

North 922 Tower View Drive, Suite N Greenville, WI 54942, USA

Boston

120 Presidential Way, Suite 330 Woburn, MA 01801, USA

Chicago

1441 East Business Center Drive Mt. Prospect, IL 60056, USA

Dallas

1825 Lakeway Drive, Suite 600 Lewisville, TX 75057, USA

Detroit – Automotive Engineering Center 2601 Cambridge Court, Suite 320 Auburn Hills, MI 48326, USA

New York

395 Moreland Road Hauppauge, NY 11788, USA

Silicon Valley

4935 Southfront Road, Suite F Livermore, CA 94550, USA

United States



USA Headquarters, East: Festo Corp., 395 Moreland Road, Hauppauge, NY 11788 Phone: 1.631.435.0800; Fax: 1.631.435.8026;

Email: info@festo-usa.com www.festo.com/us

Canada



Headquarters: Festo Inc., 5300 Explorer Drive, Mississauga, Ontario L4W 5G4 Phone: 1.905.624.9000; Fax: 1.905.624.9001; Email: festo.canada@ca.festo.com

Mexico



Headquarters: Festo Pneumatic, S.A., Av. Ceylán 3, Col. Tequesquinahuac, 54020 Tlalnepantla, Edo, de México Phone: 011 52 [55] 53 21 66 00; Fax: 011 52 [55] 53 21 66 65; Email: festo.mexico@mx.festo.com www.festo.com/mx

Central USA

Festo Corporation 1441 East Business Center Drive Mt. Prospect, IL 60056, USA Phone: 1.847.759.2600 Fax: 1 847 768 9480



Western USA

Festo Corporation 4935 Southfront Road, Livermore, CA 94550. USA

Phone: 1.925.371.1099 Fax: 1.925.245.1286



Festo Worldwide

Argentina Australia Austria Belarus Belgium Brazil Bulgaria Canada Chile China Colombia Croatia Czech Republic Denmark Estonia Finland France Germany Great Britain Greece Hong Kong Hungary India Indonesia Iran Ireland Israel Italy Japan Latvia Lithuania Malaysia Mexico Netherlands New Zealand Norway Peru Philippines Poland Romania Russia Serbia Singapore Slovakia Slovenia South Africa South Korea Spain Sweden Switzerland Taiwan Thailand Turkey Ukraine United States Venezuela