Electrical connection technology, for fieldbus connection

Technical data – FBS/FBSD

- Plug/plug socket for fieldbus connection
- Can be assembled with any cable length
- 5-pin plug/4-pin or 5-pin socket
- With screw terminals
- Wire cross section of up to 0.75 mm²



General technical data FBSD-... FBS-... Туре Type of mounting Union nut M12 Mounting position Any Electrical connection Type A EN 61076-2-101, EN 61984 Based on standard Connection cross section [mm²] 0.25 ... 0.75 Max. tightening torque for locking [Nm] 0.5 Acceptable current load at 40 °C [A] 4 Protection class to EN 60529 IP67 (assembled) Material of housing Reinforced polyamide Brass, coated with white bronze of contacts Nickel-plated and gold-plated brass FBSD-GD-9-5POL: nickel-plated and gold-plated brass of union nut Nickel-plated die-cast zinc of seals Nitrile rubber Note on materials Conforms to RoHS Fire protection classification to UL94 HB,V2 CE mark (see declaration of conformity) To EU Low Voltage Directive Degree of contamination 3 Ambient temperature -40 ... +85 [°C]

FESTO

Electrical connection technology, for fieldbus connection Technical data – FBS/FBSD

FESTO

.

Ordering data								
	Electrical connection	Operating voltage range [V AC] [V DC]		Cable connection	Permitted cable \emptyset [mm]	Product weight [g]	Part No.	Туре
OF T	Straight plug, 5-pin, screw terminal	60	60	Pg9	6 8	23.5	175380	FBS-M12-5GS-PG9
	Straight socket, 4-pin, screw terminal	250	250	Pg7	4 6	28	18497	FBSD-GD-7
	Straight socket, 4-pin, screw terminal	250	250	Pg9	8 9.5	29	18495	FBSD-GD-9
	Straight socket, 5-pin, screw terminal (DeviceNet)	60	60	Pg9	6 8	33	18324	FBSD-GD-9-5POL
	Straight socket, 4-pin, screw terminal	250	250	Pg13.5	10 12	40	18496	FBSD-GD-13,5
	Angled socket, 4-pin, screw terminal	250	250	Pg7	4 6	25	18524	FBSD-WD-7
	Angled socket, 4-pin, screw terminal	250	250	Pg9	6 8	30	18525	FBSD-WD-9

Electrical connection technology, for fieldbus connection Technical data – FBS/FBSD

FESTO

