


Solenoid valve, inch VZWM

FESTO



Characteristics

At a glance

- Indirectly actuated poppet valve with diaphragm seal
- Process valve connection N14 ...N2
- Flow rate 1400 ... 31000 l/min
- Brass or cast stainless steel version
- Wide range of coils

Type code

001	Series	
VZWM	Solenoid valve, process directional control valve VZWM	
002	Directional control valve type	
L	In-line valve	
003	Valve function	
M22C	2/2-way valve, normally closed	

004	Process valve connection	
N14	1/4 NPT	
N38	3/8 NPT	
N12	1/2 NPT	
N34	3/4 NPT	
N1	1 NPT	
N114	1 1/4 NPT	
N112	1 1/2 NPT	
N2	2 NPT	

005	Electrical connection	
F4	Electric with armature tube for solenoid coil 8	
F5	Electric with armature tube for solenoid valve 13	

006	Corrosion protection	
	Standard	
R1	Stainless steel	

Datasheet

General technical data NPT thread

Connection Process valve	1/4 NPT	3/8 NPT	1/2 NPT	3/4 NPT	1 NPT	1 1/4 NPT	1 1/2 NPT	2 NPT
Nominal size	13 ... 13.5 mm			25 ... 27.5 mm		40 mm		50 mm
Valve function	2/2-way, closed, monostable							
Design	Diaphragm valve, servo-controlled							
Sealing principle	Soft							
Type of actuation	Electric							
Type of piloting	Pilot actuated							
Flow direction	Non-reversible							
Type of mounting	In-line installation							
Mounting position	Preferably vertical							
Standard nominal flow rate (standardised to DIN 1343)	1,400 l/min	2,100 l/min	2,400 l/min	10,000 l/min	11,700 l/min	24,000 l/min	26,400 l/min	31,000 l/min
Flow rate Kv	1.6 m³/h	2 m³/h	2.4 m³/h	8.5 m³/h	10.7 m³/h	21.3 m³/h	27.4 m³/h	39 m³/h
C value	6 l/sbar	8.8 l/sbar	9.8 l/sbar	39 l/sbar	41 l/sbar	75 l/sbar	82 l/sbar	110 l/sbar
b value	0.3	0.35	0.37	0.5	0.57	0.6	0.67	0.68
Pressure difference	0.5 bar					0.7 bar		
Material housing	Stainless steel casting, Brass							
Material number housing	1.4581, 2.0402							
Material seals	NBR							
Material plunger tube	High-alloy steel							
Note on materials	RoHS-compliant							
Max. tightening torque for connecting thread	35 Nm	60 Nm	105 Nm	200 Nm	350 Nm	450 Nm	540 Nm	620 Nm
Max. tightening torque for cover screw	20 Nm			30 Nm				
Max. tightening torque for coil fastening	0.5 ... 2 Nm					2 Nm		

Operating and environmental conditions NPT thread

Connection Process valve	1/4 NPT	3/8 NPT	1/2 NPT	3/4 NPT	1 NPT	1 1/4 NPT	1 1/2 NPT	2 NPT
Medium	Compressed air to ISO 8573-1:2010 [7:4:4], Inert gases, Water, Neutral fluids							
Ambient temperature ¹⁾	-10 ... 60°C							
Pressure difference	0.5 bar					0.7 bar		
Medium pressure, valve for liquid media	0.5 ... 6 bar					0.7 ... 6 bar		
Medium pressure, valve for gaseous media	0.5 ... 10 bar					0.7 ... 10 bar		
Media temperature	-10 ... 60°C							
Media temperature for fluids	5 ... 50°C							
Max. viscosity	22 mm²/s							
CE mark (see declaration of conformity)	–			In accordance with EU Pressure Equipment Directive				
UKCA marking (see declaration of conformity)	–			to UK Pressure Equipment Regulations				
Corrosion resistance class CRC ²⁾	1 - Low corrosion stress, 3 - high corrosion stress							

1) Note the ambient temperature of the solenoid coils.

2) Corrosion resistance class CRC 1 to Festo standard FN 940 070. Parts with low corrosion stress. Transport and storage protection. Parts that do not have primarily decorative surface requirements e.g. in non-visible interior areas, or parts that are covered.

Corrosion resistance class 3 to Festo standard 940 070. Components subject to high corrosion stress. External visible parts in direct contact with a normal industrial environment or media, such as solvents and cleaners, with primarily functional surface requirements.

Valve switching times NPT thread

Connection Process valve	1/4 NPT	3/8 NPT	1/2 NPT	3/4 NPT	1 NPT	1 1/4 NPT	1 1/2 NPT	2 NPT
Switching time off	10 ms			12 ms		20 ms		21 ms
Switching time on	8 ms			15 ms		26 ms		62 ms
Switch-off time for fluids	200 ... 210 ms	190 ... 210 ms	200 ... 220 ms	930 ... 950 ms		1,900 ms	2,000 ms	2,800 ms
Switch-on time for fluids	80 ... 100 ms	110 ms		400 ... 420 ms	300 ... 400 ms	1,400 ms		2,100 ms

Datasheet

Electrical data G thread


Connection Process valve	G1/4	G3/8	G1/2	G3/4	G1	G1 1/4	G1 1/2	G2
Electrical connection	Solenoid coil type MD-... , coil can be ordered as an accessory, Solenoid coil type MH-... , coil can be ordered as an accessory					Solenoid coil type MH-... , coil can be ordered as an accessory		

Weight NPT thread

Connection Process valve	1/4 NPT	3/8 NPT	1/2 NPT	3/4 NPT	1 NPT	1 1/4 NPT	1 1/2 NPT	2 NPT
Product weight	400 ... 500 g	400 ... 450 g	400 ... 415 g	1,200 ... 1,220 g	1,100 ... 1,200 g	2,600 ... 2,700 g	2,500 ... 2,510 g	3,700 ... 4,000 g

Dimensions

Dimensions – 2/2-way valve, NPT


Download CAD data www.festo.com

- [1] Connection for plug socket according to DIN EN 17301-803, type A
 [2] Plug socket MSSD-N
 [3] Space for inscription label
 [4] Retaining bracket HRM-...

	B ±1,5	D	D1	H ±2	H1 ±1,5	H2 ±1	L ±2	L1 ±1,5	L2	F	T1	T2 ±0,5	≈G
VZWM-L-M22C-N14-F4	48	1/4NPT	M4	85,5	15	49	67	25	21	F5	12	4	27
VZWM-L-M22C-N38-F4	48	3/8NPT	M4	85,5	15	49	67	25	21	F5	12	4	27
VZWM-L-M22C-N12-F4	48	1/2NPT	M4	85	15	49	67	25	21	F5	12	4	27
VZWM-L-M22C-N34-F4	70	3/4NPT	M6	107	24,2	70,5	96	40	28	F5	16	6	41
VZWM-L-M22C-N1-F4	70	1NPT	M6	107	24,2	70,5	96	40	28	F5	16	6	41
VZWM-L-M22C-N114-F5	96	1 1/4NPT	M6	143,5	32,5	87	140	59,5	40,25	F5	22	6	58
VZWM-L-M22C-N112-F5	96	1 1/2NPT	M6	143,5	32,5	87	140	59,5	40,25	F5	22	6	58
VZWM-L-M22C-N2-F5	112	2NPT	M6	159	38,5	103,5	168	59,5	54,25	F5	25	6	70
VZWM-L-M22C-N14-F5-R1	44	1/4NPT	M4	106	15,6	51	67	25	21	F4	–	4	27
VZWM-L-M22C-N38-F5-R1	44	3/8NPT	M4	106	15,6	51	67	25	21	F4	–	4	27
VZWM-L-M22C-N12-F5-R1	44	1/2NPT	M4	106	15,6	51	67	25	21	F4	–	4	27
VZWM-L-M22C-N34-F5-R1	70	3/4NPT	M6	126	24,2	70	96	40	28	F4	–	6	41
VZWM-L-M22C-N1-F5-R1	70	1NPT	M6	126	24,2	70	96	40	28	F4	–	6	41
VZWM-L-M22C-N114-F5-R1	96	1 1/4NPT	M6	145	34	89,5	140	59,5	40,25	F5	–	6	58
VZWM-L-M22C-N112-F5-R1	96	1 1/2NPT	M6	145	34	89,5	140	59,5	40,25	F5	–	6	58
VZWM-L-M22C-N2-F5-R1	112	2NPT	M6	159	38,5	104	168	59,5	40,25	F5	–	6	70

Dimensions

Dimensions – Mounting bracket HRM


[Download CAD data](#) www.festo.com



	B1	B2	B3	D1 Ø	D2 Ø	H1	H2	L1	L2 ±0,1
HRM-1	25	12,5	2	6	5	37	10	40	25
HRM-2	35	17,5	3	7	7	66	16	55	40
HRM-3	47	23,5	3	9	7	87	23	75	59,5


Ordering data


Ordering data					
	Connection Process valve	Nominal size	Electrical connection	Part no.	Type
	1/4 NPT	13 mm	Solenoid coil type MH- ..., coil can be ordered as an accessory	546170	VZWM-L-M22C-N14-F5-R1
		13.5 mm	Solenoid coil type MD- ..., coil can be ordered as an accessory	546154	VZWM-L-M22C-N14-F4
	3/8 NPT	13 mm	Solenoid coil type MH- ..., coil can be ordered as an accessory	546171	VZWM-L-M22C-N38-F5-R1
		13.5 mm	Solenoid coil type MD- ..., coil can be ordered as an accessory	546155	VZWM-L-M22C-N38-F4
	1/2 NPT	13 mm	Solenoid coil type MH- ..., coil can be ordered as an accessory	546172	VZWM-L-M22C-N12-F5-R1
		13.5 mm	Solenoid coil type MD- ..., coil can be ordered as an accessory	546156	VZWM-L-M22C-N12-F4
	3/4 NPT	25 mm	Solenoid coil type MH- ..., coil can be ordered as an accessory	546173	VZWM-L-M22C-N34-F5-R1
		27.5 mm	Solenoid coil type MD- ..., coil can be ordered as an accessory	546157	VZWM-L-M22C-N34-F4
	1 NPT	25 mm	Solenoid coil type MH- ..., coil can be ordered as an accessory	546174	VZWM-L-M22C-N1-F5-R1
		27.5 mm	Solenoid coil type MD- ..., coil can be ordered as an accessory	546158	VZWM-L-M22C-N1-F4
	1 1/4 NPT	40 mm	Solenoid coil type MH- ..., coil can be ordered as an accessory	546159	VZWM-L-M22C-N114-F5
	1 1/2 NPT			546175	VZWM-L-M22C-N114-F5-R1
				546176	VZWM-L-M22C-N112-F5-R1
				546160	VZWM-L-M22C-N112-F5
		546177		VZWM-L-M22C-N2-F5-R1	
	2 NPT	50 mm		546161	VZWM-L-M22C-N2-F5

Accessories

Mounting bracket HRM			
	Product weight	Part no.	Type
	39 g	9769	HRM-1
	130 g	9770	HRM-2
	246 g	9771	HRM-3

Solenoid coil for VZWM- ... -F4- ...				
	Ambient temperature	Product weight	Part no.	Type
	-20 ... 50 °C	110 g	549905	MD-2-230VAC-PA
			★ 549903	MD-2-24VDC-PA
			549904	MD-2-110VAC-PA

Solenoid coil for VZWM- ... -F5- ...				
	Ambient temperature	Product weight	Part no.	Type
	-20 ... 50 °C	150 g	549906	MH-2-24VDC-PA
			549908	MH-2-230VAC-PA
			549907	MH-2-110VAC-PA

Plug socket			
	Description	Part no.	Type
	3-pin, square design, plug pattern according to EN 175301-803 form A	550067	MSSD-N