
Vacuum generator VADM-200-P Part number: 162520





Data sheet

| Feature | Value | |
|-----------------------------------------------|--------------------------------------------------------|--|
| Nominal size, Laval nozzle | 2 mm | |
| Grid dimension | 22 mm | |
| Silencer design | Closed | |
| Mounting position | optional | |
| Ejector characteristic | High vacuum | |
| Grade of filtration | 40 µm | |
| Manual override | Non-detenting | |
| Integrated function | Electric on-off valve Filter Vacuum switch | |
| Measured variable | Relative pressure | |
| Measuring principle | Piezoresistive | |
| Switching element function | N/O contact | |
| Switching function | Threshold value comparator | |
| Valve function | Closed | |
| Reverse polarity protection | For all electrical connections | |
| Display type | LED | |
| Setting range hysteresis | -50 kPa5 kPa -0.5 bar0.05 bar -7.25 psi0.725 psi | |
| Setting options | Potentiometer | |
| Switching status indication | Optical | |
| Setting range threshold value | -90 kPa0 kPa -0.9 bar0 bar -13.05 psi0 psi | |
| Operating pressure | 0.2 MPa0.8 MPa 2 bar8 bar 29 psi116 psi | |
| Max. vacuum | 85 % | |
| Nominal operating pressure | 0.6 MPa 6 bar 87 psi | |
| Air supply time at nominal operating pressure | 0.29 s | |

FESTO

| Feature | Value |
|-----------------------------------------|---------------------------------------------------|
| Operational voltage range DC | 21.6 V26.4 V |
| Duty cycle | 100% |
| Switching output | PNP |
| Approval | RCM trademark c UL us - Recognized (OL) |
| CE mark (see declaration of conformity) | To EU EMC Directive |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation not possible |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Media temperature | 0 °C60 °C |
| Degree of protection | IP65 |
| Ambient temperature | 0 °C50 °C |
| Product weight | 330 g |
| Pressure measuring range | 0 MPa0.1 MPa 0 bar1 bar 0 psi14.5 psi |
| Electrical connection | 4-pin M8x1 Plugs |
| Type of mounting | With through-hole Via female thread Either: |
| Pneumatic connection, port 1 | G1/4 |
| Pneumatic connection, port 3 | Integrated silencer |
| Vacuum connection | G3/8 |
| Note on materials | RoHS-compliant |
| Material seals | NBR |
| Material receiver nozzle | Brass, nickel-plated |
| Material filter | PA |
| Material filter housing | PC |
| Material housing | Wrought aluminium alloy |
| Material silencer | PE POM |
| Material piston | POM |
| Material transmitter nozzle | Nickel-plated brass |