

# Valve terminal CPV14-VI

Part number: 18210

**FESTO**



## Data sheet

Feature	Value
Electrical control	AS-Interface CPI installation system Individual connection Fieldbus Multi-pin plug
Electrical I/O system	yes
Terminal type	10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Media temperature	-5 °C...50 °C
Ambient temperature	-5 °C...50 °C
Storage temperature	-20 °C...40 °C
Degree of protection	IP65
Corrosion resistance class CRC	1 - Low corrosion stress 2 - Moderate corrosion stress
Operating pressure	-0.09 MPa...1 MPa -0.9 bar...10 bar
Note on operating pressure	0 - 0.8 MPa with ext. pilot air 0 - 8 bar with external pilot air
Pilot pressure	0.3 MPa...8 MPa 3 bar...80 bar
LABS (PWIS) conformity	VDMA24364-B1/B2-L
CE mark (see declaration of conformity)	To EU EMC Directive To EU Explosion Protection Directive (ATEX) In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK EX instructions To UK RoHS instructions
KC mark	KC-EMV
Approval	RCM trademark c UL us - Recognized (OL)
Explosion protection	Class I, Div. 2 (US) Zone 2 (ATEX) Zone 2 (UKEX)
ATEX category gas	II 3G

Feature	Value
Explosion protection certification outside the EU	EPL Gc (GB) NEC 500 Class I, Div. 2
Explosion ignition protection type for gas	Ex ec IIC T4 Gc X
Explosion ambient temperature	-5 °C ≤ Ta ≤ +50 °C
Note on materials	RoHS-compliant
Valve terminal structure	Fixed grid
Max. number of valve positions	8
Max. number of valve functions	16
Max. number of pressure zones	2
Type of actuation	Electric
Valve function	2x2/2-way, monostable, closed 2x2/2-way, open/closed, monostable 2x3/2-way, monostable, closed 2x3/2-way, open, monostable 2x3/2-way, open/closed, monostable 5/2 double solenoid 5/2-way, monostable Vacuum generator Vacuum generator + 2/2-way, closed, monostable
Design	Piston gate valve
Sealing principle	Soft
Valve size	14 mm
Pilot air supply	External Internal
Max. standard nominal flow rate	800 l/min at 14 mm
Nominal size	6 mm
Suitability for vacuum	yes
pneumatic working port	G1/8 QS-6 QS-8 QS-1/8 QS-1/4
Pneumatic connection, port 1	Common line
Pneumatic connection, port 2	G1/8
Pneumatic connection, port 3	Common line
Pneumatic connection, port 4	G1/8
Pilot air port 12/14	Common line
Pilot exhaust port 82/84	Common line
Signal status display	LED
Nominal operating voltage DC	24 V