

# Filter regulator MS6N-LFR-1/4-D7-CUM-AS

Part number: 531317

FESTO



## Data sheet

| Feature   | Value   |
|---|---|
| Size  | 6   |
| Series  | MS  |
| Actuator lock   | Rotary knob with detent<br>can be closed with accessories |
| Mounting position                                     | Vertical +/-5°  |
| Grade of filtration                                   | 5 µm  |
| Condensate drain                                      | Manually rotating   |
| Design  | Filter regulator with pressure gauge                      |
| Max. condensate volume                                | 38 ml   |
| Controller function                                   | Output pressure constant<br>With secondary venting        |
| Bowl guard  | Integrated as metal bowl                                  |
| Degree of condensate separation                       | 75 %  |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | With pressure gauge                                       |
| Operating pressure                                    | 0.08 MPa...2 MPa<br>0.8 bar...20 bar                      |
| Pressure regulation range                             | 0.5 bar...12 bar  |
| Max. pressure hysteresis                              | 0.025 MPa<br>0.25 bar<br>3.625 psi                        |
| Standard nominal flow rate (standardised to DIN 1343) | 2200 l/min  |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [-:4:-]<br>Inert gases  |
| Corrosion resistance class CRC                        | 2 - Moderate corrosion stress                             |
| LABS (PWIS) conformity                                | VDMA24364-B1/B2-L   |
| Storage temperature                                   | -10 °C...60 °C  |
| Suitable for use with food                            | See supplementary material information                    |
| Air purity class at output                            | Compressed air to ISO 8573-1:2010 [6:4:4]                 |
| Media temperature                                     | -10 °C...60 °C  |
| Ambient temperature                                   | -10 °C...60 °C  |
| Pore size   | 5 µm  |
| Product weight  | 1087 g  |

| Feature                      | Value   |
|------------------------------|---|
| Type of mounting             | Front panel mounting<br>In-line installation<br>With accessories<br>Either: |
| Pneumatic connection, port 1 | 1/4 NPT   |
| Pneumatic connection, port 2 | 1/4 NPT   |
| Note on materials            | RoHS-compliant  |
| Material control panel       | PA<br>POM   |
| Material seals               | NBR   |
| Material filter              | PE  |
| Material housing             | Die-cast aluminium  |
| Material membrane            | NBR   |
| Material bowl                | Wrought aluminium alloy   |
| Material separating plate    | POM   |