

# Compact cylinder ADN-100-60-I-P-A

Part number: 536391

**FESTO**



## Data sheet

| Feature  | Value  |
|--|--|
| Stroke   | 60 mm  |
| Piston diameter  | 100 mm   |
| Piston rod thread  | M12  |
| Cushioning   | Elastic cushioning rings/plates at both ends   |
| Mounting position  | optional   |
| Conforms to standard   | ISO 21287  |
| Piston-rod end   | Female thread  |
| Position detection   | Via proximity switch   |
| Variants   | Piston rod at one end  |
| Operating pressure   | 0.06 MPa...1 MPa<br>0.6 bar...10 bar   |
| Mode of operation  | Double-acting  |
| Operating medium   | Compressed air to ISO 8573-1:2010 [7:4:4]  |
| Note on operating and pilot medium                           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                               | 2 - Moderate corrosion stress  |
| LABS (PWIS) conformity                                       | VDMA24364-B1/B2-L  |
| Ambient temperature  | -20 °C...80 °C   |
| Impact energy in end positions                               | 2.5 J  |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke  | 4524 N   |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 4712 N   |
| Moving mass  | 566 g  |
| Product weight   | 2154 g   |
| Type of mounting   | With through-hole<br>Via female thread<br>With accessories<br>Either:                      |
| Pneumatic connection   | G1/8   |
| Note on materials  | RoHS-compliant   |
| Material collar screws                                       | Steel  |
| Material cover   | Die-cast aluminium, coated   |
| Material seals   | TPE-U(PUR)   |
| Material piston rod  | High-alloy steel   |

| Feature                  | Value                                   |
|--------------------------|---|
| Material cylinder barrel | Smooth-anodised wrought aluminium alloy |