

Compact cylinder

ADN-1 5/8"-1 1/4"-I-P-A

Part number: 557113

FESTO



Data sheet

| Feature | Value |
|--|--|
| Stroke | 1.25 in |
| Piston diameter | 1 5/8" |
| Piston rod thread | 5/16-24 UNF-2B |
| Based on standard | ISO 21287 |
| Cushioning | Elastic cushioning rings/plates at both ends |
| Mounting position | optional |
| Mode of operation | Double-acting |
| Piston-rod end | Female thread |
| Design | Piston Piston rod Profile barrel |
| Position detection | Via proximity switch |
| Variants | Piston rod at one end |
| Operating pressure | 0.1 MPa...1 MPa 1 bar...10 bar 14.5 psi...145 psi |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -4 °F...176 °F |
| Impact energy in end positions | 0.516 ft-lbf |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke | 154 lbf |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 170 lbf |
| Moving mass for 0 mm stroke | 2.83 oz |
| Additional moving mass per 10 mm stroke | 1.31 oz |
| Basic weight for 0 mm stroke | 12.2 oz |
| Additional weight per 10 mm stroke | 0.319 oz |
| Type of mounting | With through-hole Via female thread With accessories Either: |
| Pneumatic connection | 1/8 NPT |

| Feature | Value |
|--------------------------|---|
| Material collar screws | Steel |
| Material cover | Anodised wrought aluminium alloy |
| Material dynamic seals | TPE-U(PU) |
| Material piston rod | High-alloy steel |
| Material cylinder barrel | Smooth-anodised wrought aluminium alloy |