
Pressure sensor SPAW-B2R-G14F-2PA-M12 Part number: 8022776

FESTO





Data sheet

c mark (see declaration of conformity) Take an attenuate a surred variable assured variable assurement method rt value for pressure measuring range value for pressure measuring range output out	CCM trademark UL us listed (OL) TO EU EMC Directive In accordance with EU RoHS Directive TO UK instructions for EMC TO UK ROHS instructions ROHS-compliant Relative pressure
In CA marking (see declaration of conformity) To T	n accordance with EU RoHS Directive TO UK instructions for EMC TO UK ROHS instructions ROHS-compliant
e on materials Resured variable assurement method rt value for pressure measuring range -1 -1 value for pressure measuring range 0. 1 1 1 1	o UK RoHS instructions RoHS-compliant
asured variable asurement method rt value for pressure measuring range -0 -1 -1 value for pressure measuring range 0. 1 1	·
rt value for pressure measuring range -1 value for pressure measuring range 0. value for pressure measuring range 1 1	Polativo proceuro
rt value for pressure measuring range -1 -1 value for pressure measuring range 0. 1 1	Relative pressure
value for pressure measuring range 0. 1 1.	Piezoresistive pressure sensor
1	0.1 MPa 1 bar 14.5 psi
rload proceuro	o.1 MPa bar 4.5 psi
2	2.2 MPa 2 bar 29 psi
Li	Compressed air to ISO 8573-1:2010 [-:-:-] iquid media Gaseous media
dia temperature -2	20 ℃85 ℃
pient temperature 0	°C80 °C
uracy in ± % FS 1	. %FS
etition accuracy in ± %FS 0.	0.15 %FS
tching output 22	xPNP
tching function Fr	reely programmable
tching element function S	Switchable
c. output current 2	250 mA
logue output 4	- 20 mA
e time 3	B ms
ort circuit current rating ye	
erational voltage range DC 11	res
erse polarity protection Fo	es 5 V35 V

Feature	Value
Electrical connection 1, connection type	Plugs
Electrical connection 1, connector system	M12x1, A-coded to EN 61076-2-101
Electrical connection 1, number of connections/cores	5
Electrical connection 1, type of mounting	Screw-type lock
Type of mounting	Via female thread With accessories
Mounting position	optional
Pneumatic connection	Female thread G1/4
Product weight	230 g
Material housing	ABS High-alloy stainless steel
Material in contact with the medium	High-alloy stainless steel
Display type	4-place alphanumeric LED indicator
Displayable units	MPa bar kPa kg/cm² psi
Switching status indication	Red LED
Setting options	Via display and keys
Protection against tampering	PIN code
Setting range threshold value	0.5 %100 %
Setting range hysteresis	0.5 %99.5 %
Degree of protection	IP65 IP67
Corrosion resistance class CRC	4 - Very high corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III