


Cantilever axis ELCC-TB-KF-60- -

Part number: 8060571

FESTO



Data sheet

Feature	Value
Effective diameter of drive pinion	30.558 mm
Working stroke	50 mm...1300 mm
Size	60
Stroke reserve	0 mm...1300 mm
Toothed-belt pitch	3 mm
Mounting position	optional
Guide	Recirculating ball bearing guide
Design	Electromechanical cantilever axis
Max. acceleration	50 m/s ²
Max. speed	5 m/s
Repetition accuracy	±0.05 mm
Corrosion resistance class CRC	0 - No corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Degree of protection	IP20
Ambient temperature	-10 °C...60 °C
2nd moment of area Iy	240600 mm ⁴
2nd moment of area Iz	304210 mm ⁴
Max. drive torque	5.2 Nm
Max. force Fy	4216 N
Max. force Fz	4119 N
Max. moment Mx	36 Nm
Max. moment My	293 Nm
Max. moment Mz	288 Nm
Max. feed force Fx	300 N
Mass moment of inertia JH per metre of stroke	8.9 kgcm ²
Mass moment of inertia JL per kg of working load	2.3 kgcm ²
Mass moment of inertia JO	5.9 kgcm ²
Feed constant	96 mm/U
Reference service life	5000 km
Lubrication interval dependent on operating distance	1000 km
Moving mass with 0 mm stroke with second drive head	2738 g

Feature	Value
Moving mass for 0 mm stroke	1636 g
Additional moving mass per 10 mm stroke	38 g
Weight of additional slide	805 g
Basic weight for 0 mm stroke	4146 g
Additional weight per 10 mm stroke	38 g
Basic weight for 0 mm stroke with 2nd drive head	6053 g
Material end cap	Anodised wrought aluminium alloy
Material profile	Anodised wrought aluminium alloy
Note on materials	RoHS-compliant
Material drive head	Anodised wrought aluminium alloy
Material guide rail	Rolled steel, Corrotect coated
Material housing	High-alloy stainless steel
Material slide	Anodised die-cast aluminium
Material toothed belt clamping piece	Anodised wrought aluminium alloy
Material toothed belt	Polychloroprene with glass filament and nylon coating PUR with steel cord and fabric sheathing Polyurethane with steel cord