


Filter regulator PCRI-100-F90-12-C-T3

Part number: 8141656

FESTO



Data sheet

Feature	Value
Actuator lock	Rotary knob with detent
Mounting position	optional
Grade of filtration	5 µm
Condensate drain	None
Design	Sub-base valve Directly actuated diaphragm regulator
Controller function	Output pressure constant Via primary pressure compensation With secondary venting
Pressure gauge (ANALOG) or Pressure display (DIGITAL)	Prepared for G1/4
Operating pressure	0.1 MPa...0.9 MPa 1 bar...9 bar
Pressure regulation range	0.5 bar...8 bar
Max. pressure hysteresis	0.025 MPa 0.25 bar 3.625 psi
Standard nominal flow rate (standardised to DIN 1343)	1400 l/min
Explosion protection	Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Operating medium	Compressed air to ISO 8573-1:2010 [-:7:-] Inert gases
Note on operating and pilot medium	Lubricated operation not possible
Corrosion resistance class CRC	3 - high corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Air purity class at output	Compressed air to ISO 8573-1:2010 [6:7:-] Inert gases
Media temperature	-40 °C...80 °C
Ambient temperature	-40 °C...80 °C
Product weight	1950 g
Pneumatic connection	Sub-base design, airing
Note on materials	RoHS-compliant
Material cover	Smooth-anodised wrought aluminium alloy (20 µm)

Feature	Value
Material seals	EPDM NBR
Material rotary knob	POM
Material spring	Spring steel
Material filter	PE
Material housing	Smooth-anodised wrought aluminium alloy (20 µm)
Material screws	High-alloy stainless steel