

Solenoid valve

MHA1-M5H-3/2G-0,6-TC

Part number: 197004

FESTO

manifold block valve for individual and battery mounting, particularly small design, with plug connection at top.



Data sheet

| Feature | Value |
|---|--|
| Valve function | 3/2 closed, monostable |
| Type of actuation | electrical |
| Width | 10 mm |
| Standard nominal flow rate | 10 l/min |
| Operating pressure MPa | 0 ... 0.8 MPa |
| Working pressure | 0 ... 8 bar |
| Operating pressure | 0 ... 116 psi |
| Design structure | Poppet valve with spring return |
| Type of reset | mechanical spring |
| Protection class | IP40 |
| Authorization | c UL us - Recognized (OL) |
| Certificate issuing department | UL MH19482 |
| Nominal size | 0.65 mm |
| Grid dimension | 10 mm |
| Exhaust-air function | throttleable |
| Sealing principle | soft |
| Assembly position | Any |
| Manual override | Pushing |
| Type of piloting | direct |
| Flow direction | non reversible |
| Valve position identification | Label |
| Lap | Underlap |
| Note on forced dynamisation | Switching frequency at least once a week |
| Maximum switching frequency | 20 Hz |
| Switching time off | 4 ms |
| Switching time on | 4 ms |
| Duty cycle | 100 % |
| Electrical power consumption | 1 W |
| Characteristic coil data | 12 V DC: 1 W |
| Permissible voltage fluctuation | +/- 10 % |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Vibration resistance | Transport application test at severity level 2 in accordance with FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| PWIS conformity | VDMA24364-B2-L |
| Storage temperature | -20 ... 60 °C |
| Medium temperature | -5 ... 40 °C |
| Ambient temperature | -5 ... 40 °C |
| Product weight | 10 g |

| Feature | Value |
|------------------------------|---------------------------------|
| Electrical connection | Plug |
| Mounting type | On subbase with through hole |
| Pneumatic connection, port 1 | Subbase |
| Pneumatic connection, port 2 | Subbase |
| Pneumatic connection, port 3 | Subbase |
| Materials note | Conforms to RoHS |
| Material seals | FPM HNBR NBR |
| Material housing | PA-reinforced PPS-reinforced |