


# Round cylinder DSNU-S-8-40-P-A-MQ

Part number: 5205903

FESTO



## Data sheet

| Feature  | Value   |
|--|---|
| Stroke   | 40 mm   |
| Piston diameter  | 8 mm  |
| Piston rod thread  | M4  |
| Cushioning   | P: Flexible cushioning rings/plates at both ends                            |
| Assembly position  | Any   |
| Design structure   | Piston<br>Piston rod<br>Cylinder barrel                                     |
| Position detection                                       | For proximity sensor  |
| Operating pressure MPa                                   | 0.15 ... 1 MPa  |
| Working pressure   | 1.5 ... 10 bar  |
| Mode of operation  | double-acting   |
| Operating medium   | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                    |
| Note on operating and pilot medium                       | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC                  | 2 - Moderate corrosion stress   |
| PWIS conformity  | VDMA24364-B2-L  |
| Cleanroom class  | ISO class 6   |
| Ambient temperature                                      | -20 ... 80 °C   |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), retracting | 22.6 N  |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance    | 30.2 N  |
| Moving mass with 0 mm stroke                             | 6.3 g   |
| Additional mass factor per 10 mm of stroke               | 1 g   |
| Basic weight for 0 mm stroke                             | 20 g  |
| Additional weight per 10 mm stroke                       | 2.4 g   |
| Mounting type  | with accessories  |
| Pneumatic connection                                     | M5  |
| Materials note   | Conforms to RoHS  |
| Material cover   | Anodised wrought aluminium alloy  |
| Material seals   | TPE-U(PU)   |
| Material piston rod                                      | High alloy steel, non-corrosive   |
| Material cylinder barrel                                 | High alloy steel, non-corrosive   |