


# pancake cylinder DPCB-N-...-4"- -

Part number: 8104886



Exemplary representation

## Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Stroke	0.125 ... 4 "
Piston diameter	4"
Piston rod thread	3/4-16 UNF-2B 3/4-16 UNF-2A 3/4-10 UNC-2B 3/4-10 UNC-2A
Cushioning	No cushioning P: Flexible cushioning rings/plates at both ends Elastic cushioning rings/plates, at front Elastic cushioning rings/plates, at rear
Assembly position	Any
Mode of operation	double-acting
Piston-rod end	Male thread Female thread No thread
Design structure	Piston Piston rod Cylinder barrel
Position detection	For proximity sensor
Variants	Increased chemical resistance Extended piston rod Low-friction Through piston rod Through, hollow piston rod Temperature range -40 - 80 °C Scraper made of NBR Reinforced end cap Quadratic lid shape With sensor mounting rail with sensor fastening rail rotated 90° with sensor fastening rail rotated 180° with sensor fastening rail rotated 270° Compressed air connection, rotated 90° Compressed air connection, rotated 180° Compressed air connection, rotated 270°
Protection against torque/guide	Double piston rod with end plate Double piston rod with end plate rotated 90° Double piston rod with end plate with recess and through-hole Double piston rod with end plate with recess and through-hole rotated 90°
Working pressure	15 ... 150 Psi
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
PWIS conformity	VDMA24364 zone III

Feature	Value
Ambient temperature	-25 ... 221 °F
Product weight	53.47 ... 69.5 Pound
Mounting type	Threaded direct mounting on end cap Threaded direct mounting on bearing cap Threaded direct mounting on both sides with swivelling rod eye on end cap rotated 90° with swivelling rod eye on end cap With through-hole on end cap With through-hole on bearing cap With through-hole on both sides With threaded flange on bearing cap With trunnion mounting on end cap With trunnion mounting on bearing cap with accessories Optional
Pneumatic connection	Female thread 1/8 NPT
Materials note	Conforms to RoHS
Material cover	Wrought Aluminum alloy
Material of dynamic seals	FPM NBR
Material piston rod	high-alloy stainless steel, hard chrome plated
Material cylinder barrel	Reinforced composite material